



FINAL DRAFT International Standard

ISO/FDIS 5530-1

Wheat flour — Physical characteristics of doughs —

Part 1:

Determination of water absorption and rheological properties using a farinograph

Farines de blé tendre — Caractéristiques physiques des pâtes —

*Partie 1: Détermination de l'absorption d'eau et des
caractéristiques rhéologiques au moyen du farinographe*

ISO/TC 34/SC 4

Secretariat: **SAC**

Voting begins on:

2025-09-08

Voting terminates on:

2025-12-01

ISO/CEN PARALLEL PROCESSING

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO/FDIS 5530-1

<https://standards.iteh.ai/catalog/standards/iso/f3a3eb9f-4289-4026-9342-d6e3ccb294b3/iso-fdis-5530-1>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2025

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	3
5 Reagent	3
6 Apparatus	3
7 Sampling	4
8 Procedure	4
8.1 Determination of the moisture content of the flour	4
8.2 Preparation of the farinograph	4
8.3 Test portion	5
8.3.1 General	5
8.3.2 Constant flour mass procedure	5
8.3.3 Constant dough mass procedure	7
8.4 Common rules of determination	8
9 Evaluation of the farinogram and calculation of the derived rheological characteristics	9
9.1 General	9
9.2 Water absorption of flour	9
9.3 Characteristics relating to the consistency of dough	10
10 Precision	11
10.1 Interlaboratory tests	11
10.2 Repeatability	11
10.3 Reproducibility	12
10.4 Comparison of two groups of measurements in two laboratories	12
11 Test report	13
Annex A (informative) Description of the farinograph	14
Annex B (informative) Examples of farinogram types	19
Annex C (informative) Results of interlaboratory test	25
Annex D (informative) Critical difference data	34
Bibliography	36

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 34, *Food products*, Subcommittee SC 4, *Cereals and pulses*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 338, *Cereal and cereal products*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This fifth edition cancels and replaces the fourth edition (ISO 5530-1:2025), of which it constitutes a minor revision.

The changes are as follows:

- the values in [B.5.1](#) have been modified.

A list of all parts in the ISO 5530 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Wheat flour — Physical characteristics of doughs —

Part 1:

Determination of water absorption and rheological properties using a farinograph

1 Scope

This document specifies a method using a farinograph for the determination of the water absorption of flours and the mixing behaviour of doughs made from them by a constant flour mass procedure or by a constant dough mass procedure.

The method is applicable to experimental and commercial flours from wheat (*Triticum aestivum* L.).

NOTE This document is related to ICC 115/1^[5] and AACC Method 54-21.02^[6].

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 712-1, *Cereals and cereal products — Determination of moisture content — Part 1: Reference method*

ISO 3696, *Water for analytical laboratory use — Specification and test methods*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1 consistency

resistance of a dough to being mixed in specific conditions

Note 1 to entry: For the purposes of this document, consistency refers to the resistance of dough being mixed in a farinograph under the conditions specified in the methodology.

Note 2 to entry: It is expressed in *farinograph unit (FU)* (3.2).

Note 3 to entry: Specific conditions include mixing conditions, temperature, hydration, etc.

3.2 farinograph unit FU

arbitrary unit used for *consistency* (3.1) on the farinogram

Note 1 to entry: For the mathematical expression of FU, see 6.1.

Note 2 to entry: It is also possible to define an FU as a torque expressed in Nm, measured in the axis of the mixer.

3.3

maximum consistency

consistency (3.1) measured at the end of the *dough development time* (3.5)

Note 1 to entry: For the mathematical expression of maximum consistency, see 9.3.

Note 2 to entry: It is expressed in *farinograph unit (FU)* (3.2).

3.4

water absorption of flour

Wa

volume of water required to produce a dough with a *maximum consistency* (3.3) of 500 *farinograph unit (FU)* (3.2) under the specified operating conditions

Note 1 to entry: Water absorption is expressed in millilitres per 100 g of flour at 14 % (mass fraction) moisture content to an accuracy of 0,1 ml.

Note 2 to entry: Water absorption can also be expressed in % (ml per 100 g).

3.5

dough development time

DDT

DEPRECATED: peak time

time from the beginning of the addition of water to the point on the curve immediately before the first sign of the decrease of *maximum consistency* (3.3)

Note 1 to entry: In cases where two peaks are observed, the second peak shall be used to measure the DDT.

Note 2 to entry: See [Figure 1](#) and 9.3.

Note 3 to entry: It is expressed in minutes to the nearest 0,1 min.

3.6

stability

difference in time between the point where the top part of the curve intercepts, for the first time, the line of 500 *farinograph unit (FU)* (3.2) and the last point where leaves this line

Note 1 to entry: This value measures the tolerance of the flour to mixing.

Note 2 to entry: When the *maximum consistency* (3.3) of a peak curve deviates from the 500 FU line, the line of this consistency should be used to read the interceptions (see also [B.5.2](#)).

Note 3 to entry: The stability is expressed in minutes, to an accuracy of 0,5 min.

3.7

degree of softening

difference between the height of the centre of the curve at the point where it begins to decline (*dough development time* (3.5)) and the height of the centre of the curve 12 min after that point

Note 1 to entry: It is expressed in *farinograph unit (FU)* (3.2).

Note 2 to entry: In cases where two peaks appear, the second peak is considered to determine the degree of softening.

Note 3 to entry: The degree of softening should be expressed to the nearest 5 farinograph unit (FU).

Note 4 to entry: This definition is equivalent to ICC 115/1^[5].