
**Identification cards — Test methods —
Part 2:
Cards with magnetic stripes**

*Cartes d'identification — Méthodes d'essai —
Partie 2: Cartes à bandeaux magnétiques*

Sample Document

get full document from standards.iteh.ai

Sample Document

get full document from standards.iteh.ai



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2015

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

	Page
Foreword.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	2
4 Default items applicable to the test methods.....	4
4.1 Test environment.....	4
4.2 Pre-conditioning.....	4
4.3 Selection of test methods.....	4
4.4 Default tolerance.....	4
4.5 Total measurement uncertainty.....	4
5 Test methods.....	5
5.1 Magnetic stripe area warpage.....	5
5.1.1 Apparatus.....	5
5.1.2 Procedure.....	5
5.1.3 Test report.....	6
5.2 Height and surface profile of the magnetic stripe.....	6
5.2.1 Apparatus.....	6
5.2.2 Procedure.....	7
5.2.3 Expression of results.....	8
5.2.4 Test report.....	10
5.3 Surface roughness of the magnetic stripe.....	10
5.3.1 Procedure.....	11
5.3.2 Test report.....	11
5.4 Wear test for magnetic stripe.....	11
5.4.1 Apparatus.....	11
5.4.2 Procedure.....	11
5.4.3 Test report.....	12
5.5 Amplitude measurements.....	13
5.5.1 Calibration reference.....	13
5.5.2 Apparatus.....	13
5.5.3 Procedure.....	18
5.5.4 Test report.....	20
5.6 Flux transition spacing variation.....	20
5.6.1 Apparatus.....	20
5.6.2 Procedure.....	21
5.6.3 Test report.....	21
5.7 Magnetic stripe adhesion.....	21
5.7.1 Apparatus.....	21
5.7.2 Procedure.....	21
5.7.3 Test report.....	22
5.8 Static magnetic characteristics.....	22
5.8.1 Apparatus.....	22
5.8.2 Procedure.....	23
5.8.3 Test report.....	24
5.9 Waveform U_{i6}	24
5.9.1 Apparatus.....	24
5.9.2 Procedure.....	24
5.9.3 Test report.....	25
5.10 High coercivity, high density over-write.....	25
5.10.1 Apparatus.....	25
5.10.2 Test method.....	25
5.10.3 Test report.....	25

Annex A (informative) Effects of wear on test heads and the use of wear resistant test heads	26
---	-----------

Sample Document

get full document from standards.iteh.ai

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 10373-2 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 17, *Cards and personal identification*.

This third edition cancels and replaces the second edition (ISO/IEC 10373-2:2006), which has been technically revised. It also incorporates the Technical Corrigendum ISO/IEC 10373-2:2006/Cor1:2010.

The user is encouraged to review the entire standard for revisions and updates. The major changes made during this revision are listed below.

- References to ISO/IEC 7811-8 and ISO/IEC 8484 were added.
- Calibration of reference current for ISO/IEC 7811-2 has been added. This will result in a small offset in requirements from the existing 2006 edition but will be equivalent to the requirements as written originally.
- Test densities of 500 ftpi have been changed to 508 ftpi to more closely agree with actual values used.
- Requirements that are different for different base standards have been moved into tables in most cases.
- In [5.5.2.3](#), Note 2 contained a normative requirement so it was moved out of note.
- The 2 cases of [Figure 14](#) have been combined and a table was given. Conflicting symmetry requirements were resolved by taking $T1 = T2 \pm 0,02 T1$.
- Description of correcting reference values was clarified and terms were deleted since these were not used. Reference to older editions of base standards was deleted.
- Contents of the technical corrigendum have been incorporated.

ISO/IEC 10373 consists of the following parts, under the general title *Identification cards — Test methods*:

- *Part 1: General characteristics*
- *Part 2: Cards with magnetic stripes*
- *Part 3: Integrated circuit cards with contacts and related interface devices*
- *Part 5: Optical memory cards*
- *Part 6: Proximity cards*

- *Part 7: Vicinity cards*
- *Part 8: USB-ICC*
- *Part 9: Optical memory cards — Holographic recording method*

Sample Document

get full document from standards.iteh.ai

Identification cards — Test methods —

Part 2: Cards with magnetic stripes

1 Scope

ISO/IEC 10373 defines test methods for characteristics of identification cards according to the definition given in ISO/IEC 7810. Each test method is cross-referenced to one or more base standards, for example ISO/IEC 7810, or one or more of the supplementary standards that define the information storage technologies employed in identification card applications.

This part of ISO/IEC 10373 defines test methods which are specific to magnetic stripe technology.

NOTE 1 Criteria for acceptability do not form part of this part of ISO/IEC 10373 but will be found in the International Standards mentioned above.

NOTE 2 Test methods described in this part of ISO/IEC 10373 are intended to be performed separately. A given card is not required to pass through all the tests sequentially.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1302, *Geometrical Product Specifications (GPS) — Indication of surface texture in technical product documentation*

ISO 2409, *Paints and varnishes — Cross-cut test*

ISO 3274, *Geometrical Product Specifications (GPS) — Surface texture: Profile method — Nominal characteristics of contact (stylus) instruments*

ISO 4288, *Geometrical Product Specifications (GPS) — Surface texture: Profile method — Rules and procedures for the assessment of surface texture*

ISO/IEC 7810, *Identification cards — Physical characteristics*

ISO/IEC 7811-2, *Identification cards — Recording technique — Part 2: Magnetic stripe — Low coercivity*

ISO/IEC 7811-6, *Identification cards — Recording technique — Part 6: Magnetic stripe — High coercivity*

ISO/IEC 7811-7, *Identification cards — Recording technique — Part 7: Magnetic stripe — High coercivity, high density*

ISO/IEC 7811-8, *Identification cards — Recording technique — Part 8: Magnetic stripe — Coercivity of 51,7 kA/m (650 Oe)*

ISO/IEC 8484, *Information technology — Magnetic stripes on savingsbooks*

IEC 60454-2, *Pressure-sensitive adhesive tapes for electrical purposes — Part 2: Methods of test*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

NOTE Static magnetic characteristics definitions were originally derived from IEC 50-221 (which has been replaced by IEC 60050-221) and ISO 31-5:1992 (which has been replaced by IEC 80000-6).

3.1 test method

method for testing characteristics of identification cards for the purpose of confirming their compliance with International Standards

3.2 testably functional

has survived the action of some potentially destructive influence to the extent that

- a) any magnetic stripe present on the card shows a relationship between signal amplitudes before and after exposure that is in accordance with the base standard
- b) any integrated circuit(s) present in the card continue to show an Answer to Reset response¹⁾ which conforms to the base standard
- c) any contacts associated with any integrated circuit(s) present in the card continue to show electrical resistance and impedance which conform to the base standard
- d) any optical memory present in the card continues to show optical characteristics which conform to the base standard
- e) any contactless integrated circuit(s) in the card continue to operate as intended

3.3 warpage

deviation from flatness

3.4 flux transitions per millimetre ft/mm

linear recording density applied to a track on a magnetic stripe

3.5 recording

creating a track of flux reversals according to a test method given in this part of ISO/IEC 10373, with the values of all applicable test parameters specified

3.6 encoding

creating a track of flux reversals whose spacing is modified, according to a coding scheme, to represent data

3.7 surface roughness

surface topology of an area of surface, qualified in the International Standards by reference to various resolution determinants and methods of calculation

3.8 amplitude measurements

(magnetic stripe) measurement of read-back signal amplitude according to a test method given in this part of ISO/IEC 10373, with the values of all applicable test parameters specified

1) This part of ISO/IEC 10373 does not define any test to establish the complete functioning of integrated circuit(s) cards. The test methods require only that the minimum functionality (testably functional) be verified. This can, in appropriate circumstances, be supplemented by further application-specific functionality criteria which are not available in the general case.

3.9**flux transition spacing variation**

deviation from nominal of measured values of the distance between adjacent flux transitions along a line parallel to the centreline of the encoded track

3.10**magnetic stripe adhesion**

strength of the bond between the magnetic stripe and the card

3.11**normal use**

use as an identification card according to ISO/IEC 7810, involving equipment processes appropriate to the card technology and storage as a personal document between equipment processes

3.12**static saturation $M(H)$ loop**

normal hysteresis loop for which the magnetic field strength is cycled between the extremes $-H_{\max}$ to $+H_{\max}$ at such a low rate of change that the loop is not influenced by the rate of change

3.13**coercivity**

$$H'_{cM} = H'_{cJ}$$

continuously applied magnetic field which reduces the magnetization to zero from a previously saturated state in the opposite direction, measured parallel to the longitudinal axis of the stripe

3.14**remanent coercivity**

$$H_r$$

applied magnetic field which when removed returns the material to a zero magnetization state from a previously saturated state in the opposite direction, measured parallel to the longitudinal axis of the stripe

3.15**Oersted****Oe**

Gaussian CGS unit of magnetic field strength which is commonly used in the magnetic recording industry, equal to approximately 79,578 A/m

3.16**static demagnetization** **S_{160}**

reduction in magnetization under the influence of an opposing magnetic field; characterised by $[M_r - M^+(-160)] \div M_r$; the average slope of the "demagnetization" quadrant of the static saturation $M(H)$ loop between magnetic field strength values of $H = 0$ and $H = -160$ kA/m

3.17**squareness** **SQ**

ratio of M_r , the value of magnetization (M) at zero magnetic field strength ($H = 0$), to $M(H_{\max})$, the value of magnetization at $H_{\max}$ obtained from the static saturation $M(H)$ loop

3.18**longitudinal squareness** **$SQ_{||}$**

squareness of the medium measured parallel to the longitudinal axis of the magnetic stripe

3.19**perpendicular squareness** **$SQ_{\perp}$**

squareness of the medium measured perpendicular to the plane of the magnetic stripe