

INTERNATIONAL STANDARD



**Information technology – Home electronic system (HES) architecture –
Part 5-8: Intelligent grouping and resource sharing for HES Class 2 and Class 3 –
Remote access core protocol**

get full document from standards.iteh.ai



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2017 ISO/IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about ISO/IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

INTERNATIONAL STANDARD



**Information technology – Home electronic system (HES) architecture –
Part 5-8: Intelligent grouping and resource sharing for HES Class 2 and Class 3 –
Remote access core protocol**

get full document from standards.iteh.ai

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 35.200; 35.240.67

ISBN 978-2-8322-4693-1

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	5
1 Scope.....	7
2 Normative references	7
3 Terms, definitions and abbreviated terms	8
3.1 Terms and definitions.....	8
3.2 Abbreviated terms.....	10
4 Conformance.....	11
5 IGRS RA overview.....	11
6 IGRS RA service functional flow	11
7 Registration management.....	13
7.1 User or device registration flow.....	13
7.2 User registration management	14
7.3 Device registration management.....	14
7.4 Registration response status code	15
8 Login.....	15
8.1 User or device login flow.....	15
8.2 User connection.....	16
8.3 Messages for user connection ID binding.....	16
8.4 Device connection.....	17
8.5 Messages for device connection ID binding.....	17
9 Device access rights configuration.....	18
9.1 Overview.....	18
9.2 Messages for device access rights configuration request.....	18
9.3 Messages for device access rights configuration response	19
10 User and device relationship management.....	20
10.1 Overview.....	20
10.2 Relationship management mechanism	23
10.3 Relationship establishment	24
10.3.1 Messages for relationship establishment request.....	24
10.3.2 Relationship establishment request procedure for IRSP.....	24
10.3.3 Target accepts or rejects relationship establishment request	25
10.3.4 IRSP processes relationship establishment acceptance message from target.....	26
10.4 Releasing relationship.....	27
10.5 Device verification code management	28
10.5.1 Device verification code management initiated by IGRS RA user	28
10.5.2 Device verification code management initiated by IGRS RA device.....	29
11 Message exchange.....	30
11.1 Overview.....	30
11.2 User or device ↔ User or device message exchange that needs response	30
11.3 User or device ↔ User or device message exchange that does not need response.....	31
11.4 User or device ↔ IRSP message exchange	32
11.5 IGRS RA server pushes message to user or device	32
11.6 IGRS RA NAT traversal.....	33

11.7	Message exchange mode	34
11.7.1	Overview	34
11.7.2	Message exchange of “point-to-point” and “point-to- multiple-point”	35
11.7.3	Message exchange of “instant transmission” and “offline storage”	35
12	Logout	35
13	User and device discovery and online status management	36
14	Security	38
	Bibliography	39
	Figure 1 – Typical flow of IGRS RA service	12
	Figure 2 – IGRS RA user or device registration flow	13
	Figure 3 – IGRS RA User or Device Login Flow	16
	Figure 4 – Flow of relationship establishment request which needs approval from target	20
	Figure 5 – Flow of relationship establishment request which does not need approval from target	20
	Figure 6 – IGRS RA Relationships	22
	Figure 7 – Flow of relationship releasing	27
	Figure 8 – Flow of message exchange between user or device and user or device that needs response	30
	Figure 9 – Flow of message exchange between user or device and user or device that does not need response	31
	Figure 10 – Flow of message exchange between user or device and IRSP	32
	Figure 11 – IRSP pushes message to user or device	33
	Figure 12 – IGRS RA NAT traversal mechanism	34
	Figure 13 – Point-to-point message exchange in IGRS RA system	35
	Figure 14 – IGRS RA user or device offline flow	36
	Figure 15 – User and device discovery mechanisms in IGRS RA system	37
	Figure 16 – Non-uniqueness of user addressing	38
	Table 1 – Registration response status code and the contents in the registration response messages	15
	Table 2 – Rules of IRSP processing target relationship establishment acceptance response messages	26

INFORMATION TECHNOLOGY – HOME ELECTRONIC SYSTEM (HES) ARCHITECTURE –

Part 5-8: Intelligent grouping and resource sharing for HES Class 2 and Class 3 – Remote access core protocol

FOREWORD

- 1) ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.
- 2) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees and ISO member bodies.
- 3) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC National Committees and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO, IEC or ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 5) ISO and IEC do not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. ISO or IEC are not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC National Committees or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this ISO/IEC publication may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 14543-5-8 was prepared by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

The list of all currently available parts of the ISO/IEC 14543 series, under the general title *Information technology – Home electronic system (HES) architecture*, can be found on the IEC and ISO websites.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

The ISO/IEC 14543-5 series of standards specifies the services and protocol of the application layer for Intelligent Grouping and Resource Sharing (IGRS) devices and services in the Home Electronic System. Some parts reference Classes 1, 2 and 3, which are HES designations specified in the HES architecture standard, ISO/IEC 14543-2-1.

The ISO/IEC 14543-5 series includes the following parts.

- Part 5-1: Core protocol
 - Specifies the TCP/IP protocol stack as the basis and the HTTP protocol as the message-exchange framework among devices.
 - Specifies a series of device and service interaction/invocation standards, including device and service discovery protocol, device and service description, service invocation, security mechanisms, etc.
 - Specifies core protocols for a type of home network that supports streaming media and other high-speed data transports within a home.
- Parts 5-2#: Application profile
 - Based on the IGRS core protocol.
 - Specifies a device and service interaction mechanism, as well as application interfaces used in IGRS basic applications.
 - Multiple application profiles are specified, including:
 - Part 5-21: AV profile
 - Part 5-22: File profile
- Part 5-3: Basic application
 - Includes an IGRS basic application list.
 - Specifies a basic application framework.
 - Specifies operation details (device grouping, service description template, etc.), function definitions and service invocation interfaces.
- Part 5-4: Device validation
 - Defines a standard method to validate an IGRS-compliant device.
- Part 5-5: Device type
 - Specifies IGRS device types used in IGRS applications.
- Part 5-6: Service type
 - Specifies basic service types used in IGRS applications.
- Part 5-7: Remote access system architecture
 - Specifies the architecture and framework for the remote access of IGRS devices and services in the Home Electronic System. The remote access communications protocol and application profiles are specified in the following parts of ISO/IEC 14543-5:
 - ISO/IEC 14543-5-8: Remote access core protocol
 - ISO/IEC 14543-5-9: Remote access service platform
 - ISO/IEC 14543-5-101: Remote AV access profile
 - ISO/IEC 14543-5-102: Remote universal management profile
 - ISO/IEC 14543-5-11: Remote user interface
 - ISO/IEC 14543-5-12: Remote access test and verification
 - The relationships among these parts are specified in Part 5-7.

- Part 5-8: Remote access core protocol
 - Provides detailed system components, system function modules, basic concepts of IGRS remote access elements and their relationships, message exchange mechanisms and security related specifications.
 - Specifies interfaces between IGRS Remote Access (RA) client and service platforms. Defines co-operative procedures among IGRS RA clients.
- Part 5-9: Remote access service platform
 - Specifies the IGRS RA service platform (IRSP) architectures and interfaces among servers in the service platforms.
 - Based on Part 5-8: Remote access core protocol.
- Parts 5-10#: Remote access application profiles
 - Defines a device and service interaction mechanism for various applications.
 - Based on Part 5-8: Remote access core protocol.
 - Two profiles are under development:
 - Part 5-101: Remote AV access profile.¹ This part defines the common requirements for IGRS RA AV users and devices in IGRS networks.
 - Part 5-102: Remote universal management profile.² This part specifies a mechanism for integrating devices with both relatively high and low processing capabilities into IGRS networks. It also specifies universal remote device discovery and a management framework.
 - Additional application profiles will be specified in the future.
- Part 5-11: Remote user interface³
 - Specifies adaptive user interface generation and remote device control mechanisms suitable for different remote access applications and devices.
- Part 5-12: Remote access test and verification⁴
 - Defines a standard method to test and verify IGRS-RA compliant device and service interfaces.

¹ Under preparation. Stage at the time of publication: ISO/IEC DIS 14543-5-101:2017.

² Under preparation. Stage at the time of publication: ISO/IEC CD 14543-5-102:2016.

³ Under preparation. Stage at the time of publication: ISO/IEC DIS 14543-5-11:2017.

⁴ Under preparation. Stage at the time of publication: ISO/IEC DIS 14543-5-12:2017.

INFORMATION TECHNOLOGY – HOME ELECTRONIC SYSTEM (HES) ARCHITECTURE –

Part 5-8: Intelligent grouping and resource sharing for HES Class 2 and Class 3 – Remote access core protocol

1 Scope

This part of ISO/IEC 14543-5 specifies the core protocol of IGRS user and device remote access, including intelligent grouping and resource sharing. The protocol features are:

- a) IGRS RA user and IGRS RA device concepts and relationship management mechanisms,
- b) user and device remote discovery and online and offline status management mechanisms,
- c) user and device remote access message formats and message exchanging flows, and
- d) remote data and service distribution and sharing mechanisms.

This document is applicable to remote access of an IGRS sub-network (called an IGRS subnet) for resource sharing and service collaboration among home and/or remote computers, consumer electronics and communication devices.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 14543-5-9, *Information technology – Home electronic system (HES) architecture – Part 5-9: Intelligent grouping and resource sharing for HES Class 2 and Class 3 – Remote access service platform*

ISO/IEC 9594-8|Recommendation ITU-T X.509, *Information technology – Open Systems Interconnection – The Directory: Public-key and attribute certificate frameworks*

IETF RFC 2616, *Hypertext Transfer Protocol – HTTP/1.1*

IETF RFC 2818, *HTTP over TLS*

IETF RFC 4422, *Simple Authentication and Security Layer (SASL)*

IETF RFC 5246, *The Transport Layer Security (TLS) Protocol – Version 1.2*

IETF RFC 6120, *Extensible Messaging and Presence Protocol (XMPP): Core*

IETF RFC 6121, *Extensible Messaging and Presence Protocol (XMPP): Instant Messaging and Presence*

IETF RFC 7622, *Extensible Messaging and Presence Protocol (XMPP): Address Format*

3 Terms, definitions and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1.1 binding

relationship established between a user and a device, which represents an own/owned relationship between the user and the device

Note 1 to entry: The user and device with binding relationship are shown in each other's roster. One user can bind multiple devices, and one device can be bound by multiple users.

3.1.2 buddy

relationship established between two users, which represents that the two users trust each other

Note 1 to entry: Two users with buddy relationship are shown in each other's roster.

3.1.3 connection ID

instance identification that identifies the connection between "user and IRSP" and "device and IRSP"

3.1.4 contact group

set of multiple contacts where each has the same attribute

3.1.5 device connection

network connection established between an IGRS RA device and the IRSP

Note 1 to entry: Only one device connection can be maintained at any time. Multiple devices of one user can connect to the IRSP simultaneously.

3.1.6 device connection ID

identification that represents an instance of a connection between an IGRS RA device and the IRSP

EXAMPLE If the device ID is "#igrsdevice@igrs.com" and the connection ID is "home", the device connection ID is "#igrsdevice@igrs.com/home".

Note 1 to entry: A device connection ID is unique. The IRSP tests and guarantees the uniqueness of the device connection ID.

Note 2 to entry: A device connection ID consists of a device ID and a connection ID. A "/" is used to separate these two IDs.

3.1.7 device ID

unique identification of an IGRS RA device

EXAMPLE If the local part of a device ID is "#igrsdevice" and the domain name part of the user ID is "igrs.com", the device ID is "#igrsdevice@igrs.com".

Note 1 to entry: A device ID consists of a local part and a domain name part. A "@" is used to separate the two parts. Each device ID starts with a "#".

3.1.8**device verification code**

string used to examine if the user has the authority to bind a device

Note 1 to entry: For a device without a user interface, the device verification code is used to bind a device to a user. The device owner guarantees the safety of the device verification code.

3.1.9**IGRS RA device**

physical device that is accessible to the IGRS RA user in the IGRS RA system

Note 1 to entry: A binding relationship can be established between an IGRS RA device and an IGRS RA user. A sibling relationship can be established between two IGRS RA devices.

3.1.10**IGRS RA server**

instantiation of a service provider that may be included in an IRSP

Note 1 to entry: An IGRS RA server is deployed on the Internet. It maintains relationships among IGRS RA user and IGRS devices. It also provides re-transmission of collaborative messages. The IGRS RA user and IGRS device can start a data connection to the IRSP and supports interconnections using the data connection and re-transmission functions of the IRSP.

3.1.11**IGRS RA service platform****IRSP**

collection of multiple IGRS RA servers that are deployed on the Internet to maintain the relationships among IGRS RA user and IGRS RA device and to exchange collaborative messages

Note 1 to entry: IGRS RA user and device can establish connections to the IRSP, can send collaborative messages over these connections and can exchange messages in the servers of the IRSP.

3.1.12**IGRS RA user**

entity that uses the IGRS RA devices and application services

Note 1 to entry: Generally, an IGRS RA user is a human being. Each IGRS RA user should have a unique user ID (identification). A bundle relationship can be established between one IGRS RA user and another. A binding relationship can be established between one IGRS RA user and one IGRS device.

3.1.13**interested connection**

connection that logged onto the IRSP using a user ID and requested the roster of that user

3.1.14**roster**

list that stores all users and devices by which this specific user or device is permitted access

Note 1 to entry: A roster is managed by the IRSP. Each user or device has one and only one roster on the IRSP.

3.1.15**roster item**

item in the roster

3.1.16**service ID**

identification of a service

3.1.17

sibling

relationship established between two or more devices, which represents that these devices have a binding relationship with the same user, or these devices belong to the same user

Note 1 to entry: Devices with sibling relationship are shown in each other's roster.

3.1.18

user connection

network connection established between an IGRS RA user and the IRSP

Note 1 to entry: Multiple user connections can be maintained simultaneously for one user.

3.1.19

user connection ID

identification that represents an instance of a connection between an IGRS RA user and the IRSP

EXAMPLE If the user ID is "igrsuser@igrs.com" and the connection ID is "office", the user connection ID is "igrsuser@igrs.com/office".

Note 1 to entry: A user connection ID is unique. The IRSP tests and guarantees the uniqueness of a user connection ID.

Note 2 to entry: A user connection ID consists of a user ID and a connection ID. A "/" is used to separate the two IDs.

Note 3 to entry: The connection ID is set by the user when logging in.

3.1.20

user ID

unique identification of an IGRS RA user

EXAMPLE If the local part of a user ID is "igrsuser" and the domain name part of the user ID is "igrs.com", the user ID is "igrsuser@igrs.com".

Note 1 to entry: A user ID consists of a local part and a domain name part. A "@" is used to separate the two parts.

3.2 Abbreviated terms

AS	autonomous system
HTTP	hypertext transfer protocol
ID	identification
IGRS	intelligent grouping and resource sharing
IRSP	IGRS RA service platform
NAT	network address translation
RA	remote access
SASL	simple authentication and security layer
TLS	transport layer security
TCP/IP	transmission control protocol/Internet protocol
UI	user interface
XMPP	extensible messaging and presence protocol