

Third edition
2017-10-15

AMENDMENT 3
2018-07

**Information technology — High
efficiency coding and media delivery
in heterogeneous environments —**

Part 2:
High efficiency video coding

**AMENDMENT 3: Additional
supplemental enhancement information**

*Technologies de l'information — Codage à haute efficacité et livraison
des médias dans des environnements hétérogènes —*

Partie 2: Codage vidéo à haute efficacité

*AMENDEMENT 3: Informations additionnelles supplémentaires pour
amélioration*



Reference number
ISO/IEC 23008-2:2017/Amd.3:2018(E)

© ISO/IEC 2018

iTeh Standards
(<https://standards.itih.ai>)
Document Preview

[ISO/IEC 23008-2:2017/Amd 3:2018](https://standards.itih.ai/catalog/standards/iso/6661eb2c-70f2-4b66-9d68-d9084cf92d40/iso-iec-23008-2-2017-amd-3-2018)

<https://standards.itih.ai/catalog/standards/iso/6661eb2c-70f2-4b66-9d68-d9084cf92d40/iso-iec-23008-2-2017-amd-3-2018>



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*, in collaboration with ITU-T. The identical text for ISO/IEC 23008-2 is published as ITU-T H.265.

A list of all parts in the ISO/IEC 23008 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Information technology — High efficiency coding and media delivery in heterogeneous environments —

Part 2: High efficiency video coding

AMENDMENT 3: Additional supplemental enhancement information

General

Throughout the specification, replace all single-word instances of "nested" with "scalable-nested" (e.g., there is no single-word instance of "nested" in "non-nested"), and all instances of "non-nested" with "non-scalable-nested", except in 3.158 (which is kept unchanged) and Table F.4 in F.14.3.1 (for which a change is provided below).

Clause 3

Add the following term definitions (in alphabetical order within the current list) and correct all term numbering sequentially:

3.X

azimuth circle

circle on a sphere connecting all points with the same azimuth value

Note 1 to entry: An azimuth circle is always a *great circle* like a longitude line on the earth.

3.X

constituent picture

part of a spatially frame-packed stereoscopic video picture that corresponds to one view, or a picture itself when frame packing is not in use or the temporal interleaving frame packing arrangement is in use

3.X

elevation circle

circle on a sphere connecting all points with the same elevation value

Note 1 to entry: An elevation circle is similar to a latitude line on the earth. Except when the elevation value is zero, an elevation circle is not a *great circle* like a longitude circle on the earth.

3.X

global coordinate axes

coordinate axes associated with *omnidirectional video* that are associated with an externally referenceable position and orientation

Note 1 to entry: The global coordinate axes may correspond to the position and orientation of a device or rig used for omnidirectional audio/video acquisition as well as the position of an observer's head in the three-dimensional space of the *omnidirectional video* rendering environment.

3.X

great circle

intersection of a sphere and a plane that passes through the centre point of the sphere

Note 1 to entry: A great circle is also known as an orthodrome or Riemannian circle.

3.X

local coordinate axes

coordinate axes having a specified rotation relationship relative to the *global coordinate axes*

3.X

omnidirectional video

video content in a format that enables rendering according to the user's viewing orientation, e.g., if viewed using a head-mounted device, or according to a user's desired *viewport*, reflecting a potentially rotated viewing position

3.X

packed region

region in a *region-wise packed picture* that is mapped to a *projected region* according to a *region-wise packing*

3.X

projected picture

picture that uses a *projection* format for *omnidirectional video*

3.X

projected region

region in a *projected picture* that is mapped to a *packed region* according to a *region-wise packing*

3.X

projection

specified correspondence between the colour samples of a *projected picture* and azimuth and elevation positions on a sphere

3.X

region-wise packed picture

decoded picture that contains one or more *packed regions*

Note 1 to entry: A packed picture may contain a *region-wise packing* of a *projected picture*.

3.X

region-wise packing

transformation, resizing, and relocation of *packed regions* of a *region-wise packed picture* to remap the *packed regions* to *projected regions* of a *projected picture*

3.X

sphere coordinates

azimuth and elevation angles identifying a location of a point on a sphere

3.X

sphere region

region on a sphere, specified either by four *great circles* or by two *azimuth circles* and two *elevation circles*, or such a region on a rotated sphere after applying yaw, pitch, and roll rotations

3.X

tilt angle

angle indicating the amount of tilt of a *sphere region*, measured as the amount of rotation of a *sphere region* along the axis originating from the sphere origin passing through the centre point of the *sphere region*, where the angle value increases clockwise when looking from the origin towards the positive end of the axis

3.X

viewport

region of *omnidirectional video* content suitable for display and viewing by the user

Clause 4

Add the following to the list of abbreviations (in alphabetical order):

MCTS motion-constrained tile set

5.8

Add the following function definitions:

Asin(x) the trigonometric inverse sine function, operating on an argument x that is in the range of -1.0 to 1.0, inclusive, with an output value in the range of $-\pi \div 2$ to $\pi \div 2$, inclusive, in units of radians (5-2)

Atan(x) the trigonometric inverse tangent function, operating on an argument x, with an output value in the range of $-\pi \div 2$ to $\pi \div 2$, inclusive, in units of radians (5-3)

$$\text{Atan2}(y,x) = \begin{cases} \text{Atan}\left(\frac{y}{x}\right) & ; \text{ if } x > 0 \\ \text{Atan}\left(\frac{y}{x}\right) + \pi & ; \text{ if } x < 0 \ \& \& \ y \geq 0 \\ \text{Atan}\left(\frac{y}{x}\right) - \pi & ; \text{ if } x < 0 \ \& \& \ y < 0 \\ +\frac{\pi}{2} & ; \text{ if } x == 0 \ \& \& \ y \geq 0 \\ -\frac{\pi}{2} & ; \text{ otherwise} \end{cases} \quad (5-4)$$

Renumber the prior Formulae 5-2 through 5-15 as 5-5 to 5-18 to account for the added formulae.

Add the following function definition:

Sin(x) the trigonometric sine function operating on an argument x in units of radians (5-19)

Renumber the prior Formulae 5-19 through 5-20 as 5-20 to 5-21 to account for the added formulae.

Add the following function definition:

Tan(x) the trigonometric tangent function operating on an argument x in units of radians (5-22)

7.4.2.4.4, NOTE 2

Delete the sentence that says “Consequently, hypothetical reference decoder (HRD) parameters carried in non-nested buffering period, picture timing and decoding unit information SEI messages apply to access units based on such access unit boundary detection.”

7.4.4

Replace paragraph 6 (directly after NOTE 1) and NOTE 2 with the following:

general_non_packed_constraint_flag equal to 1 specifies that there are no frame packing arrangement SEI messages, segmented rectangular frame packing arrangement SEI messages, omnidirectional projection indication SEI messages, or cubemap projection SEI messages present in the CVS. **general_non_packed_constraint_flag** equal to 0 indicates that there may or may not be one or more frame packing arrangement SEI messages, segmented rectangular frame packing arrangement