
**Information technology — Data
interchange on 120 mm and 80 mm
optical disk using +RW DL format —
Capacity: 8,55 Gbytes and 2,66 Gbytes
per side (recording speed 2,4X)**

*Technologies de l'information — Échange de données sur disques
optiques de 120 mm et 80 mm utilisant le format +RW DL — Capacité:
8,55 Go et 2,66 Go par face (vitesse d'enregistrement 2,4X)*

Sample Document

get full document from standards.iteh.ai

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

Sample Document

get full document from standards.iteh.ai



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	viii
Introduction	ix
1 Scope	1
2 Conformance.....	1
2.1 Optical disk.....	1
2.2 Generating system.....	1
2.3 Receiving system.....	2
2.4 Compatibility statement	2
3 Normative references	2
4 Terms and definitions	2
5 Conventions and notations	4
5.1 Representation of numbers	4
5.2 Names	5
6 Abbreviated terms	5
7 General description of the optical disk	5
8 General Requirements	6
8.1 Environments	6
8.1.1 Test environment.....	6
8.1.2 Operating environment	7
8.1.3 Storage environment.....	7
8.1.4 Transportation.....	7
8.2 Safety requirements	7
8.3 Flammability	7
9 Reference Drive.....	7
9.1 Optical system	8
9.2 Optical beam	8
9.3 Read channel 1.....	9
9.4 Disk clamping.....	9
9.5 Rotation of the disk	10
9.6 Wobble channel (Read channel 2)	10
9.7 Tracking channel (Read channel 2)	10
9.8 Reference servo systems	10
9.8.1 Normalized servo transfer function	10
9.8.2 Reference Servo for Axial Tracking	11
9.8.3 Reference Servo for Radial Tracking.....	12
10 Dimensional characteristics	13
10.1 Reference Planes	14
10.2 Overall dimensions.....	15
10.3 First transition area	15

10.4	Second transition area	16
10.5	Clamping Zone	16
10.6	Third transition area	16
10.7	Information Zone	16
10.7.1	Sub-division of the Information Zone	17
10.7.2	Track mode	17
10.8	Rim area	18
10.9	Remark on tolerances	18
11	Mechanical characteristics	18
11.1	Mass	18
11.2	Moment of inertia	18
11.3	Dynamic imbalance	18
11.4	Axial runout	18
11.4.1	Tracking requirements at the Reference velocity (CLV)	18
11.5	Radial runout	19
11.5.1	Tracking requirements at the Reference velocity (CLV)	19
12	Optical characteristics in the Information Zone	19
12.1	Index of refraction	19
12.2	Thickness of the substrate	19
12.3	Reflectivity	20
12.4	Birefringence	21
12.5	Angular deviation	21
13	Data format	21
13.1	Data Frames	22
13.1.1	Identification Data (ID)	22
13.1.2	ID Error Detection Code (IED)	23
13.1.3	RSV	23
13.1.4	Error Detection Code (EDC)	23
13.2	Scrambled Frames	24
13.3	ECC Blocks	25
13.4	Recording Frames	26
13.5	Modulation and NRZI conversion	27
13.6	Physical Sectors	27
13.7	Layout of a Recording UNit (RUN)	28
13.7.1	Recording Unit position	29
13.8	d.c. component suppression control	29
14	Track format	31
14.1	Track shape	31
14.2	Track path	31
14.3	Track pitch	31
14.4	Track layout	31
14.4.1	ADIP information	31
14.4.2	Physical format information in ADIP	35
15	General description of the Information Zone	50
16	Layout of the Information Zone	51

16.1	Usage of the Data Zone	51
16.2	Physical Sector Numbers (PSNs).....	52
17	Lead-in Zone.....	53
17.1	Initial Zone	53
17.2	Inner Disk Test Zone	53
17.3	Guard Zone 1	54
17.4	Reserved Zone 1	54
17.5	Reserved Zone 2	54
17.6	Inner Disk Identification Zone	54
17.7	Reserved Zone 3	55
17.8	Reference Code Zone	55
17.9	Buffer Zone 1	55
17.10	Control Data Zone.....	55
17.10.1	Physical format information	55
17.10.2	Disk manufacturing information	57
17.10.3	Content provider information	58
17.11	Buffer Zone 2.....	58
18	Data Zone.....	58
19	Middle Zones	58
19.1	Buffer Zones 3.....	59
19.2	Reserved Zones 4	59
19.3	Guard Zones 2.....	59
20	Outer Drive Areas	60
20.1	Reserved Zone 5	61
20.2	Outer Disk Test Zone.....	61
20.3	Guard Zone 3.....	61
21	Lead-out Zone	61
21.1	Buffer Zone 4.....	62
21.2	Inner Disk Test Zone	62
21.3	Final Zone	62
22	Assignment of Logical Sector Numbers (LSNs).....	62
23	Formatting	62
23.1	Pre-formatting	63
23.1.1	Verification	63
23.2	Background formatting	63
23.2.1	Initialization	63
23.2.2	De-icing.....	63
23.2.3	Finalization	66
23.2.4	Verification (optional)	66
23.3	Sequential recording without formatting	66
24	Disk Control Blocks.....	68
24.1	General format of Disk Control Blocks	68
24.2	Format of the Formatting DCB (FDCB).....	70
24.3	Format of the Write inhibit DCB (WDCB).....	75
25	General.....	77

26	Method of testing	77
26.1	Environment	77
26.2	Reference Drive	77
26.2.1	Optics and mechanics	77
26.2.2	Read power	77
26.2.3	Read channels	77
26.2.4	Tracking	78
26.3	Definition of signals	78
27	Characteristics of the groove signals	79
27.1	Phase depth	79
27.2	Push-pull signal	79
27.3	Track Cross signal	79
27.4	Normalized wobble signal	79
27.5	Characteristics of the wobble	80
28	Method of testing	80
28.1	Environment	80
28.2	Reference Drive	80
28.2.1	Optics and mechanics	80
28.2.2	Read power	80
28.2.3	Read channels	80
28.2.4	Tracking	81
28.2.5	Scanning velocity	81
28.3	Write conditions	81
28.3.1	Write pulse waveform	81
28.3.2	Write power	81
28.3.3	Write power shift for layer L1 due to recording on layer L0	82
28.4	Measurement conditions	82
29	Characteristics of the recorded signals	82
29.1	Channel bit length	82
29.2	Definition of signals	82
29.2.1	High frequency signals (HF)	82
29.2.2	Modulated amplitude	83
29.2.3	Signal asymmetry	83
29.2.4	Normalized Slicing Level jump	83
29.2.5	Jitter	84
29.3	Read stability	84
30	Additional testing conditions	85
30.1	Test environment	85
30.1.1	Optics	85
30.2	Definition of signals	85
30.2.1	Modulated amplitude	86
30.2.2	Signal asymmetry	86
30.2.3	Jitter	86
30.2.4	Track Cross signal	86
30.2.5	Differential phase tracking error signal	86

30.2.6	Tangential push-pull signal	87
31	Quality of the recording layer	88
31.1	Defects	88
31.2	Data errors	88
32	Method of testing	89
32.1	Environment	89
32.2	Reference Drive	89
32.2.1	Optics and mechanics	89
32.2.2	Read power	89
32.2.3	Read channels	89
32.2.4	Error correction	89
32.2.5	Tracking	89
33	Minimum quality of a Recording Unit	90
33.1	Tracking	90
33.2	User-written data	90
Annex A (normative)	80 mm +RW DL disk	91
Annex B (normative)	Structure for Extended format information in the Data Zone	96
Annex C (normative)	Measurement of light reflectivity	99
Annex D (normative)	Measurement of birefringence	101
Annex E (normative)	Measuring conditions for operation signals	104
Annex F (normative)	Measurement of the differential phase tracking error	107
Annex G (normative)	The write pulse wave form for testing	111
Annex H (normative)	8-to-16 Modulation	116
Annex I (normative)	Optimum Power Control	125
Annex J (normative)	Logical to Physical address translation	130
Annex K (informative)	Recommended access method for players	131
Annex L (informative)	Measurement of the groove wobble amplitude	132
Annex M (informative)	Transportation	134
Annex N (informative)	Defect Management and Physical Formatting	135
Annex O (informative)	Video Content Protection System	136
Annex P (informative)	How to use the Physical format information in ADIP	137
Annex Q (informative)	Values to be Implemented in Existing and Future Specifications	139
Bibliography		143

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 29642 was prepared by Ecma International (as ECMA-374) and was adopted, under a special “fast-track procedure”, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

This second edition cancels and replaces the first edition (ISO/IEC 29642:2007), which has been technically revised.

get full document from standards.iteh.ai

Introduction

Ecma Technical Committee TC31 was established in 1984 for the standardization of Optical Disks and Optical Disk Cartridges (ODC). Since its establishment, the Committee has made major contributions to ISO/IEC toward the development of International Standards for 80 mm, 90 mm, 120 mm, 300 mm, and 356 mm media. Numerous standards have been developed by TC31 and published by Ecma, almost all of which have also been adopted by ISO/IEC under the fast-track procedure as International Standards.

In June 2006, a group of companies proposed that TC31 develop a standard for 120 mm dual layer rewritable optical disks using phase change recording technology and based on ISO/IEC 16448, ISO/IEC 17341 and ISO/IEC 26925. TC31 adopted this project and started the work that has resulted in this International Standard.

This International Standard specifies two Types of rewritable optical disks: one (Type S9) making use of recording on only a single side of the disk and yielding a nominal capacity of 8,55 Gbytes or 2,66 Gbytes per disk and the other (Type D18) making use of recording on both sides of the disk and yielding a nominal capacity of 17,1 Gbytes or 5,32 Gbytes per disk.

This International Standard, taken together with a standard for volume and file structure, such as for instance developed in Ecma Technical Committee TC15, provides the requirements for information interchange between systems.

Sample Document

get full document from standards.iteh.ai

Sample Document

get full document from standards.iteh.ai

Information technology — Data interchange on 120 mm and 80 mm optical disk using +RW DL format — Capacity: 8,55 Gbytes and 2,66 Gbytes per side (recording speed 2,4X)

1 Scope

This International Standard specifies the mechanical, physical and optical characteristics of 120 mm rewritable optical disks with capacities of 8,55 Gbytes and 17,1 Gbytes. It specifies the quality of the recorded and unrecorded signals, the format of the data and the recording method, thereby allowing for information interchange by means of such disks. The data can be written, read and overwritten many times using the phase change method. These disks are identified as +RW DL.

This International Standard also specifies 80 mm disks with capacities of 2,66 Gbytes and 5,32 Gbytes. These disks have the same characteristics as the 120 mm disks, except for some parameters related to the smaller dimensions. All parameters unique for the 80 mm disks are specified in Annex A.

This International Standard specifies the following:

- two related but different Types of this disk (see Clause 7);
- the conditions for conformance;
- the environments in which the disk is to be tested, operated and stored;
- the mechanical, physical and dimensional characteristics of the disk, so as to provide mechanical interchange between data processing systems;
- the format of the information on the disk, including the physical disposition of the tracks and sectors, the error correcting codes and the coding method;
- the characteristics of the signals recorded on the disk, thus enabling data processing systems to read the data from the disk.

This International Standard provides for the interchange of disks between optical disk drives. Together with a standard for volume and file structure, it provides for full data interchange between data processing systems.

2 Conformance

2.1 Optical disk

A claim of conformance with this International Standard shall specify the Type implemented. An optical disk is in conformance with this International Standard if it meets all mandatory requirements specified for its Type.

2.2 Generating system

A generating system is in conformance with this International Standard if the optical disk it generates is in accordance with 2.1.

2.3 Receiving system

A receiving system is in conformance with this International Standard if it is able to handle both Types of optical disk according to 2.1.

2.4 Compatibility statement

A claim of conformance by a generating or receiving system with this International Standard shall include a statement listing any other standards supported. This statement shall specify the numbers of the standards, the optical disk types supported (where appropriate) and whether support includes reading only or both reading and writing.

3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 4873:1991, *Information technology — ISO 8-bit code for information interchange — Structure and rules for implementation*

ISO/IEC 16448:2002, *Information technology — 120 mm DVD — Read-only disk*

ECMA-287, *Safety of electronic equipment* (2002)

4 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

4.1

channel bit

elements by which the binary values ZERO and ONE are represented by marks and spaces on the disk

4.2

clamping zone

annular part of the disk within which the clamping force is applied by the clamping device

4.3

Digital Sum Value

DSV

arithmetic sum obtained from a bit stream by allocating the decimal value +1 to bits set to ONE and the decimal value –1 to bits set to ZERO

4.4

disk reference plane

plane defined by the perfectly flat annular surface of an ideal spindle onto which the clamping zone of the disk is clamped, and which is normal to the axis of rotation

4.5

dummy substrate

layer, which can be transparent or not, provided for the mechanical support of the disk and, in some cases, of the recording layer as well

4.6

entrance surface

surface of the disk onto which the optical beam first impinges

4.7**field**

subdivision of a sector

4.8**groove**

trench-like feature of the disk, applied before the recording of any information and used to define the track location

NOTE The groove is located nearer to the entrance surface than the “land” in between the grooves. The recording is made on the groove.

4.9**interleaving**

process of reallocating the physical sequence of units of data so as to render the data more immune to burst errors

4.10**mark**

feature of the recording layer that can take the form of an amorphous domain, a pit or any other type or form that can be sensed by the optical system

NOTE The pattern of marks and spaces represents the data on the disk.

4.11**phase change**

physical effect by which the area of a recording layer irradiated by a laser beam is heated so as to change from an amorphous state to a crystalline state and vice versa

4.12**physical sector**

smallest addressable part of a track in the Information Zone of a disk that can be accessed independently of other addressable parts of the zone

4.13**recording layer**

layer of the disk on which data is written during manufacture and/or use

4.14**Reed–Solomon code****RS**

error detection and/or correction code

4.15**reference velocity**

linear velocity that results in the nominal channel bit rate of 26,156 25 Mbit/s

4.16**space**

feature of the recording layer that can take the form of a crystal, a non-pit or any other type or form that can be sensed by the optical system

NOTE The pattern of marks and spaces represents the data on the disk.

4.17**spacer**

transparent layer of the disk, provided for achieving an accurate separation of the pair of recording layers which are accessed by the optical beam through the same entrance surface

4.18

substrate

transparent layer of the disk, provided for mechanical support of the recording layer, through which the optical beam accesses the recording layer

4.19

track

360° turn of a continuous spiral

4.20

track pitch

distance between adjacent track centrelines, measured in a radial direction

4.21

Video Content Protection System

VCPS

method to prevent unauthorized copying and/or redistribution of video data that is recorded in the DVD+R/+RW video format

4.22

wobble

continuous sinusoidal deviation of the track from the average centreline

NOTE The location information is included as phase modulated data in the wobble.

4.23

zone

annular area of the disk

5 Conventions and notations

5.1 Representation of numbers

A measured value may be rounded off to the least significant digit of the corresponding specified value. For instance, it implies that a specified value of 1,26 with a positive tolerance of + 0,01 and a negative tolerance of - 0,02 allows a range of measured values from 1,235 to 1,274.

Numbers in decimal notations are represented by the digits 0 to 9.

Numbers in hexadecimal notation are represented by the hexadecimal digits 0 to 9 and A to F in parentheses.

The setting of bits is denoted by ZERO and ONE.

Numbers in binary notations and bit patterns are represented by strings of digits 0 and 1, with the most significant bit shown to the left. In a pattern of n bits, bit b_{n-1} shall be the most significant bit (msb) and bit b_0 shall be the least significant bit (lsb). Bit b_{n-1} shall be recorded first.

Negative values of numbers in binary notation are given as Two's complement.

In each data field, the data is recorded so that the most significant byte (MSB), identified as Byte 0, shall be recorded first and the least significant byte (LSB) last.

In a field of $8n$ bits, bit $b_{(8n-1)}$ shall be the most significant bit (msb) and bit b_0 the least significant bit (lsb).

Bit $b_{(8n-1)}$ shall be recorded first.

5.2 Names

The names of entities, e.g. specific tracks, fields, etc., are given with an initial capital.

6 Abbreviated terms

a.c.	alternating current	NA	Numerical Aperture
ADIP	address in pre-groove	NRZ	Non Return to Zero
ASM	asymmetry	NRZI	Non Return to Zero Inverted
BP	Byte Position	NSL	Normalized Slicing Level
BPF	Band Pass Filter	OPC	Optimum Power Control
CAV	Constant Angular Velocity	OTP	Opposite Track Path
CLD	Constant Linear Density	PAA	Physical Address in ADIP
CLV	Constant Linear Velocity	PBS	Polarizing Beam Splitter
d.c.	direct current	PI	Parity of Inner-code
DCB	Disk Control Block	PLL	Phase Locked Loop
DCC	d.c. Component suppression Control	PO	Parity of Outer-code
DOW	Direct OverWrite	PP	Push-Pull
DSV	Digital Sum Value	pp	peak-to-peak
ECC	Error Correction Code	PSN	Physical Sector Number
EDC	Error Detection Code	PTP	Parallel Track Path
EI	Extended Information	RIN	Relative Intensity Noise
FBA	First Backwards-formatted Address	RPM	Revolutions Per Minute
FDCB	Formatting DCB	RS	Reed–Solomon code
HF	High Frequency	RSV	reserved
ID	Identification Data		(in use by specific applications)
IED	ID Error Detection code	RUN	Recording UNit
LPF	Low Pass Filter	SNR	Signal to Noise Ratio
LSB	Least Significant Byte	SPS	Start Position Shift
lsb	least significant bit	SYNC	synchronization code
LSN	Logical Sector Number		
LWA	Last Written/forwards-formatted Address		
MSB	Most Significant Byte		
msb	most significant bit		

7 General description of the optical disk

The optical disk that is the subject of this International Standard consists of two substrates bonded together by an adhesive layer, so that the recording layer(s) is (are) on the inside. The centering of the disk is performed on the edge of the centre hole of the assembled disk on the side currently accessed. Clamping is performed in the Clamping Zone. This International Standard provides for two Types of such disks.

Type S9 consists of a substrate, a dummy substrate and two recording layers with a spacer between them. Both recording layers can be accessed from one side only. The capacity is 8,55 Gbytes for the 120 mm sized disk and 2,66 Gbytes for the 80 mm sized disk.

Type D18 consists of two substrates, each having two recording layers with a spacer between those two recording layers. From each side of the disk only one pair of recording layers can be accessed. The capacity is 17,1 Gbytes for the 120 mm sized disk and 5,32 Gbytes for the 80 mm sized disk.

Data can be written onto the disk as marks in the form of amorphous spots in each of the crystalline recording layers and can be overwritten with a focused optical beam, using the phase change effect between amorphous and crystalline states. The data can be read with a focused optical beam, using the phase change effect as the difference in the reflectivity between amorphous and crystalline states.