TECHNICAL SPECIFICATION

ISO/TS 11665-12

First edition
2018-10

Measurement of radioactivity in the environment — Air: radon-222 —

Part 12: Determination of the diffusion coefficient in waterproof materials: membrane one-side activity concentration measurement method

Mesurage de la radioactivité dans l'environnement — Air : radon 222 —

Partie 12: Détermination du coefficient de diffusion des matériaux imperméables: méthode de mesure de l'activité volumique d'un côté de la membrane

iTeh Standards
(https://standards.iteh.ai)
Document Preview
12:2018
https://standards.iteh.ai/catalog/standards/iso/1c97ba53-ad86-4c7f-91e5-5a7e3c4dd212/iso-ts-11665-12-2018

Reference number
ISO/TS 11665-12:2018(E)

© ISO 2018

iTeh Standards
(https://standards.iteh.ai)
Document Preview

ISO/TS 11665-12:2018
https://standards.iteh.ai/catalog/standards/iso/1c97ba53-ad86-4c7f-91e5-5a7e3c4dd212/iso-ts-11665-12-2018



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

 © ISO 2018 – All rights reserved

Contents

Page

Foreword ... **iv**

Introduction ... **v**

1 Scope ... **1**

2 Normative references ... **1**

3 Terms, definitions and symbols ... **1**
3.1 Terms and definitions ... 1
3.2 Symbols ... 2

4 Principle ... **3**

5 Equipment ... **5**

6 Sample preparation ... **6**
6.1 General consideration ... 6
6.2 Fixing the sample in the holder ... 7
6.3 Connection of the holder (cap) with the chamber ... 7

7 Control measurements ... **8**
7.1 Verification of radon-tightness ... 8
7.2 Calibration ... 9
7.3 Detector background ... 9
7.4 Instrument statistical fluctuation ... 9

8 Measurement of radon activity concentration ... **10**

9 Processing and expression of the results for the sample ... **11**
9.1 Determination of the radon diffusion coefficient in the sample ... 11
9.2 Characteristics of measurement limits ... 11
9.3 Estimation of confidence interval and uncertainty ... 13
9.4 Expression of the results ... 13

10 Requirements for the test ... **14**

11 Influencing factors ... **15**

12 Expression of the results and assessment of the standard uncertainty for the material ... **16**

13 Quality management and calibration of the test device ... **17**

14 Test report ... **17**
14.1 The test report for material ... 17
14.2 The test report for each sample ... 18
14.3 Archived material ... 18

Annex A (informative) **Determination of the radon diffusion coefficient of the sample** ... **19**

Bibliography ... **27**

iTeh Standards
(https://standards.iteh.ai)
Document Preview
ISO/TS 11665-12:2018
https://standards.iteh.ai/catalog/standards/iso/1c97ba53-ad86-4c7f-91e5-5a7e3c4dd212/iso-ts-11665-12-2018

© ISO 2018 – All rights reserved

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

iTeh Standards
(https://standards.iteh.ai)
Document Preview

This document was prepared by Technical Committee ISO/TC 85, *Nuclear energy, nuclear technologies, and radiological protection*, Subcommittee SC 2, *Radiological protection*.

A list of all parts in the ISO 11665 series can be found on the ISO website.

ISO/TS 11665-12:2018
https://standards.iteh.ai/catalog/standards/iso/1c97ba33-ad86-4c7b-91e1-5a7e3c4dd212/iso-ts-11665-12-2018

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

© ISO 2018 – All rights reserved

Introduction

Radon isotopes 222, 219 and 220 are radioactive gases produced by the disintegration of radium isotopes 226, 223 and 224, which are decay products of uranium-238, uranium-235 and thorium-232 respectively, and are all found in the earth's crust. Solid elements, also radioactive, followed by stable lead are produced by radon disintegration[4].

When disintegrating, radon emits alpha particles and generates solid decay products, which are also radioactive (polonium, bismuth, lead, etc.). The potential effects on human health of radon lie in its solid decay products rather than the gas itself. Whether or not they are attached to atmospheric aerosols, radon decay products can be inhaled and deposited in the bronchopulmonary tree to varying depths according to their size.

Radon is today considered to be the main source of human exposure to natural radiation. UNSCEAR[5] suggests that, at the worldwide level, radon accounts for around 52 % of global average exposure to natural radiation. The radiological impact of isotope 222 (48 %) is far more significant than isotope 220 (4 %), while isotope 219 is considered negligible. For this reason, references to radon in this document refer only to radon-222.

Radon activity concentration can vary from one to more orders of magnitude over time and space. Exposure to radon and its decay products varies tremendously from one area to another, as it depends on the amount of radon emitted by the soil, weather conditions, and on the degree of containment in the areas where individuals are exposed.

As radon tends to concentrate in enclosed spaces like houses, the main part of the population exposure is due to indoor radon. Soil gas is recognized as the most important source of residential radon through infiltration pathways. Other sources are described in other parts of ISO 11665 and ISO 13164 series for water[2].

iTeh Standards
(https://standards.iteh.ai)
Document Preview

Radon enters into buildings via a diffusion mechanism caused by the all-time existing difference between radon activity concentrations in the underlying soil and inside the building, and via a convection mechanism inconstantly generated by a difference in pressure between the air in the building and the air contained in the underlying soil. Indoor radon activity concentration depends on radon activity concentration in the underlying soil, the building structure, the equipment (chimney, ventilation systems, among others), the environmental parameters of the building (temperature, pressure, etc.) and the occupants' lifestyle.

To limit the risk to individuals, a national reference level of 100 $Bq \cdot m^{-3}$ is recommended by the World Health Organization[6]. Wherever this is not possible, this reference level should not exceed 300 $Bq \cdot m^{-3}$. This recommendation that was endorsed by the European community member states establishes national reference levels for indoor radon activity concentrations. The reference levels for the annual average activity concentration in air cannot be higher than 300 $Bq \cdot m^{-3}$[8].

To reduce the risk to the overall population, building codes which require radon prevention measures in buildings under construction and radon mitigating measures in existing buildings should be implemented. Radon measurements are needed because building codes alone cannot guarantee that radon concentrations are below the reference level.

When a building requires protection against radon from the soil, radon-proof insulation (based on membranes, coatings or paints) placed between the soil and the indoors may be used as a stand-alone radon prevention/remediation strategy or in combination with other techniques such as passive or active soil depressurization. Radon-proof insulation functions at the same time as the waterproof insulation.

The radon diffusion coefficient is a parameter that determines the barrier properties of waterproof materials against the diffusive transport of radon. Applicability of the radon diffusion coefficient for radon-proof insulation can be prescribed by national building standards and codes. Requirements for radon-proof insulation as regards the durability, mechanical and physical properties and the maximum

© ISO 2018 – All rights reserved