SLOVENSKI STANDARD
oSIST prEN 1015-18:2026

01-december-2026

Metode preskušanja zidarske malte - 18. del: Določanje koeficienta kapilarnega vpijanja vode strjene malte

Methods of test for mortar for masonry - Part 18: Determination of water absorption coefficient due to capillary action of hardened mortar

Prüfverfahren für Mörtel für Mauerwerk - Teil 18: Bestimmung der kapillaren Wasseraufnahme von erhärtetem Mörtel (Festmörtel)

Sample Document

Méthodes d'essai des mortiers pour maçonnerie - Partie 18: Détermination du coefficient d'absorption d'eau par capillarité du mortier durci

get full document from standards.iteh.ai

Ta slovenski standard je istoveten z: **prEN 1015-18**

ICS:

91.100.10	Cement. Mavec. Apno. Malta	Cement. Gypsum. Lime. Mortar

oSIST prEN 1015-18:2026 **en,fr,de**

2003-01.Slovenski inštitut za standardizacijo. Razmnoževanje celote ali delov tega standarda ni dovoljeno.

oSIST prEN 1015-18:2026 • https://standards.iteh.ai/catalog/standards/sist/c9dabf39-3ba1-47ce-976b-93c6e4d2f2dd/osist-pren-1015-18-2026

Sample Document

get full document from standards.iteh.ai

oSIST prEN 1015-18:2026

EUROPEAN STANDARD

NORME EUROPÉENNE

EUROPÄISCHE NORM

DRAFT
prEN 1015-18

October 2026

ICS 91.100.10

Will supersede EN 1015-18:2002

English Version

Methods of test for mortar for masonry - Part 18: Determination of water absorption coefficient due to capillary action of hardened mortar

Méthodes d'essai des mortiers pour maçonnerie - Partie 18: Détermination du coefficient d'absorption d'eau par capillarité du mortier durci

Prüfverfahren für Mörtel für Mauerwerk - Teil 18: Bestimmung der kapillaren Wasseraufnahme von erhärtetem Mörtel (Festmörtel)

This draft European Standard is submitted to CEN members for enquiry. It has been drawn up by the Technical Committee CEN/TC 125.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Sample Document

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

get full document from standards.iteh.ai

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

© 2026 CEN All rights of exploitation in any form and by any means reserved worldwide for CEN national Members.

Ref. No. prEN 1015-18:2026 E

oSIST prEN 1015-18:2026 • https://standards.iteh.ai/catalog/standards/sist/c9dabf39-3ba1-47ce-976b-93c6e4d2f2dd/osist-pren-1015-18-2026

oSIST prEN 1015-18:2026

Contents

Page

European foreword 3
1 Scope 4
2 Normative references 4
3 Terms and definitions 4
4 Principle 4
5 Symbols 4
6 Apparatus 5
6.1 Tray, of minimum depth of 20 mm and of plan area large enough to contain the test specimens to be immersed and fitted with a means of maintaining a constant water level. 5
6.2 Four support pads or similar per test specimen, to store the test specimen, with a minimum contact area, clear of the base tray and with the test specified depth of immersion. 5
6.3 Stopwatch, graduated in seconds 5
6.4 Weighing instrument, with an accuracy of 0,1 % of the total, dry mass of the test specimen. 5
6.5 Ventilated oven, capable of maintaining a temperature of 60 °C ± 5 °C 5
6.6 Trowel or palette knife 5
6.7 Conditioning chamber or room, capable of maintaining a relative humidity of 95 % ± 5 % and 65 % ± 5 %. 5
6.8 Metal mould and other ancillary apparatus, to produce 160 mm x 40 mm x 40 mm prisms as described in EN 1015-11. 5
7 Materials 5
7.1 Water 5
7.2 Demoulding agent (release oil, mould oil, formwork release agent oil) may only be used in areas where the sides of the prism are not covered by non-woven fabric or filter paper. .. 5
7.3 Sealing material, e.g. paraffin wax or synthetic reactive resin with a melting point above 60 °C 5
7.4 Absorbent filter papers 5
7.5 White cotton gauze, sheets each with a size of approximately 150 mm x 175 mm. as a separating layer to detach the filter paper 6
8 Sampling and preparation and storage of test specimens 6
8.1 General 6
8.2 Laboratory prepared mortars 6
8.3 Mortars, other than laboratory prepared mortars 6
8.4 Preparation and curing of the prisms 6
8.5 Drying, breaking and sealing the test specimen 7
9 Procedure 7
10 Calculation and expression of results 8
10.1 Renovation mortar 8
10.2 Mortars other than renovation mortars 9
11 Test report 10

Sample Document
Get full document from standards.iteh.ai

oSIST prEN 1015-18:2026 • https://standards.iteh.ai/catalog/standards/sist/c9dabf39-3ba1-47ce-976b-93c6e4d2f2dd/osist-pren-1015-18-2026

oSIST prEN 1015-18:2026

European foreword

This document (prEN 1015-18:2026) has been prepared by Technical Committee CEN/TC 125 “Masonry”, the secretariat of which is held by BSI.

This document is currently submitted to the CEN Enquiry.

This document will supersede EN 1015-18:2002.

EN 1015-18:2026 includes the following significant technical changes with respect to EN 1015-18:2002:

- the content of the test standard has been adapted to the new template for test standards.
- the distinction between ‘renovation mortar’ and ‘other than renovation mortar’ has been retained.
- the symbols have been defined in greater detail.
- the sequence for preparing the individual test specimens has been specified as: drying, breaking and sealing the test specimen.
- the test report has been expanded to include the reporting of a standardized water absorption (kg/m^2) at t = 10 min.

Sample Document

get full document from standards.iteh.ai

oSIST prEN 1015-18:2026 • https://standards.iteh.ai/catalog/standards/sist/c9dabf39-3ba1-47ce-976b-93c6e4d2f2dd/osist-pren-1015-18-2026