



SLOVENSKI STANDARD

oSIST prEN 1127-2:2026

01-september-2026

Eksplzivne atmosfere - Protieksplzijska zaščita - 2. del: Osnovni pojmi in metodologija za rudarstvo

Explosive atmospheres - Explosion prevention and protection - Part 2: Basic concepts and methodology for mining

Explosionsfähige Atmosphären - Explosionsschutz - Teil 2: Grundlagen und Methodik in Bergwerken

Atmosphères explosives - Prévention de l'explosion et protection contre l'explosion - Partie 2 : Notions fondamentales et méthodologie dans l'exploitation des mines

Ta slovenski standard je istoveten z: **prEN 1127-2**

ICS:

13.230	Varstvo pred eksplozijo	Explosion protection
73.020	Rudarstvo in kamnolomsko izkopavanje	Mining and quarrying

oSIST prEN 1127-2:2026

en

Sample Document

get full document from standards.iteh.ai

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

DRAFT
prEN 1127-2

September 2026

ICS 13.230; 73.100.01

Will supersede EN 1127-2:2014

English Version

**Explosive atmospheres - Explosion prevention and
protection - Part 2: Basic concepts and methodology for
mining**

Atmosphères explosives - Prévention de l'explosion et
protection contre l'explosion - Partie 2 : Notions
fondamentales et méthodologie dans l'exploitation des
mines

Explosionsfähige Atmosphären - Explosionsschutz -
Teil 2: Grundlagen und Methodik in Bergwerken

This draft European Standard is submitted to CEN members for enquiry. It has been drawn up by the Technical Committee CEN/TC 305.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

© 2026 CEN All rights of exploitation in any form and by any means reserved
worldwide for CEN national Members.

Ref. No. prEN 1127-2:2026 E

Contents	Page
European foreword.....	4
Introduction	5
1 Scope	9
2 Normative references	10
3 Terms and definitions	11
4 Risk assessment.....	12
4.1 General.....	12
4.2 Identification of explosion hazards.....	12
4.3 Identification of ignition hazards.....	12
4.4 Estimation of the possible effects of an explosion	13
5 Possible ignition sources.....	13
5.1 Hot surfaces.....	13
5.2 Flames and hot gases (including hot particles).....	13
5.3 Mechanically generated sparks	13
5.4 Electrical equipment.....	13
5.5 Stray electric currents.....	13
5.6 Static electricity	14
5.7 Lightning	14
5.8 Radio frequency (RF) electromagnetic waves from 10^4 Hz to 3×10^{11} Hz (high frequency).....	14
5.9 Electromagnetic waves from 3×10^{11} Hz to 3×10^{15} Hz	14
5.10 Ionizing radiation.....	14
5.11 Ultrasonics.....	14
5.12 Adiabatic compression and shock waves	14
5.13 Exothermic reactions, including self-ignition of dusts.....	14
6 Risk reduction	14
6.1 Fundamental principles.....	14
6.2 Avoidance or reduction of explosive atmosphere	15
6.2.1 Process parameters.....	15
6.2.2 Design and construction of equipment, protective systems and components containing flammable substances.....	16
6.3 Classification of hazardous atmospheric conditions	17
6.3.1 General.....	17
6.3.2 Hazardous atmospheric conditions.....	17
6.4 Requirements for the design and construction of equipment, protective systems and components by avoidance of effective ignition sources.....	18
6.4.1 General.....	18
6.4.2 Hot surfaces.....	19
6.4.3 Flames and hot gases	20
6.4.4 Mechanically generated sparks	20
6.4.5 Electrical equipment.....	21
6.4.6 Stray electric currents.....	21
6.4.7 Static electricity	21
6.4.8 Lightning	21

6.4.9	Radio frequency (RF) electromagnetic waves from 10^4 Hz to 3×10^{11} Hz	21
6.4.10	Electromagnetic waves from 3×10^{11} Hz to 3×10^{15} Hz.....	22
6.4.11	Ionizing radiation	22
6.4.12	Ultrasonics	23
6.4.13	Adiabatic compression and shock waves.....	23
6.4.14	Exothermic reactions, including self-ignition of dusts	23
6.5	Requirements for design and construction of equipment, protective systems and components to reduce the explosion effects	23
6.5.1	General	23
6.5.2	Special equipment for underground mining	24
6.6	Provisions for emergency measures	24
6.7	Principles for measuring and control systems for explosion prevention and protection.....	25
7	Information for use.....	25
7.1	General	25
7.2	Information for commissioning, maintenance and repair to prevent explosion.....	26
7.3	Qualifications and training	26
Annex A	(informative) Relation between Equipment categories and hazardous atmospheric conditions.....	27
Annex B	(normative) Tools for use in potentially explosive atmospheres	28
Annex C	(informative) Significant technical changes between this document and the previous edition of this European Standard.....	29
Annex ZA	(informative) Relationship between this European Standard and the essential health and safety requirements of Directive 2014/34/EU aimed to be covered	31
Annex ZB	(informative) Relationship between this European Standard and the essential requirements of Regulation (EU) 2023/1230 aimed to be covered.....	34
Bibliography		39

prEN 1127-2:2026 (E)**European foreword**

This document (prEN 1127-2:2026) has been prepared by Technical Committee CEN/TC 305 “Potentially explosive atmospheres - Explosion prevention and protection”, the secretariat of which is held by DIN.

This document is currently submitted to the CEN Enquiry.

This document will supersede EN 1127-2:2014.

prEN 1127-2:2026 includes the following significant technical changes with respect to EN 1127-2:2014:

- classification corrected from type-A-standard to type-B-standard;
- references updated;
- Annex ZA and Annex ZB updated.

This document has been prepared under a standardization request addressed to CEN by the European Commission. The Standing Committee of the EFTA States subsequently approves these requests for its Member States.

For the relationship with EU Legislation, see informative Annex ZA and Annex ZB, which is an integral part of this document.

Sample Document

get full document from standards.iteh.ai

Introduction

General

CEN and CENELEC are producing a series of standards to assist designers, manufacturers and other interested bodies to interpret the essential safety requirements in order to achieve conformity with European legislation. Within this series of standards, CEN has undertaken to draw up a standard to give guidance in the field of explosion prevention and protection, as hazards from explosions are to be considered in accordance with EN ISO 12100:2010.

This document is a type-B standard as stated in EN ISO 12100.

This document is of relevance, in particular, for the following stakeholder groups representing the market players with regard to machinery safety:

- machine manufacturers (small, medium and large enterprises);
- health and safety bodies (regulators, accident prevention organizations, market surveillance etc.);

Others can be affected by the level of machinery safety achieved with the means of the document by the above-mentioned stakeholder groups:

- machine users/employers (small, medium and large enterprises);
- machine users/employees (e.g. trade unions, organizations for people with special needs);
- service providers, e.g. for maintenance (small, medium and large enterprises);
- consumers (in case of machinery intended for use by consumers).

The above-mentioned stakeholder groups have been given the possibility to participate at the drafting process of this document.

In addition, this document is intended for standardization bodies elaborating type-C standards.

The requirements of this document can be supplemented or modified by a type-C standard.

For machines that are covered by the scope of a type-C standard and have been designed and built according to the requirements of that standard, the requirements of that type-C standard take precedence.

Special considerations for mining

Explosions can result from:

- materials processed or used by the equipment and components, e.g. minerals obtained as part of the winning process;
- materials released by the equipment and components;
- materials in the vicinity of the equipment, protective systems and components;
- materials of which the equipment, protective systems and components are constructed.

As the explosion protection of equipment, protective systems and components depends on:

- the design and construction of the equipment, protective systems and components;
- the intended use;

prEN 1127-2:2026 (E)

- the foreseeable misuse;
- the ambient conditions;
- the materials extracted and handled.

This document also includes safety aspects related to these factors, i.e. it is imperative that the manufacturer consider how and for what the equipment, protective systems and components will be used and take this into account during their design and construction. Only in this way can hazards inherent in equipment, protective systems and components be reduced.

NOTE 1 This document can also serve as a guide for users of equipment, protective systems and components when assessing the risk of explosion in the workplace and selecting the appropriate equipment, protective systems and components.

Mines can be either gassy or non-gassy depending upon the mineral/material being extracted and whether or not firedamp can occur in the workings. It is usual practice to consider all coal mines as gassy mines. Non-coal mines can, however, also be susceptible to the occurrence of firedamp, e.g. if minerals/materials are being extracted in the vicinity of oil-bearing strata or unworked coal seams which are disturbed by the extraction process or mines susceptible to outbursts of flammable gas.

In mines where flammable minerals/materials are extracted, there can also be a risk of explosions because small particles of the extracted product can be blown into the air to form dust/air mixtures able to support rapid combustion. Combustible dust can either be an explosion risk on its own (when in the form of an explosive dust/air mixture), or it can settle in layers which can be blown from the floor and sides of the roadways by a firedamp explosion. In the latter case, the explosive violence can increase many times as more and more fuel in the form of combustible dust is raised by a blast wave and added to the flame as it travels along the roadways.

The risk of an explosive atmosphere occurring and its consequences will therefore vary from mine to mine, depending on the type of mine, its layout, the mineral being extracted and the likelihood of firedamp and/or combustible dust occurring.

In **coal mining**, firedamp and coal dust naturally associated with the coal is released by the activity of the miners. Therefore, the potential explosion risk is greater as a result of explosive air/gas or air/dust mixtures forming that cannot be totally excluded by the preventive measures taken.

Firedamp/air mixtures are usually diluted by the ventilation and evacuated to the surface via the mine workings so that the gas content in normal operation is kept far below the lower explosion limit. However, as a result of system malfunction (e.g. fan failure), sudden release of large gas quantities (gas outbursts) or intensified gas release caused by decreasing air pressure or by increased coal production, the permissible gas concentration thresholds may be exceeded. The explosive atmosphere caused in this way, even though limited in space and/or time, can cause a hazard not just at its point of origin but also in the escape roads, waste air paths and other connected mine structures in the mine layout.

Coal dust/air mixtures are usually neutralized at the dust source by water sprays, dust removal systems on heading machines and/or treating with inert dust in order to reduce the explosive potential. However, an explosion hazard can exist if explosive dust can become airborne, e.g. at transfer points, in bunkers and other conveying systems.

In contrast to surface industries, in gassy mines electrical and non-electrical equipment and mining personnel are in permanent contact with gas and/or dust/air mixtures which, under unfavourable conditions, can constitute explosive atmospheres. Accordingly, particularly stringent safety requirements are in force for explosion protection and escape possibilities in the event of a hazard. Due to the possibly devastating effects of underground gas/dust explosions, underground mining is permitted only well outside the explosion range.

In gassy mines, the decision as to whether or not mine workers can operate in a particular workplace depends upon the atmospheric conditions prevailing at the time. Traditionally, a factor of safety is also introduced so that it is common practice throughout the European member states for equipment to be de-energized or made safe and for miners to be withdrawn from their workplace if the atmospheric conditions attain a specific percentage of the lower explosion limit (LEL) of methane (firedamp) in air as defined by the relevant national legislation of the member states.

NOTE 2 The current limit values for disconnecting equipment and withdrawing personnel are different in each member state.

Two different ranges of explosive atmospheres originating from the intended installation and use of the equipment are taken into account when dealing with requirements for Equipment categories M 2 and M 1:

- **potentially explosive atmosphere** — range between 0 % and below LEL or above UEL up to 100 % of firedamp in air;
- **explosive atmosphere** — range between LEL and UEL of firedamp in air.

In mine workings with explosive atmospheres, only Equipment category M 1 equipment is acceptable as it has a very high level of protection. Equipment category M 1 equipment, e.g. telephones or gas measuring equipment can continue to be operated in explosive atmospheres, because they are safe even in the event of rare equipment faults. This is ensured by the existence of two independent protective measures or double fail-safe systems.

In mine workings with potentially explosive atmospheres, both Equipment categories M 1 and M 2 equipment may be used. Equipment category M 2 equipment may be used as it has a high level of protection and is suitable for the severe conditions in mining. In an explosive atmospheres, Equipment category M 2 equipment needs to be capable of being disconnected or made safe.

NOTE 3 Under special conditions, it might be necessary to operate Equipment category M 2 equipment in an explosive atmosphere for a short time, e.g. when personnel are escaping from mine workings with high firedamp readings with their Equipment category M 2 caplights switched on, when personnel are being recovered by the mine rescue service or the firedamp extraction system has been started up.

Equipment category M 1 and M 2 equipment can only be operated with the characteristics specified by the manufacturer as only then do they ensure the relevant level of protection. The manufacturer specifies the operating characteristics for the equipment.

In practice, national regulations require that gas measurements be taken at certain points and at specific intervals and suitable measures are taken to de-energize the equipment either manually or automatically if the firedamp concentration reaches a certain value. A subdivision into hazards caused by an explosive gas atmosphere and those caused by an explosive dust atmosphere is, in contrast to EN 1127-1:2019, not advisable in underground mining as the hazard to the mine workings can be caused simultaneously by firedamp and by clouds of combustible dust. Therefore, the explosion protection measures will always cover both, i.e. the hazard caused by firedamp and the one caused by combustible dust.

The definition of potentially explosive atmospheres in coal mines susceptible to firedamp based on Directive 2014/34/EU extends the definition of potentially explosive atmosphere to include combustible dust as well as firedamp. Extensive research has shown that the minimum ignition energy (MIE) of coal dust/air mixtures is several hundred times that of firedamp/air mixtures and that the maximum experimental safe gap (MESG) of coal dust particles is more than double that for firedamp. It is therefore reasonable to assume that the equipment, protective systems and components which are designed and constructed for use in firedamp/air mixtures are also suitable for use in coal dust/air mixtures.

The comparison of methane and coal dust experimental data relates only to atmospheres (mixtures of gas and/or dust with air), not to dust layers. Additional precautions are required when considering coal

prEN 1127-2:2026 (E)

dust deposits as, in this case, the maximum surface temperature of the equipment (limited to 150 °C for Group I equipment) on which the deposits can form can be limited to values below the minimum ignition temperature.

It is vital to bear in mind that in both coal mines and non-coal mines there can be areas where firedamp does not occur but where there is a risk of explosion because of combustible dust.

Sample Document

get full document from standards.iteh.ai

1 Scope

This document specifies methods for explosion prevention and protection in mining by outlining the basic concepts and methodology for the design and construction of equipment, protective systems and components.

This document applies to Group I equipment, protective systems and components intended for use in underground parts of mines and those parts of their surface installations at risk from firedamp and/or combustible dust.

NOTE Detailed information on specific equipment, protective systems and components is contained in the relevant individual standards. Safety-relevant data regarding flammable materials and explosive atmospheres are required for the design and construction of the explosion protection measures.

This document specifies methods for the identification and assessment of hazardous situations that may lead to explosions and describes the design and construction measures appropriate for the required safety. This is achieved by:

- risk assessment;
- risk reduction.

The safety of equipment, protective systems, and components can be achieved by eliminating hazards and/or limiting the risk, i.e.:

- a) by appropriate design (without using safeguarding);
- b) by safeguarding;
- c) by information for use;
- d) by any other preventive measures.

Measures in accordance with a) (prevention) and b) (protection) against explosions are dealt with in Clause 6 of this document; measures according to c) against explosions are dealt with in Clause 7 of this document. Measures in accordance with d) are not described in this document. They are dealt with in EN ISO 12100:2010, Clause 6.

The preventive and protective measures described in this document will not provide the required level of protection unless the equipment, protective systems and components are operated in line with their intended use and are installed and maintained according to the relevant codes of practice or requirements.

This document is applicable to any equipment, protective systems and components intended to be used in potentially explosive atmospheres. These atmospheres can arise from flammable materials processed, used or released by the equipment, protective systems and components or from materials in the vicinity of the equipment, protective systems and components and/or from the materials of construction of the equipment, protective systems and components.

As shot firing can release potentially explosive atmospheres, this document is also applicable to the equipment used for shot firing, apart from the explosives and detonators.

This document is applicable to equipment, protective systems and components at all stages of use.

This document is not applicable to:

- medical devices intended for use in a medical environment;

prEN 1127-2:2026 (E)

- equipment, protective systems and components where the explosion hazard results exclusively from the presence of explosives or unstable chemical substances;
- equipment, protective systems and components where the explosion can result from reaction of substances with oxidising agents other than atmospheric oxygen or by other hazardous reactions or conditions other than atmospheric conditions;
- equipment intended for use in domestic and non-commercial environments where explosive atmospheres may only rarely be created and solely as a result of the accidental leakage of fuel gas;
- personal protective equipment covered by Regulation (EU) 2016/425; the design and construction of systems containing desired, controlled combustion processes, unless they can act as ignition sources in potentially explosive atmospheres;
- mines where firedamp and/or combustible dust are not naturally present and surface installations such as coal preparation plants, power plants, coke oven plants etc. in which an explosive atmosphere can be present, but which are not part of a coal mine. These are covered by EN 1127-1:2019.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 1127-1:2019, *Explosive atmospheres — Explosion prevention and protection — Part 1: Basic concepts and methodology*

EN 13237:2024, *Potentially explosive atmospheres — Terms and definitions for equipment and protective systems intended for use in potentially explosive atmospheres*

EN 14373:2021+A1:2025, *Explosion suppression systems*

EN 14460:2018, *Explosion resistant equipment*

EN 14797:2006, *Explosion venting devices*

EN 15089:2009, *Explosion isolation systems*

EN 50303:2000, *Group I, category M1 equipment intended to remain functional in atmospheres endangered by firedamp and/or coal dust*

EN IEC 60079-0:2018,¹ *Explosive atmospheres — Part 0: Equipment — General requirements (IEC 60079-0:2017)*

EN 60079-2:2014,² *Explosive atmospheres — Part 2: Equipment protection by pressurized enclosure “p” (IEC 60079-2:2014)*

¹ As impacted by EN IEC 60079-0:2018/AC:2020 and EN IEC 60079-0:2018/A11:2024.

² As impacted by EN 60079-2:2014/AC:2015.