
Satelitske zemeljske postaje in sistemi (SES) - Mobilne zemeljske postaje (MES), vključno z ročnimi zemeljskimi postajami za S-PCN, ki delujejo v frekvenčnem pasu 1,6 GHz/2,4 GHz, pri mobilnih satelitskih storitvah (MSS) - Harmonizirani standard za dostop do radijskega spektra

Satellite Earth Stations and Systems (SES) - Mobile Earth Stations (MES), including handheld earth stations, for Satellite Personal Communications Networks (S-PCN) operating in the 1,6 GHz/2,4 GHz frequency band under the Mobile Satellite Service (MSS) - Harmonised Standard for access to radio spectrum

Sample Document

get full document from standards.iteh.ai

Ta slovenski standard je istoveten z: ETSI EN 301 441 V2.2.0 (2026-07)

ICS:

33.060.30	Radiorelejni in fiksni satelitski komunikacijski sistemi	Radio relay and fixed satellite communications systems
33.070.99	Druge mobilne storitve	Other mobile services

oSIST prEN 301 441 V2.2.0:2026 **en**

Sample Document

get full document from standards.iteh.ai

Draft ETSI EN 301 441 V2.2.0 (2026-07)



**Satellite Earth Stations and Systems (SES);
Mobile Earth Stations (MES),
including handheld earth stations, for Satellite Personal
Communications Networks (S-PCN) operating
in the 1,6 GHz/2,4 GHz frequency band
under the Mobile Satellite Service (MSS);
Harmonised Standard for access to radio spectrum**

Reference

REN/SES-00442

Keywords
earth station, MES, MSS, regulation, satellite,
S-PCN

ETSI
650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program..

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part of this document may be reproduced in any form, by any means and in any media, without the prior written authorization of ETSI and except as expressly permitted below.

By way of exception and when the document is a normative deliverable (European Standard (EN), Technical Specification (TS), Group Specification (GS) or ETSI Standard (ES)), ETSI authorizes to reproduce and incorporate into products, services and technical documentation only those extracts (e.g. templates) that are strictly necessary for the technical implementation of the normative deliverable, to ensure compliance with the latter. Nothing in this notice shall be construed as limiting any mandatory exceptions to copyright provided by applicable law.

© ETSI 2026.
All rights reserved.

Contents

Intellectual Property Rights	6
Foreword.....	6
Modal verbs terminology.....	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	9
3 Definition of terms, symbols and abbreviations.....	9
3.1 Terms.....	9
3.2 Symbols.....	11
3.3 Abbreviations	11
4 Technical requirements specifications	12
4.1 Environmental profile.....	12
4.1.1 General.....	12
4.1.2 Temperature.....	12
4.1.3 Voltage.....	12
4.2 Conformance requirements	12
4.2.1 Unwanted emissions outside the band 1 610 MHz to 1 626,5 MHz and the band 1 626,5 MHz to 1 628,5 MHz (carrier-on).....	12
4.2.1.1 Justification	12
4.2.1.2 Technical requirements	12
4.2.1.3 Conformance test	13
4.2.2 Unwanted emissions within the band 1 610 MHz to 1 626,5 MHz and the band 1 626,5 MHz to 1 628,5 MHz (carrier-on).....	13
4.2.2.1 Justification	13
4.2.2.2 Technical requirements	13
4.2.2.3 Conformance test	15
4.2.3 EIRP density within the operational band.....	15
4.2.3.1 Justification	15
4.2.3.2 Technical requirements	15
4.2.3.3 Conformance test	15
4.2.4 Unwanted emissions in carrier-off state.....	15
4.2.4.1 Justification	15
4.2.4.2 Technical requirements	15
4.2.4.3 Conformance test	16
4.2.5 MES Control and Monitoring Functions (CMF)	16
4.2.5.1 Void.....	16
4.2.5.2 Void.....	16
4.2.5.3 Network control authorization	16
4.2.5.3.1 Justification	16
4.2.5.3.2 Technical requirements.....	16
4.2.5.3.3 Conformance test.....	16
4.2.5.4 Network control reception.....	16
4.2.5.4.1 Transmission disable/enable.....	16
4.2.5.4.2 Transmit frequency control	17
4.2.5.5 Fellow radio stations in a dual-mode or multi-mode terminal	17
4.2.5.5.1 Justification	17
4.2.5.5.2 Technical requirements.....	17
4.2.5.5.3 Conformance test.....	17
4.2.6 Equipment identity.....	17
4.2.6.1 Justification	17
4.2.6.2 Technical requirements	17
4.2.6.3 Conformance test	17
4.2.7 Protection of the radio astronomy service operation in the band 1 610,6 MHz to 1 613,8 MHz.....	18

4.2.7.1	Justification	18
4.2.7.2	Technical requirements	18
4.2.7.3	Conformance test	18
4.2.8	Receiver Adjacent Channel Selectivity.....	18
4.2.8.1	Justification	18
4.2.8.2	Technical requirements	18
4.2.8.3	Conformance test	18
4.2.9	Receiver Blocking Characteristics	18
4.2.9.1	Justification	18
4.2.9.2	Technical requirements	19
4.2.9.3	Conformance test	19
5	Testing for compliance with technical requirements.....	19
5.1	Environmental conditions for testing	19
5.1.0	General.....	19
5.1.1	Specification of the environmental test conditions	19
5.1.2	Tests under extreme voltage conditions.....	20
5.2	Essential radio test suites.....	20
5.2.1	General.....	20
5.2.1.1	Presentation of equipment for testing purposes.....	20
5.2.1.2	Description of equipment	20
5.2.1.3	Testing of host-connected equipment and plug-in modules	21
5.2.1.3.1	Test set up arrangements	21
5.2.1.3.2	Set up for combined equipment	21
5.2.1.3.3	Set up for the use of a test jig	21
5.2.1.4	CMF simulator	21
5.2.1.5	General test requirements.....	22
5.2.1.5.1	MES test modes	22
5.2.1.5.2	Test arrangement for control and monitoring tests	22
5.2.1.5.3	Void.....	23
5.2.1.5.4	Test methods for MES RF emissions according to the equipment type	23
5.2.1.5.5	Procedures for measurement of radiated emissions.....	24
5.2.1.5.6	Procedures for measurement of MES RF conducted emissions	28
5.2.1.5.7	Void.....	30
5.2.1.5.8	Test report.....	30
5.2.2	Unwanted emissions outside the band 1 610 MHz to 1 626,5 MHz and the band 1 626,5 MHz to 1 628,5 MHz (carrier-on).....	30
5.2.2.1	Method of test	30
5.2.2.2	Peak measurement.....	30
5.2.2.3	Average measurement.....	30
5.2.2.4	Test requirements.....	31
5.2.3	Unwanted emissions within the band 1 610 MHz to 1 626,5 MHz and the band 1 626,5 MHz to 1 628,5 MHz (carrier-on).....	31
5.2.3.1	Method of test	31
5.2.3.2	Measurement method	31
5.2.3.3	Test requirements.....	32
5.2.4	EIRP density within the operational band.....	32
5.2.4.1	Method of test	32
5.2.4.2	Peak limit test.....	33
5.2.4.3	Mean limit test	33
5.2.4.4	Test requirements.....	33
5.2.5	Unwanted emissions in carrier-off state.....	33
5.2.5.1	Method of test	33
5.2.5.2	Measurement method	34
5.2.5.3	Test requirements.....	34
5.2.6	MES Control and Monitoring Functions (CMF)	34
5.2.6.1	Void.....	34
5.2.6.2	Void.....	34
5.2.6.3	Network control authorization	34
5.2.6.3.1	Method of test.....	34
5.2.6.3.2	Test procedure	34
5.2.6.3.3	Test requirement	35

5.2.6.4	Network control reception.....	35
5.2.6.4.1	Transmission disable/enable	35
5.2.6.4.2	Transmit frequency control	36
5.2.6.5	Fellow radio stations in a dual-mode or multi-mode terminal	37
5.2.6.5.1	Method of test.....	37
5.2.6.5.2	Test procedure	37
5.2.6.5.3	Test requirements	37
5.2.7	Equipment identity.....	37
5.2.7.1	Method of test	37
5.2.7.2	Test procedure.....	37
5.2.7.3	Test requirements.....	37
5.2.8	Receiver Adjacent Channel Selectivity.....	37
5.2.8.1	General	37
5.2.8.2	Test set-up	37
5.2.8.3	Test procedure.....	38
5.2.9	Receiver Blocking Characteristics	38
5.2.9.1	General	38
5.2.9.2	Test set-up	38
5.2.9.3	Test procedure.....	38
Annex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	39
Annex B (informative):	Explanation of nominated bandwidth.....	42
B.1	Introduction	42
B.2	Interpretation of Parameters $[B_n, f_c, a, b]$	42
B.3	Choice of nominated bandwidth.....	42
B.4	Maximum value for nominated bandwidth	44
Annex C (informative):	Laboratory Test Equipment and its Maximum measurement uncertainty.....	47
Annex D (informative):	Vibration characteristics.....	48
Annex E (informative):	Bibliography.....	49
Annex F (informative):	Change history	50
History		51

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables (European Standard (EN), Technical Specification (TS), Group Specification (GS) or ETSI Standard (ES)) may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Satellite Earth Stations and Systems (SES), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI Standardisation Request deliverable Approval Procedure (SRdAP).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.2] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.3].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Sample Document

get full document from standards.iteh.ai

1 Scope

The present document applies to Mobile Earth Station (MES) radio equipment which have the following characteristics:

- the MES has both transmit and receive capabilities and operate in a Satellite-Personal Communications Network (S-PCN). An S-PCN MES can be a handheld, portable, vehicle-mounted, host connected, semi-fixed or fixed equipment, or can be an element in a multi-mode terminal. It consists of a number of modules with associated connections and user interface, or can be a self-contained single unit;
- these MESs are controlled and monitored by Control Monitoring Functions (CMF). The CMF is outside the scope of the present document;
- if the MES is an element in a multi-mode terminal, unless otherwise stated in the present document, its requirements apply only to the S-PCN MES element of the terminal operating in the MSS frequency bands given in table 1;
- the MES is capable in operating in all or part of the frequency bands shown in table 1.

Table 1: Mobile Satellite Service (MSS) frequency bands

MES	MSS frequency bands
Transmit	1 610 MHz to 1 626,5 MHz
Receive	1 613,8 MHz to 1 626,5 MHz
Receive	2 483,5 MHz to 2 500,0 MHz

NOTE: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.3] is given in annex A.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found in the [ETSI docbox](#).

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

The following referenced documents are necessary for the application of the present document.

- [1] Void.
- [2] [Recommendation ITU-T O.153 \(10/92\)](#): "Basic parameters for the measurement of error performance at bit rates below the primary rate".
- [3] Void.
- [4] Void.
- [5] Void.
- [6] [Final Acts of the World Radiocommunication Conference \(WRC '95\); Geneva 1995](#).
- [7] [IEC 60068-2-1 \(2025\)](#): "Environmental testing - Part 2: Tests. Tests A: Cold".
- [8] [IEC 60068-2-2 \(2025\)](#): "Environmental testing - Part 2: Tests. Tests B: Dry heat".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

The following referenced documents may be useful in implementing an ETSI deliverable or add to the reader's understanding, but are not required for conformance to the present document.

- [i.1] Void.
- [i.2] [Commission Implementing Decision C\(2015\) 5376](#) final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.3] [Directive 2014/53/EU](#) of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.4] [IEC 60068-2-64:2008+AMD1:2019 CSV](#): "Environmental testing. Part 2-64: Tests. Test Fh: Vibration, broadband random and guidance".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the following terms apply:

carrier-on state (allocated a channel): state in which the MES is transmitting a carrier

carrier-off state (idle mode): radio state in which the MES does not actually transmit a carrier

CMF control message: message, normally originating from a network, to a specified terminal or set of terminals of the network which indicates to the terminal or set of terminals that it/they carry out some specific action or enter or maintain some specific state

NOTE: For test purposes CMF control messages can originate from CMF Simulator.

conducted measurement: measurement of emissions from an antenna port of the MES made by direct wired connection to the port

environmental profile: range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

Equivalent Isotropically Radiated Power (EIRP): product of transmitter power and maximum antenna gain, equivalent to an isotropic source radiating uniformly in all directions

fellow radio station: another radio station operating in the same service, frequency band, or coordination environment as the station in question, such that it shares allocated spectrum with the mobile satellite earth terminal

handheld: MES which is self-contained and is small enough and light enough to be carried and used during a call with one hand

host-connected: MES for which connection to or integration with host equipment is necessary to offer functionality

host equipment: any equipment which has a complete user functionality when not connected to the MES, and to which the MES provides additional functionality, and to which connection is necessary for the MES to offer functionality

in-band signals: signals which are located in the operating band plus an offset of 10 MHz outside this operating band

Installable Equipment (IE), Internally Mounted Equipment (IME) And Externally Mounted Equipment (EME): Installable Equipment (IE) is an equipment which is intended to be installed in a vehicle

NOTE: An IE consist of one or several interconnected modules. The IE is composed of modules intended to be externally mounted as defined for the intended use of the MES, and defined as Externally Mounted Equipment (EME) and the remaining modules(s) as Internally Mounted Equipment (IME).

Laboratory Test Equipment: logical grouping that contains the standard test equipment provided by a test laboratory

MSS band: continuous range of frequencies allocated by the ITU to the MSS

multi-mode: equipment that accommodates radio stations of different radio networks

narrow-band system: narrow-band system is one in which the nominal carrier frequency spacing for MESs in the earth-to-space direction is less than 300 kHz

network control channel: channel by which an MES receives general control information from the CMF(originated by a network control facility) of its S-PCN

nominated bandwidth (Bn): Bandwidth of the Mobile Earth Station (MES) radio frequency transmission which is wide enough to encompass all spectral elements of the transmission

NOTE 1: The nominated bandwidth is centred on the transmit frequency and does not exceed 5 times the occupied bandwidth.

NOTE 2: The nominated bandwidth is wide enough to take account of the transmit carrier frequency stability. This definition is chosen to allow flexibility regarding adjacent channel interference levels which will be taken into account by operational procedures depending on the exact transponder carrier assignment situation.

NOTE 3: The Bn is defined relative to the MES actual carrier frequency f_c .

Bn is the width of the frequency interval ($f_c - a$, $f_c + b$), where a and b can vary with f_c which are defined for the intended use of the MES. The frequency interval ($f_c - a$, $f_c + b$) does not encompass more than either:

- i) when $a = b$, 4 or less carrier frequencies for narrow-band systems;
- ii) when $a \neq b$, 1 nominal carrier frequency for narrow-band systems; or
- iii) 1 nominal carrier frequency for wide-band systems.

The frequency interval ($f_c - a$, $f_c + b$) remains within the operational band of the MES.

NOTE 4: Further explanation of nominated bandwidth is presented in annex B.

operational band: sub-portion of the 1 610 MHz to 1 626,5 MHz band which has been assigned in the earth-to-space direction to the MSS network within which the MES is operating

Portable Equipment (PE): generally intended to be self-contained, free standing and portable. A PE would normally consist of a single module, but can consist of several interconnected modules

radiated measurement: measurement of an actual radiated field

Special Test Equipment (STE): equipment which allows a test laboratory to control the MES so that the tests required by the present document can be performed

test laboratory: laboratory which performs the conformance testing of the MES against the present document

test load: test load is a substantially non-reactive, non-radiating power attenuator which is capable of safely dissipating the power from the transmitter(s)

unwanted emissions: unwanted emissions are those falling outside the nominated bandwidth in the carrier-on state, and those generated in the carrier-off state

wide-band system: wide-band system is one in which the nominal carrier frequency spacing for MESs in the Earth-to-Space direction is equal to or greater than 300 kHz

3.2 Symbols

Void.

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AK-R	Air Kerma Rate
ASD	Acceleration Spectral Density
BE _L	Lower Band Edge of the operating band
BE _U	Upper Band Edge of the operating band
B _n	Nominated Bandwidth
BW	Bandwidth
CDMA	Code Division Multiple Access
CMF	Control and Monitoring Functions
CW	Continuous Wave
dBW	decibels relative to 1 Watt
EFTA	European Free Trade Association
EIRP	Equivalent Isotropically Radiated Power
EMC	Electro-Magnetic Compatibility
EME	Externally Mounted Equipment
EN	European Standard
ERM	Electromagnetic compatibility and Radio spectrum Matters
ETS	European Telecommunication Standard
EU	European Union
EUT	Equipment Under Test
IE	Installable Equipment
IEC	International Electrotechnical Commission
IME	Internally Mounted Equipment
ITU	International Telecommunication Union
ITU-T	ITU Telecommunication Standardization Sector
MES	Mobile Earth Station
MIC	MES unique Identification Code (within its S-PCN)
MSS	Mobile Satellite Service
OATS	Open Area Test Site
PCN	Personal Communications Network
PE	Portable Equipment
R&TTE	Radio and Telecommunications Terminal Equipment
RE	Radio Equipment
RED	Radio Equipment Directive
RF	Radio Frequency
SNR	Signal to Noise Ratio
S-PCN	Satellite Personal Communications Network
STE	Special Test Equipment
TBR	Technical Basis for Regulation
WRC	World Radiocommunication Conference
ZVEI	Zentralverband Elektrotechnik- und Elektronik-industrie

4 Technical requirements specifications

4.1 Environmental profile

4.1.1 General

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be in accordance with its intended use, but as a minimum, shall be that specified in the test conditions contained in the present document. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the specified operational environmental profile defined by its intended use.

The environmental profile for operation of the equipment shall include the ranges of humidity, temperature and supply voltage.

4.1.2 Temperature

The MES shall fulfil all the requirements in the full temperature ranges of:

- -10 °C to +55 °C;

taken from IEC publications 60068-2-1 [7] and 60068-2-2 [8].

4.1.3 Voltage

The nominal, lower and the higher extreme voltages shall be defined for the intended use of the MES and provided with the EUT documentation.

The MES shall fulfil all the requirements in the full voltage range between the extreme voltages.

4.2 Conformance requirements

4.2.1 Unwanted emissions outside the band 1 610 MHz to 1 626,5 MHz and the band 1 626,5 MHz to 1 628,5 MHz (carrier-on)

4.2.1.1 Justification

Protection of other radio services operating outside the band 1 610 MHz to 1 628,5 MHz from emissions caused by S-PCN MESs operating within the band 1 610 MHz to 1 626,5 MHz.

4.2.1.2 Technical requirements

The maximum EIRP density of the unwanted emissions from the MES outside the band 1 610,0 MHz to 1 626,5 MHz and the band 1 626,5 MHz to 1 628,5 MHz shall not exceed the limits in table 3.

In table 3, whenever a change of limit between adjacent frequency bands occurs, the lower of the two limits shall apply at the transition frequency.

Table 2: Void

Table 3: Maximum unwanted emissions outside the band 1 610 MHz to 1 626,5 MHz and the band 1 626,5 MHz to 1 628,5 MHz

Frequency (MHz)	Carrier-on		
	EIRP (dBW)	Measurement bandwidth	Measurement method
0,1 to 30	-66	10 kHz	Peak-hold
30 to 1 000	-66	100 kHz	Peak-hold
1 000 to 1 559	-60	1 MHz	Average
1 559 to 1 580,42	-70	1 MHz	Average (see note 1)
1 580,42 to 1 605	-70	1 MHz	Average
1 605 to 1 610	-70 to -10 (see note 2)	1 MHz	Average
1 610 to 1 626,5	Not applicable	Not applicable	Not applicable
1 626,5 to 1 628,5	Not applicable	Not applicable	Not applicable
1 628,5 to 1 631,5	-60	30 kHz	Average
1 631,5 to 1 636,5	-60	100 kHz	Average
1 636,5 to 1 646,5	-60	300 kHz	Average
1 646,5 to 1 666,5	-60	1 MHz	Average
1 666,5 to 2 200	-60	3 MHz	Average
2 200 to 12 750	-60	3 MHz	Peak hold

NOTE 1: In the sub-band 1 573,42 MHz to 1 580,42 MHz, the average measurement time is 20 ms.
NOTE 2: Linearly interpolated in dBW vs. frequency offset.

The conformance requirements apply for the full range of environmental conditions corresponding to the type of equipment as specified in clause 4.1.

4.2.1.3 Conformance test

Conformance tests are described in clause 5.2.2.

4.2.2 Unwanted emissions within the band 1 610 MHz to 1 626,5 MHz and the band 1 626,5 MHz to 1 628,5 MHz (carrier-on)

4.2.2.1 Justification

Protection of radio services and systems operating within the frequency band 1 610 to 1 628,5 MHz from unwanted emissions caused by S-PCN MESs operating in the band 1 610 MHz to 1 626,5 MHz.

4.2.2.2 Technical requirements

The maximum EIRP spectral density of the unwanted emissions from the MES within the band 1 610 MHz to 1 628,5 MHz shall not exceed the limits in tables 4, 5 or 6, as applicable.

In tables 4, 5 and 6, whenever a change of limit between adjacent frequency bands occurs, the lower of the two limits shall apply at the transition frequency.

When conflicts between multiple requirements exist, the more stringent requirement applies.