
Okoljski inženiring (EE) - Napajanje opreme v dostopovnem omrežju

Environmental Engineering (EE) - Powering of equipment in access network

Ta slovenski standard je istoveten z: ETSI EN 302 099 V2.3.0 (2026-09)

ICS:

19.040	Preskušanje v zvezi z okoljem	Environmental testing
33.050.01	Telekomunikacijska terminalska oprema na splošno	Telecommunication terminal equipment in general

oSIST prEN 302 099 V2.3.0:2026**en**

Sample Document

get full document from standards.iteh.ai

Draft ETSI EN 302 099 V2.3.0 (2026-09)



Environmental Engineering (EE); Powering of equipment in access network

Sample Document

get full document from standards.iteh.ai

ReferenceREN/EE-027017

Keywordsaccess, network, power supply, remote

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part of this document may be reproduced in any form, by any means and in any media, without the prior written authorization of ETSI and except as expressly permitted below.

By way of exception and when the document is a normative deliverable (European Standard (EN), Technical Specification (TS), Group Specification (GS) or ETSI Standard (ES)), ETSI authorizes to reproduce and incorporate into products, services and technical documentation only those extracts (e.g. templates) that are strictly necessary for the technical implementation of the normative deliverable, to ensure compliance with the latter. Nothing in this notice shall be construed as limiting any mandatory exceptions to copyright provided by applicable law.

© ETSI 2026.
All rights reserved.

Contents

Intellectual Property Rights	5
Foreword.....	5
Modal verbs terminology.....	5
1 Scope	6
2 References	6
2.1 Normative references	6
2.2 Informative references.....	7
3 Definition of terms, symbols and abbreviations.....	9
3.1 Terms.....	9
3.2 Symbols.....	10
3.3 Abbreviations	11
4 Introduction	12
4.1 General	12
5 Powering configurations.....	12
5.0 General	12
5.1 Remote powering architectures	15
5.1.1 Centralized powering architecture configurations	15
5.1.2 Cluster powering architecture configurations	17
5.2 Local powering architecture configurations	19
5.2.1 TE of access network, common to several customers.....	19
5.2.2 TE of access network, at customer premises	20
5.2.3 TE in access network reverse powered from customer premises.....	21
5.2.3.1 Reference configuration introduction.....	21
5.2.3.2 Wiring and electrical limitation consideration	21
5.2.3.3 Reverse power, voltage and current limits	21
6 Effect of the technologies on the powering strategy	22
6.0 General	22
6.1 Powering strategy of family 1: metallic links.....	23
6.2 Powering strategy of family 2: non-metallic links	24
7 Requirements for local powering	24
7.1 TE including the power plant	24
7.2 TE powered by a DC voltage nominal -48 VDC or up to 400 VDC local power unit	24
7.3 TE powered by a LPU with a DC voltage other than -48 VDC or up to 400 VDC.....	25
7.4 TE powered by a nominal AC voltage of 230 VAC, 50 Hz local power unit	25
8 Requirements for remote powering.....	25
8.0 Remote powering solutions	25
8.1 Input of the Remote Power Unit (RPU)	25
8.2 Output characteristics of the Remote Powering system	26
8.2.1 Remote powering output with an RFT-V circuit	26
8.2.2 Remote powering output with an RFT-C circuit.....	26
8.2.3 Remote powering output at up to 400 VDC	26
8.2.3.0 General consideration on line electrical parameters and operation	26
8.2.3.1 Steady state output voltage and current.....	26
8.2.3.2 Transient state output voltage	26
8.2.3.3 Architecture of RP distribution for reliable and safe operation management	26
8.2.3.4 Requirements for stable and safe operation	27
8.3 Input characteristics of remote power receiver.....	28
8.3.1 RFT-V remote power receiver input in voltage mode	28
8.3.2 RFT-C remote power receiver input in current mode.....	28
8.3.3 Remote Power Receiver (RPR) input	28
8.3.4 Remote Power Receiver (RPR) output	29

9	Power source interruption management	29
10	Power management	29
11	Safety, EMC, protection.....	32
11.1	Product Safety	32
11.2	EMC	33
11.3	Protection/resistibility	33
11.4	Earthing and bonding of access network powering solutions.....	33
11.5	Wiring requirements of remote power feeding to TE through power cable at up to 400 VDC voltage mode.....	34
11.5.1	Protection against electric shock.....	34
11.5.2	Protection against fire	34
11.5.3	Protection against physical damage	35
12	Environmental conditions.....	35
Annex A (informative):	Statistical data on electrical power supply availability, from the Low Voltage (LV) public grid (mains) in various European countries	36
Annex B (informative):	Battery sizing.....	39
B.0	General rules	39
B.1	Back-up power	40
B.2	Autonomy of the back-up power.....	40
B.3	Battery Energy Storage Technology	41
B.4	Battery utilization and state of health test	41
Annex C (informative):	Comparative reliability approach of remote powering versus local powering	42
Annex D (informative):	Bibliography.....	45
Annex E (informative):	Change history	46
History		47

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables (European Standard (EN), Technical Specification (TS), Group Specification (GS) or ETSI Standard (ES)) may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This draft European Standard (EN) has been produced by ETSI Technical Committee Environmental Engineering (EE), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI EN Approval Procedure (ENAP).

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

Modal verbs terminology

In the present document **"shall"**, **"shall not"**, **"should"**, **"should not"**, **"may"**, **"need not"**, **"will"**, **"will not"**, **"can"** and **"cannot"** are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and **"must not"** are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document describes the principles for powering of Telecommunications Equipment (TE) in access networks (both traditional copper based and Next Generation fibre and/or hybrid based) and contains requirements for the powering systems, laying down:

- the characteristics of the input and output interfaces of the power units; the recommendations for TE power protection, also regarding network integrity and public services availability requirements;
- the management data, necessary to guarantee the required availability of the network and provided public services and to ensure the maintenance of the TE power units.

The present document takes into account the innovative characteristics of fibre-based access network equipment and considers the intrinsic limitations of local power plants and power distribution when ICT equipment is installed inside telecom centre, local exchanges, street cabinets or inside buildings: it goes from "complete integration of the power plant in the TE" to "remote power feeding from a distant power plant".

The present document provides detailed information in annex A on the improved reliability of public electric power grid and on the improved reliability and availability of new fibre-based NGA network. It should be considered that, for street cabinet TE, the local power scenario is common, and, in that case, the main power supply availability characteristics are mainly based on electrical energy provider's performance.

The present document applies to the powering of all equipment of the access network (copper, fibre or radio networks) located inside or outside telecommunications centres or local exchanges, differentiating the applicable and sustainable power protection requirements. The access network is defined as the part of the telecommunications network, which comprises the network termination (passive or active) that is installed inside customer premises and the first exchange that can be also the broadband local exchange.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found in the [ETSI docbox](#).

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

The following referenced documents are necessary for the application of the present document.

- [1] [ETSI EN 300 132-1](#): "Environmental Engineering (EE); Power supply interface at the input to Information and Communication Technology (ICT) equipment; Part 1: Alternating Current (AC)".
- [2] [ETSI EN 300 132-2](#): "Environmental Engineering (EE); Power supply interface at the input of Information and Communication Technology (ICT) equipment; Part 2: -48 V Direct Current (DC)".
- [3] [IEC 62368-3](#): "Audio/video, information and communication technology equipment - Part 3: Safety aspects for DC power transfer through communication cables and ports".
- [4] [EN 60038](#): "CENELEC standard Voltages", (produced by CENELEC).
- [5] [EN 60664-1](#): "Insulation coordination for equipment within low-voltage systems - Part 1: Principles, requirements and tests", (produced by CENELEC).
- [6] [EN 50310](#): "Application of equipotential bonding and earthing in buildings with information technology equipment", (produced by CENELEC).

- [7] [ETSI EN 300 253](#): "Environmental Engineering (EE); Earthing and bonding of ICT equipment powered by -48 VDC in telecom and data centres".
- [8] [Recommendation ITU-T K.35](#): "Bonding configurations and earthing at remote electronic sites".
- [9] [Recommendation ITU-T K.45](#): "Resistibility of telecommunication equipment installed in the access and trunk networks to overvoltages and overcurrents".
- [10] [ETSI ES 203 215](#): "Environmental Engineering (EE); Measurement Methods and Limits for Power Consumption in Broadband Telecommunication Networks Equipment".
- [11] [ETSI EN 300 132-3](#): "Environmental Engineering (EE); Power supply interface at the input of Information and Communication Technology (ICT) equipment; Part 3: Up to 400 V Direct Current (DC)".
- [12] [ETSI ES 202 336-1](#): "Environmental Engineering (EE); Monitoring and Control Interface for Infrastructure Equipment (Power, Cooling and Building Environment Systems used in Telecommunication Networks); Part 1: Generic Interface".
- [13] [ETSI TS 101 548-1](#): "Access, Terminals, Transmission and Multiplexing (ATTM); European Requirements for Reverse Powering of Remote Access Equipment; Part 1: Twisted pair networks".
- [14] [ETSI EN 301 605](#): "Environmental Engineering (EE); Earthing and bonding of 400 VDC data and telecom (ICT) equipment".
- [15] Void.
- [16] [HD 60364 series](#): "Low Voltage electrical installations", produced by CENELEC.
- [17] [ETSI ES 202 336-8](#): "Environmental Engineering (EE); Monitoring and Control Interface for Infrastructure Equipment (Power, Cooling and Building Environment Systems used in Telecommunication Networks); Part 8: Remote Power Feeding System control and monitoring information model".
- [18] [ETSI ES 203 408](#): "Environmental Engineering (EE); Colour and marking of DC cable and connecting devices".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

The following referenced documents may be useful in implementing an ETSI deliverable or add to the reader's understanding, but are not required for conformance to the present document.

- [i.1] ETSI EN 300 019-1-1: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-1: Classification of environmental conditions; Storage".
- [i.2] ETSI EN 300 019-1-3: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1: Classification of environmental conditions; Sub-part 3: Stationary use at weatherprotected locations".
- [i.3] ETSI EN 300 019-1-4: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1: Classification of environmental conditions; Sub-part 4: Stationary use at non-weatherprotected locations".

- [i.4] ETSI EN 300 019-1-8: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-8: Classification of environmental conditions; Stationary use at underground locations".
- [i.5] Void.
- [i.6] Void.
- [i.7] HD 60364-1: "Low-voltage electrical installations - Part 1: Fundamental principles, assessment of general characteristics, definitions", (produced by CENELEC).
- [i.8] ETSI EN 302 999: "Safety; Remote Power Feeding Installations; Safety requirements for the erection and operation of information technology installations with remote power feeding".
- [i.9] ENISA: "Power Supply Dependencies in the Electronic Communications Sector Survey, analysis and recommendations for resilience against power supply failures", December 2013.
- [i.10] Council of European Energy Regulators (CEER): "[7TH CEER-ECRB Benchmarking report on the quality of electricity and gas supply](#)", Ref: C22-EQS-103-03.
- [i.11] [ARERA Annual report](#).
- [i.12] ETSI TS 103 553-1: "Environmental Engineering (EE); Innovative energy storage technology for stationary use; Part 1: Overview".
- [i.13] Void.
- [i.14] Void.
- [i.15] IEC EN 62368-3: "Audio/video, information and communication technology equipment - Part 3: Safety aspects for DC power transfer through communication cables and ports".
- [i.16] Recommendation ITU-T L.1001: "External universal power adapter solutions for stationary information and communication technology devices".
- [i.17] IEC EN 62368-1: "Audio/video, information and communication technology equipment - Part 1: Safety requirements".
- [i.18] [Directive \(EU\) 2022/2555](#) of the European Parliament and of the Council of 14 December 2022 on measures for a high common level of cybersecurity across the Union, amending Regulation (EU) No 910/2014 and Directive (EU) 2018/1972, and repealing Directive (EU) 2016/1148 (NIS 2 Directive).
- [i.19] ETSI EN 303 215: "Environmental Engineering (EE); Measurement methods and limits for power consumption in broadband telecommunication networks equipment".
- [i.20] Void.
- [i.21] TR 62102: "Electrical safety - Classification of interfaces for equipment to be connected to information and communications technology networks", (produced by CENELEC).
- [i.22] Void.
- [i.23] Recommendation ITU-T L.1220 (2017-08): "Innovative energy storage technology for stationary use - Part 1: Overview of energy storage".
- [i.24] Void.
- [i.25] Recommendation ITU-T L.1202 (2015): "Methodologies for evaluating the performance of an up to 400 VDC power feeding system and its environmental impact".
- [i.26] Void.
- [i.27] Broadband Forum oneM2M TR-301: "Architecture and Requirements for Fiber to the Distribution Point".

- [i.28] [ETSI TS 103 553-2](#): "Environmental Engineering (EE); Innovative energy storage technology for stationary use; Part 2: Battery".
- [i.29] [ETSI TS 103 553-3](#): "Environmental Engineering (EE); Innovative energy storage technology for stationary use; Part 3: Supercapacitor".
- [i.30] ETSI ES 202 336-11: "Environmental Engineering (EE); Monitoring and control interface for infrastructure equipment (Power, Cooling and environment systems used in telecommunication networks); Part 11: Battery system with integrated control and monitoring information model".
- [i.31] Recommendation ITU-T I.112: "Vocabulary of terms for ISDNs".
- [i.32] Recommendation ITU-T L.1221: "Innovative energy storage technology for stationary use - Part 2: Battery".
- [i.33] Recommendation ITU-T L.1222: "Innovative energy storage technology for stationary use - Part 3: Supercapacitor technology".
- [i.34] [Recommendation ITU-T L.1200 \(May 2012\)](#): "Direct current power feeding interface up to 400 V at the input to telecommunication and ICT equipment".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the following terms apply:

access gateway: gateway that interworks a significant number of analogue lines to a packet network and is located at the operator's premises

access network: part of a telecommunications network between the Network Termination/Access Gateway and the first switching unit

backfeeding or reverse powering: powering architecture that can supply power to access network units from the customer through its final distribution access copper pair

NOTE: Access network units may be ONU, ONT or remote DSL units.

centralized powering: remote powering in which the remote feeding source is located in a telecommunications centre

cluster powering: remote powering of a cluster of equipment (1 to n items of equipment), in which the remote feeding source is located outside a telecommunications centre

electric energy provider: provider of electrical energy from the public grid (mains)

ES1, ES2, ES3: See IEC EN 62368-1 [i.17].

interface A: -48 VDC power interface at input of Telecom/ICT equipment with voltage range and other electrical specifications defined in ETSI EN 300 132-2 [2]

interface A1: up to 400 VAC rms power interface at input of Telecom/ICT equipment with voltage range and other electrical specifications defined in ETSI EN 300 132-1 [1]

interface A3: up to 400 VDC power interface at input of Telecom/ICT equipment with voltage range, and other electrical specifications defined in ETSI EN 300 132-3 [11]

Local Power Unit (LPU): power supply equipment whose function is to supply a telecommunication equipment situated at the same location

NOTE: It is generally locally connected to the mains and provides DC or AC voltage output to feed telecommunication equipment.

local powering: powering principle of a telecommunications equipment by a (dedicated) power unit implemented in the same location

network termination: functional group on the network side of a user-network interface

NOTE: Source: Recommendation ITU-T I.112 [i.31].

primary circuit: See IEC EN 62368-1 [i.17].

protective device selectivity: coordination of the operating characteristics of two or more protective devices to ensure faulty equipment is safely disconnected with no or limited impact on other parts of the system

PS1, PS2, PS3: See IEC EN 62368-1 [i.17].

Remote Feeding Telecommunication (RFT) circuit: secondary circuit within the equipment, intended to supply or receive DC power via a telecommunication network at voltages equal to or exceeding the limits for TNV circuits, and on which overvoltages from telecommunication networks are possible

Remote Power Receiver (RPR): unit receiving remote DC from RPU through power lines and converting it to input power interface of a TE or a radio unit

NOTE: The RPR may be an external unit with an adapted power interface (e.g. -48 VDC) or an integrated function of a telecommunications equipment.

Remote Power Unit (RPU): unit, powered by the grid or by a DC power system delivering -48 VDC or up to 400 VDC, which supplies remote DC on power lines to distant Telecommunication Equipment (TE) e.g. radio unit or RPR

Remote Powering (RP): power feeding of a telecommunications equipment by a remote power circuit

NOTE: Such a circuit consists of a remote power unit, distribution wiring, and fed receivers.

RFT-C circuit: RFT circuit which is so designed and protected that under normal operating conditions and single fault conditions the currents in the circuit do not exceed defined values

RFT-V circuit: RFT circuit which is so designed and protected that under normal operating conditions and single fault conditions the voltages are limited and the accessible area of contact is limited

secondary circuit: See IEC EN 62368-1 [i.17].

SELV circuit: See IEC EN 62368-1 [i.17].

TN-C: See HD 60364-1 [i.7].

TN-S: See HD 60364-1 [i.7].

TNV circuit: See EN 62368-1 [i.24].

TT: See HD 60364-1 [i.7].

3.2 Symbols

For the purposes of the present document, the following symbols apply:

$I_1, I_2, I_3, I_4, I_5, I_6$	power interface
L-	Power line of negative potential polarity
L+	Power line of positive potential polarity
S	Signal
S/P _{filter}	Filter separating signal S and power P