

SLOVENSKI STANDARD
oSIST prEN IEC 61009-1:2026
01-februar-2026

Odklopniki na preostali (residualni) tok z vgrajeno nadtokovno zaščito za gospodinjsko in podobno rabo (RCBO) - 1. del: Splošna pravila (IEC 61009-1:2024)

Residual current operated circuit-breakers with integral overcurrent protection for household and similar uses (RCBOs) - Part 1: General rules (IEC 61009-1:2024)

Fehlerstrom-/Differenzstrom-Schutzschalter mit eingebautem Überstromschutz (RCBOs) für Hausinstallationen und für ähnliche Anwendungen - Teil 1: Allgemeine Anforderungen (IEC 61009-1:2024)

Document Preview
<https://standards.iteh.ai>

Ta slovenski standard je istoveten z: prEN IEC 61009-1:2026

https://standards.iteh.ai/catalog/standards/sist/9894524_16_5_4575_9212_22_401765561/osist_pr_en_iec_61009_1_2026

ICS:

29.120.50	Varovalke in druga nadtokovna zaščita	Fuses and other overcurrent protection devices
-----------	---------------------------------------	--

oSIST prEN IEC 61009-1:2026 **en**

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

DRAFT
prEN IEC 61009-1

January 2026

ICS 29.120.50

Will supersede EN 61009-1:2012; EN 61009-1:2012/A1:2014; EN 61009-1:2012/A2:2014; EN 61009-1:2012/A11:2015; EN 61009-1:2012/A12:2016; EN 61009-1:2012/A13:2021

English Version

**Residual current operated circuit-breakers with integral overcurrent protection for household and similar uses (RCBOs) -
Part 1: General rules
(IEC 61009-1:2024)**

To be completed
(IEC 61009-1:2024)

Fehlerstrom-/Differenzstrom-Schutzschalter mit eingebautem Überstromschutz (RCBOs) für Hausinstallationen und für ähnliche Anwendungen - Teil 1: Allgemeine Anforderungen
(IEC 61009-1:2024)

This draft European Standard is submitted to CENELEC members for enquiry.
Deadline for CENELEC: 2026-04-24.

The text of this draft consists of the text of IEC 61009-1:2024.

If this draft becomes a European Standard, CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CENELEC in three official versions (English, French, German).
A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

<https://standards.iteh.ai/catalog/standards/sist/e889452d-1fc5-4573-9313-23a4917f55fd/osist-pren-iec-61009-1-2026>

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

prEN IEC 61009-1:2026 (E)**European foreword**

This document (prEN IEC 61009-1:2026) consists of the text of IEC 61009-1:2024, prepared by IEC/SC 23E “Circuit-breakers and similar equipment for household use” of IEC/TC 23 “Electrical accessories”.

This document is currently submitted to the Enquiry.

The following dates are proposed:

- latest date by which the existence of this document (doa) dav + 6 months has to be announced at national level
- latest date by which this document has to be (dop) dav + 12 months implemented at national level by publication of an identical national standard or by endorsement
- latest date by which the national standards (dow) dav + 60 months conflicting with this document have to be withdrawn (to be confirmed or modified when voting)

This document will supersede EN 61009-1:2012 and all of its amendments and corrigenda (if any).

This document is read in conjunction with prEN IEC 61009-1:2026/prAA:2026.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[oSIST prEN IEC 61009-1:2026](#)

<https://standards.iteh.ai/catalog/standards/sist/e889452d-1fc5-4575-9313-23a4917f55fd/osist-pren-iec-61009-1-2026>



INTERNATIONAL STANDARD

**Residual current operated circuit-breakers with integral overcurrent protection
for household and similar uses (RCBOs) –
Part 1: General rules**

Document Preview

[oSIST prEN IEC 61009-1:2026](#)

<https://standards.iteh.ai/catalog/standards/sist/e889452d-1fc5-4575-9313-23a4917f55fd/osit-pr-en-iec-61009-1-2026>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 29.120.50

ISBN 978-2-8327-0011-2

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	10
INTRODUCTION	12
1 Scope	13
2 Normative references	15
3 Terms and definitions	16
4 Classification	16
4.1 According to the supply conditions	16
4.1.1 RCBO operating correctly on the occurrence of residual current	16
4.1.2 RCBO with 2 or 4 current paths operating correctly on the occurrence of residual current within the voltage range of 1,1 U_e and 85 V	17
4.1.3 RCBO according to 4.1.2 fitted with a functional earth (FE) and able to continue to provide protection when supplied from just one phase and FE	17
4.1.4 RCBO with 3 current paths operating correctly on the occurrence of residual current within the voltage range of 1,1 U_e and 0,7 U_e	17
4.1.5 RCBO operating correctly on the occurrence of residual current within the voltage range 1,1 U_e and U_x	17
4.1.6 RCBO according to 4.1.5, however reclosing automatically after restoration of the supply voltage	17
4.2 According to the possibility of adjusting the residual operating current	17
4.3 According to their operation in response to the type of residual current	17
4.4 According to time-delay (in the presence of a residual current)	18
4.5 According to the protection against external influences	18
4.6 According to the method of mounting	18
4.7 According to the method of connection	18
4.8 According to the type of terminals	18
4.9 According to the number of poles and current paths	18
4.10 According to the instantaneous tripping current	19
4.11 According to the I^2t characteristics	19
5 Characteristics of RCBOs	19
5.1 Summary of characteristics	19
5.2 Rated quantities and other characteristics	20
5.2.1 Rated voltages	20
5.2.2 Rated current (I_n)	20
5.2.3 Rated frequency	20
5.2.4 Rated short-circuit capacity (I_{cn})	20
5.2.5 Rated residual operating current ($I_{\Delta n}$)	20
5.2.6 Rated residual non-operating current ($I_{\Delta no}$)	21
5.2.7 Rated residual making and breaking capacity ($I_{\Delta m}$)	21
5.2.8 Void	21
5.2.9 Void	21
5.2.10 Operating characteristics in response to the type of residual current	21
5.2.11 RCBO type S	21
5.3 Standard and preferred values	21
5.3.1 Standard values of rated operational voltage (U_e)	21

5.3.2	Preferred values of rated current (I_n).....	21
5.3.3	Standard values of rated residual operating current ($I_{\Delta n}$).....	21
5.3.4	Standard value of residual non-operating current ($I_{\Delta no}$).....	22
5.3.5	Preferred values of rated frequency	22
5.3.6	Standard values of rated impulse withstand voltage (U_{imp})	22
5.3.7	Standard limit values of break time and non-actuating time for RCBO of type AC and A	22
5.3.8	Void.....	22
5.3.9	Void.....	22
5.3.10	Void.....	22
5.3.11	Minimum value of the rated residual making and breaking capacity ($I_{\Delta m}$)	22
5.3.12	Void.....	22
5.3.13	Void.....	22
5.3.14	Values of rated short-circuit capacity	22
5.3.15	Standard ranges of overcurrent instantaneous tripping	23
6	Marking and other product information.....	23
7	Standard conditions for operation in service and for installation	24
7.1	Standard conditions	24
7.2	Conditions of installation.....	24
7.3	Pollution degree.....	24
8	Requirements for construction and operation.....	24
8.1	Mechanical design	24
8.1.1	General	24
8.1.2	Mechanism	25
8.1.3	Clearances, creepage distances and solid insulation	26
8.1.4	Screws, current-carrying parts and connections	27
8.1.5	Terminals for external conductors	28
8.1.6	Non-interchangeability	30
8.2	Protection against electric shock	30
8.3	Dielectric properties and isolating capability.....	31
8.4	Temperature-rise	31
8.4.1	General	31
8.4.2	Temperature-rise limits	31
8.4.3	Ambient air temperature	31
8.5	Operating characteristics	31
8.5.1	General	31
8.5.2	Operation in response to the type of residual current	31
8.5.3	Operation in presence of a residual current equal to or greater than $I_{\Delta n}$	32
8.5.4	Operation under overcurrent conditions	32
8.6	Mechanical and electrical endurance	33
8.7	Performance at short-circuit currents	33
8.8	Resistance to mechanical shock and impact	33
8.9	Resistance to heat	33
8.10	Resistance to abnormal heat and to fire	34
8.11	Test device	34
8.12	Void	34
8.13	Void	34