



SLOVENSKI STANDARD

oSIST prEN IEC 61406-1:2026

01-februar-2026

Identifikacijska povezava - 1. del: Splošne zahteve

Identification link - Part 1: General requirements

Lien d'identification - Partie 1: Exigences générales

Ta slovenski standard je istoveten z: prEN IEC 61406-1:2025

ICS:

35.240.15 Identifikacijske kartice. Čipne kartice. Biometrija Identification cards. Chip cards. Biometrics
<https://standards.iteh.ai/en/standards/osist-pr-en-iec-61406-1-2026>

oSIST prEN IEC 61406-1:2026

en



65E/1196/CDV

COMMITTEE DRAFT FOR VOTE (CDV)

PROJECT NUMBER:

IEC 61406-1 ED2

DATE OF CIRCULATION:

2025-12-05

CLOSING DATE FOR VOTING:

2026-02-27

SUPERSEDES DOCUMENTS:

65E/1140A/RR

IEC SC 65E : DEVICES AND INTEGRATION IN ENTERPRISE SYSTEMS

SECRETARIAT:

United States of America

SECRETARY:

Mr David Richmond

OF INTEREST TO THE FOLLOWING COMMITTEES:

SC 3D, TC 57, TC 62, TC 121

HORIZONTAL FUNCTION(S):

ASPECTS CONCERNED:

☒ SUBMITTED FOR CENELEC PARALLEL VOTING☐ NOT SUBMITTED FOR CENELEC PARALLEL VOTING**Attention IEC-CENELEC parallel voting**

The attention of IEC National Committees, members of CENELEC, is drawn to the fact that this Committee Draft for Vote (CDV) is submitted for parallel voting.

The CENELEC members are invited to vote through the CENELEC online voting system.

This document is still under study and subject to change. It should not be used for reference purposes.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Recipients of this document are invited to submit, with their comments, notification of any relevant "In Some Countries" clauses to be included should this proposal proceed. Recipients are reminded that the CDV stage is the final stage for submitting ISC clauses. (SEE [AC/22/2007](#) OR [NEW GUIDANCE DOC](#)).

TITLE:

Identification Link - Part 1: General requirements

PROPOSED STABILITY DATE: 2030

NOTE FROM TC/SC OFFICERS:

Copyright © 2025 International Electrotechnical Commission, IEC. All rights reserved. It is permitted to download this electronic file, to make a copy and to print out the content for the sole purpose of preparing National Committee positions. You may not copy or "mirror" the file or printed version of the document, or any part of it, for any other purpose without permission in writing from IEC.

CONTENTS

1			
2			
3	FOREWORD.....		5
4	INTRODUCTION.....		7
5	1 Scope.....		9
6	2 Normative references		9
7	3 Terms, abbreviated terms and definitions		10
8	4 Identification Link string.....		11
9	4.1 ILS-1: Global uniqueness.....		11
10	4.1.1 Requirement.....		11
11	4.1.2 Rationale and supplemental guidance.....		11
12	4.2 ILS-2: Link to additional information.....		12
13	4.2.1 Requirement.....		12
14	4.2.2 Rationale and supplemental guidance.....		12
15	4.3 ILS-3: No reuse.....		12
16	4.3.1 Requirement.....		12
17	4.3.2 Rationale and supplemental guidance.....		13
18	4.4 ILS-4: No altering.....		13
19	4.4.1 Requirement.....		13
20	4.4.2 Rationale and supplemental guidance.....		13
21	4.5 ILS-5: String length.....		13
22	4.5.1 Requirement.....		13
23	4.5.2 Rationale and supplemental guidance.....		13
24	4.6 ILS-6: URL syntax.....		13
25	4.6.1 Requirement.....		13
26	4.6.2 Rationale and supplemental guidance.....		13
27	4.7 ILS-7: Allowed characters.....		14
28	4.7.1 Requirement.....		14
29	4.7.2 Rationale and supplemental guidance.....		14
30	4.8 ILS-8: Uppercase and lowercase characters		14
31	4.8.1 Requirement.....		14
32	4.8.2 Rationale and supplemental guidance.....		14
33	4.9 ILS-9: No character-combinations with special functions		15
34	4.9.1 Requirement.....		15
35	4.9.2 Rationale and supplemental guidance.....		15
36	4.10 ILS-10: Query string parameters starting with dot “.”		15
37	4.10.1 Requirement.....		15
38	4.10.2 Rationale and supplemental guidance.....		15
39	5 Identification Link with 2D symbol.....		16
40	5.1 General.....		16
41	5.2 2D-1: When marking with 2D symbol.....		16
42	5.2.1 Requirement.....		16
43	5.2.2 Rationale and supplemental guidance.....		16
44	5.3 2D-2: 2D symbol content.....		16
45	5.3.1 Requirement.....		16
46	5.3.2 Rationale and supplemental guidance.....		17
47	5.4 2D-3: Symbolology		17

IEC CDV 61406-1 © IEC 2025

48	5.4.1	Requirement.....	17
49	5.4.2	Rationale and supplemental guidance.....	17
50	5.5	2D-4: Module size.....	17
51	5.5.1	Requirement.....	17
52	5.5.2	Rationale and supplemental guidance.....	18
53	5.6	2D-5: Quiet zone.....	18
54	5.6.1	Requirement.....	18
55	5.6.2	Rationale and supplemental guidance.....	18
56	5.7	2D-6: Error correction	18
57	5.7.1	Requirement.....	18
58	5.7.2	Rationale and supplemental guidance.....	18
59	5.8	2D-7: Label print quality	19
60	5.8.1	Requirement.....	19
61	5.8.2	Rationale and supplemental guidance.....	19
62	5.8.3	Requirement.....	19
63	5.8.4	Rationale and supplemental guidance.....	20
64	5.9	2D-9: Durability of the 2D marking	20
65	5.9.1	Requirement.....	20
66	5.9.2	Rationale and supplemental guidance.....	20
67	5.10	2D-10: Marking with a frame	21
68	5.10.1	Requirement.....	21
69	5.10.2	Rationale and supplemental guidance.....	21
70	5.11	2D-11: Frame layout	21
71	5.11.1	Requirement.....	21
72	5.11.2	Rationale and supplemental guidance.....	21
73	5.12	2D-12: Orientation of the frame for QR-Codes and rMQR-Codes.....	23
74	5.12.1	Requirement.....	23
75	5.12.2	Rationale and supplemental guidance.....	23
76	5.13	2D-13: Positive image.....	23
77	5.13.1	Requirement.....	23
78	5.13.2	Rationale and supplemental guidance.....	23
79	5.14	2D-14: Location of the 2D symbol	24
80	5.14.1	Requirement.....	24
81	5.14.2	Rationale and supplemental guidance.....	24
82	6	Near Field Communication for the Identification Link	25
83	6.1	General.....	25
84	6.2	NFC-1: When marking with NFC	25
85	6.2.1	Requirement.....	25
86	6.2.2	Rationale and supplemental guidance.....	25
87	6.3	NFC-2: Air interface standards.....	25
88	6.3.1	Requirement.....	25
89	6.3.2	Rationale and supplemental guidance.....	25
90	6.4	NFC-3: Data format and content	26
91	6.4.1	Requirement.....	26
92	6.4.2	Rationale and supplemental guidance.....	26
93	6.5	NFC-4: Data consistency	26
94	6.5.1	Requirement.....	26
95	6.5.2	Rationale and supplemental guidance.....	26
96	6.6	NFC-5: Protection classes and approvals.....	26

IEC CDV 61406-1 © IEC 2025

97	6.6.1	Requirement.....	26
98	6.6.2	Rationale and supplemental guidance.....	27
99	6.7	NFC-6: Durability	27
100	6.7.1	Requirement.....	27
101	6.7.2	Rationale and supplemental guidance.....	27
102	6.8	NFC-7: Write protection	27
103	6.8.1	Requirement.....	27
104	6.8.2	Rationale and supplemental guidance.....	27
105	6.9	NFC-8: Tag location for use in installed state.....	27
106	6.9.1	Requirement.....	27
107	6.9.2	Rationale and supplemental guidance.....	27
108	6.10	NFC-9: Tag position relative to existing marking for identification	28
109	6.10.1	Requirement.....	28
110	6.10.2	Rationale and supplemental guidance.....	28
111	6.11	NFC-10: Tag position relative to neighbouring tags	28
112	6.11.1	Requirement.....	28
113	6.11.2	Rationale and supplemental guidance.....	28
114	6.12	NFC-11: Generic RFID Emblem in frame.....	28
115	6.12.1	Requirement.....	28
116	6.12.2	Rationale and supplemental guidance.....	29
117	6.13	NFC-12: RFID Emblem visibility	29
118	6.13.1	Requirement.....	29
119	6.13.2	Rationale and supplemental guidance.....	29
120	6.14	NFC-13: RFID Emblem position relative to tag	29
121	6.14.1	Requirement.....	29
122	6.14.2	Rationale and supplemental guidance.....	30
123	Annex A (normative)	Overview of characters permitted for the IL string	31
124	Annex B (informative)	Examples of Identification Link strings.....	34
125	Annex C (informative)	2D symbol examples and layout considerations	40
126	C.1	Choice of symbology.....	40
127	C.2	Square and rectangular symbols	41
128	C.3	Symbols not centered in the frame	41
129	C.4	Layout example when space is not sufficient.....	42
130	Annex D (informative)	2D symbols on curved surfaces.....	43
131	Annex E (informative)	Duplicates of the Identification Link	44
132	Annex F (informative)	Search Engine friendliness	45
133	Annex G (informative)	Cybersecurity aspects.....	46
134	Annex H (informative)	IL string as IRDI	47
135	ANNEX I (informative)	Print quality verification strategies	48

136
137

IEC CDV 61406-1 © IEC 2025

138	Figure 1 – Example of an IL linking a physical object to information associated with it	13
139	Figure 2 – IEC 60417-6452 frame around the 2D symbol	23
140	Figure 3 – IEC 60417-6452-1 frame around the 2D symbol	23
141	Figure 4 – Comparison of a 2D symbol as negative and normal positive image	24
142	Figure 5 – Representation of an IL on a dark background	25
143	Figure C.1 – IL size may vary depending on the used symbology left: data matrix	
144	(ISO/IEC 16022), right: QR code (ISO/IEC 18004)	41
145	Figure C.2 – IL with square and rectangular Data Matrix	42
146	Figure C.3 – IL with 2D symbols not centred in the frame.....	42
147	Figure C.4 – IL with 2D symbols quiet zone below 4 modules on 2 sides	43
148		
149	Table 1 - Minimum module size as a function of available space.....	18
150	Table 2 - Tolerances, in modules, for placing a 2D symbol within the frame	23
151	Table A.1 – List of ASCII Code Characters permitted as this standard to create an IL.....	33
152	Table B.1 – Structure of example a).....	35
153	Table B.2 – Structure of example b).....	35
154	Table B.3 – Structure of example c)	35
155	Table B.4 – Structure of example d).....	35
156	Table B.5 – Structure of example e).....	36
157	Table B.6 – Structure of example f).....	37
158	Table B.7 – Structure of example g).....	37
159	Table B.8 – Structure of example i).....	37
160	Table B.9 – Structure of example j).....	38
161	Table B.10 – Structure of example k)	38
162	Table B.11 – Structure of example l)	38
163	Table B.12 – Structure of example m).....	39
164	Table B.13 – Structure of example n).....	39
165	Table B.14 – Structure of example o).....	39
166	Table D.1 – Recommended maximum radii when using 2D Codes with error correction	
167	level “Q”.....	44

168

169