SLOVENSKI STANDARD
oSIST prEN IEC 61851-1:2025

01-oktober-2025

Sistemi za prenos prevodne moči in energije za električna vozila - 1. del: Splošne zahteve sistema in posebne zahteve za polnilno postajo za električna vozila v načinu 3

Conductive power and energy transfer systems for electric vehicles - Part 1: General system and specific mode 3 EV charging station requirements

Konduktive Ladesysteme für Elektrofahrzeuge - Teil 1: Allgemeine Anforderungen

Système de transfert de puissance/énergie conductive pour véhicules électriques - Partie 1: Exigences générales et exigences pour station de charge en mode 3

Ta slovenski standard je istoveten z: **prEN IEC 61851-1:2025**

ICS:

43.120	Električna cestna vozila	Electric road vehicles

oSIST prEN IEC 61851-1:2025 **en**

69/1069/CDV

COMMITTEE DRAFT FOR VOTE (CDV)

PROJECT NUMBER:	
IEC 61851-1 ED4	
DATE OF CIRCULATION:	CLOSING DATE FOR VOTING:
2025-08-29	**2025-11-21**
SUPERSEDES DOCUMENTS:	
69/971/CD, 69/1067/CC	

IEC TC 69 : ELECTRICAL POWER/ENERGY TRANSFER SYSTEMS FOR ELECTRICALLY PROPELLED ROAD VEHICLES AND INDUSTRIAL TRUCKS	
SECRETARIAT: Belgium	SECRETARY: Mr Peter Van den Bossche
OF INTEREST TO THE FOLLOWING COMMITTEES: TC 8,TC 23,SC 23E,SC 23H,TC 64,TC 121	HORIZONTAL FUNCTION(S):
ASPECTS CONCERNED: Safety	
☒ SUBMITTED FOR CENELEC PARALLEL VOTING	☐ NOT SUBMITTED FOR CENELEC PARALLEL VOTING

Attention IEC-CENELEC parallel voting

The attention of IEC National Committees, members of CENELEC, is drawn to the fact that this Committee Draft for Vote (CDV) is submitted for parallel voting.

The CENELEC members are invited to vote through the CENELEC online voting system.

This document is still under study and subject to change. It should not be used for reference purposes.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Recipients of this document are invited to submit, with their comments, notification of any relevant "In Some Countries" clauses to be included should this proposal proceed. Recipients are reminded that the CDV stage is the final stage for submitting ISC clauses. (SEE AC/22/2007 OR NEW GUIDANCE DOC).

TITLE:

Conductive power and energy transfer systems for electric vehicles - Part 1: General system and specific Mode 3 EV charging station requirements

PROPOSED STABILITY DATE: 2028

NOTE FROM TC/SC OFFICERS:

CONTENTS

CONTENTS 1
FOREWORD 8
INTRODUCTION 10
1 Scope 12
2 Normative references 13
3 Terms and definitions 17
3.1 Electric supply equipment 17
3.2 Earthing and protection against electric shock 19
3.3 Modes and functions 22
3.4 Cords, cables and connection means 25
3.5 Service and usage 29
3.6 General terms 30
4 System requirements 35
4.1 General requirements 35
4.2 Charging Modes 35
4.2.1 Mode 1 35
4.2.2 Mode 2 36
4.2.3 Mode 3 36
4.2.4 Mode 4 36
4.3 System functional requirements in Mode 2, 3 and 4 36
4.3.1 General 36
4.3.2 Continuous continuity checking of the protective conductor 37
4.3.3 Verification that the EV is properly connected to the EV supply equipment 37
4.3.4 Energization of the power supply to the EV 37
4.3.5 De-energization of the power supply to the EV 38
4.3.6 Specification of maximum allowable current 38
4.3.7 Intentional and unintentional unmating of the vehicle connector and/or the EV plug 38
4.3.8 Optional functions 38
4.4 Selection of accessories, cables and adaptors 41
4.4.1 General 41
4.4.2 Standard accessories 41
4.4.3 EV plugs, EV socket-outlets, vehicle connectors 41
4.4.4 Cable assembly 41
4.4.5 Adaptors 42
5 Classification of Mode 3 EV charging station 43
5.1 According to the service conditions 43
5.2 According to the mounting method 43
5.3 According to the mechanical resistance 43
5.4 According to the connection case 43
5.5 According to the power distribution system 43
5.6 According to the protection against electric shock 44
5.7 According to the communication function with the vehicle 44
5.8 According to the ability of Reverse Power Transfer 44
6 Service conditions for Mode 3 EV charging station 44

7 Void 44
8 Requirements for Mode 3 EV charging station 44
8.1 Strength of materials and parts 44
8.1.1 General 44
8.1.2 Protection against corrosion 45
8.1.3 Damp heat resistance 45
8.1.4 Properties of insulating materials 45
8.1.5 Resistance to UV radiation 46
8.1.6 Mechanical strength 47
8.1.7 Lifting provisions 48
8.2 Clearances and creepage distances 48
8.2.1 General 48
8.2.2 Clearances and creepages distances for inner layers of printed wiring boards 49
8.3 Protection against access to hazardous parts, against solid foreign objects and water (IP code) 50
8.3.1 Degrees of protection provided by Mode 3 EV charging station enclosures 50
8.3.2 Degrees of protection provided by basic interface accessories 50
8.4 Temperature rise 50
8.5 Operation at low temperatures 51
8.6 Resistance to abnormal operating and fault conditions 51
8.7 Incorporation of components 52
8.7.1 General 52
8.7.2 Surge protective devices and surge protective components 52
8.7.3 Conductive electrical interface requirements 54
8.7.4 Cable assembly requirements 55
8.7.5 Emergency switching or disconnect equipment (optional) 56
8.7.6 Switching devices intended to supply the connecting points 57
8.8 Internal electrical circuits and connections 58
8.9 Protection against electric shock 58
8.9.1 General requirements for protection against electric shock 58
8.9.2 Handling of welded contacts 59
8.9.3 Residual current protective devices protecting connecting points 60
8.9.4 Automatic or remote reclosing of protective devices 61
8.9.5 Protective conductor 64
8.9.6 Insulation resistance 64
8.9.7 Touch current 64
8.9.8 Protections against hazards caused by stored energy 65
8.9.9 Dielectric withstand voltage 65
8.9.10 Safety requirements for auxiliary circuits 65
8.10 Protection against overcurrent 66
8.10.1 General 66
8.10.2 Overload protection of the cable assembly 67
8.10.3 Short-circuit protection of the cable assembly 67
8.11 Functional requirements of Mode 3 EV charging station 67
8.12 Requirements for Mode 3 EV charging station capable of reverse power transfer 68
9 Marking and instructions for Mode 3 EV charging station 68
9.1 Installation manual 68

9.2 User manual ... 69
9.3 Marking ... 70
9.4 Status indication ... 70
10 Design verifications for Mode 3 EV charging station ... 72
10.1 General ... 72
10.2 Damp heat test ... 72
10.3 Minimum temperature functional test ... 73
10.4 Abnormal operating and simulated fault condition tests ... 73
10.4.1 General ... 73
10.4.2 Pass criteria ... 73
10.4.3 Simulated fault conditions tests ... 74
10.4.4 Abnormal operating conditions tests ... 74
10.5 Test of the anchorage of the side B cable assembly ... 75
10.6 Tests of coordination with short-circuit protective devices (SCPDs) ... 78
10.7 Simulation of switching device welded contacts ... 79
10.7.1 Test conditions ... 79
10.7.2 Pass Criteria ... 79
10.8 Tests for automatic or remote reclosing of protective devices ... 80
10.9 Protective conductor overcurrent test ... 80
10.10 Insulation resistance test ... 81
10.11 Touch current test ... 82
10.12 Stored energy test ... 82
10.13 AC withstand voltage test ... 82
10.14 Durability test for marking ... 84
11 Operating and servicing conditions for Mode 3 EV charging station ... 84
12 Routine verifications for Mode 3 EV charging station ... 84
Annex A (normative) Control pilot function through a control pilot circuit using a PWM signal and a control pilot conductor ... 85
A.1 General ... 85
A.2 Control pilot circuit ... 85
A.2.1 General ... 85
A.2.2 Typical control pilot circuit ... 86
A.2.3 Additional components and high-frequency signals ... 86
A.3 Requirements for parameters and system behaviour ... 88
A.3.1 Control pilot circuit parameters and values ... 88
A.3.2 System states ... 90
A.3.3 State transitions and sequences ... 95
A.3.4 Generation and interpretation of PWM duty cycle ... 115
A.3.5 Switching between three-phase and single-phase supply ... 116
A.4 Test procedures ... 116
A.4.1 General ... 116
A.4.2 Constructional requirements of the EV simulator ... 116
A.4.3 Test procedure ... 117
A.4.4 Measurement criteria ... 118
A.4.5 Oscillator frequency and generator voltage, duty cycle and pulse wave shape test ... 119
A.4.6 CP state tolerances test ... 122
A.4.7 State detection test ... 125
A.4.8 Sequences test ... 127

A.4.9 Test of interruption of the protective conductor 132
A.4.10 Test of short-circuit values of the voltage 134
A.4.11 Test of interruption of the control pilot conductor 135
A.4.12 Example of a test simulator of the vehicle 135
A.5 Information for implementation 139
A.5.1 Retaining a valid authorization until reaching CP state B 139
A.5.2 Load control using transitions between state x1 and x2 140
A.5.3 Information on difficulties encountered with some legacy EVs for wake-up after a long period of inactivity (informative) 140
A.5.4 Information on legacy EVs using simplified control pilot 140
A.5.5 Ventilation during supply of energy 141
Annex B (normative) Proximity detection and cable current coding circuits for the basic interface 142
B.1 Circuit diagram for vehicle couplers using a connection switch for proximity detection without current coding 142
B.2 Circuit diagram for vehicle couplers using a proximity contact for simultaneous proximity detection and current coding 143
B.3 Circuit diagram for vehicle couplers using a connection switch and current coding 145
Annex C (void) 147
Annex D (normative) Control pilot function that provides LIN communication using the control pilot circuit 148
D.1 Overview 148
D.1.1 General 148
D.1.2 Terms and abbreviations 148
D.1.3 Abbreviated terms 150
D.2 Control pilot circuit 151
D.2.1 General 151
D.2.2 Parameters 151
D.2.3 Generation and detection of CP voltage by the EV supply equipment 152
D.2.4 Detection of the control pilot voltage by the EV 152
D.2.5 LIN transceiver 153
D.3 Requirements for parameters and system behavior 153
D.3.1 General 153
D.3.2 Control pilot circuit states and transitions 153
D.4 System requirements 156
D.4.1 General 156
D.4.2 Control of LIN signals 156
D.4.3 Control of the switch S2 and the vehicle load current 157
D.4.4 Control of the switching device in the EV supply equipment 158
D.4.5 Control of latching and unlatching of IEC 62196-2 type 2 socket-outlets and vehicle inlets 159
D.5 Typical coupling session 160
D.6 LIN Communication 161
D.6.1 General 161
D.6.2 Schedules 161
D.6.3 Frames 172
D.6.4 Signals 175
D.7 Requirements for EV supply equipment and EVs that implement the control pilot functions defined in this Annex and in Annex A 184
D.7.1 General 184