
Sistemi za prenos prevodne moči in energije za električna vozila - 23. del: Postaja za kabelsko napajanje električnega vozila z enosmernim tokom

Conductive power and energy transfer systems for electric vehicles - Part 23: DC electric vehicle supply equipment

Konduktive Ladesysteme für Elektrofahrzeuge - Teil 23:
Gleichstromversorgungseinrichtungen für Elektrofahrzeuge

Système de charge par conduction pour véhicules électriques - Partie 23: Système d'alimentation en courant continu pour véhicules électriques

Ta slovenski standard je istoveten z: **prEN IEC 61851-23:2026**

ICS:

43.120	Električna cestna vozila	Electric road vehicles
--------	--------------------------	------------------------

oSIST prEN IEC 61851-23:2026	en
-------------------------------------	-----------

Sample Document

get full document from standards.iteh.ai



69/1159/CDV

COMMITTEE DRAFT FOR VOTE (CDV)

PROJECT NUMBER: IEC 61851-23 ED3	
DATE OF CIRCULATION: 2026-09-18	CLOSING DATE FOR VOTING: 2026-12-11
SUPERSEDES DOCUMENTS: 69/1076/CD, 69/1155/CC	

IEC TC 69 : ELECTRICAL POWER/ENERGY TRANSFER SYSTEMS FOR ELECTRICALLY PROPELLED ROAD VEHICLES AND INDUSTRIAL TRUCKS	
SECRETARIAT: Belgium	SECRETARY: Mr Peter Van den Bossche
OF INTEREST TO THE FOLLOWING COMMITTEES: SC 23E, SC 23H, TC 64	HORIZONTAL FUNCTION(S):
ASPECTS CONCERNED: Safety	
☒ SUBMITTED FOR CENELEC PARALLEL VOTING Attention IEC-CENELEC parallel voting The attention of IEC National Committees, members of CENELEC, is drawn to the fact that this Committee Draft for Vote (CDV) is submitted for parallel voting. The CENELEC members are invited to vote through the CENELEC online voting system.	☐ NOT SUBMITTED FOR CENELEC PARALLEL VOTING

This document is still under study and subject to change. It should not be used for reference purposes.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Recipients of this document are invited to submit, with their comments, notification of any relevant "In Some Countries" clauses to be included should this proposal proceed. Recipients are reminded that the CDV stage is the final stage for submitting ISC clauses. (SEE [AC/22/2007](#) OR [NEW GUIDANCE DOC](#)).

TITLE:

Conductive power and energy transfer systems for electric vehicles - Part 23: DC electric vehicle supply equipment

PROPOSED STABILITY DATE: 2028

NOTE FROM TC/SC OFFICERS:

Copyright © 2026 International Electrotechnical Commission, IEC. All rights reserved. It is permitted to download this electronic file, to make a copy and to print out the content for the sole purpose of preparing National Committee positions. You may not copy or "mirror" the file or printed version of the document, or any part of it, for any other purpose without permission in writing from IEC.

CONTENTS

1			
2	CONTENTS		1
3	FOREWORD		17
4	1 Scope		19
5	2 Normative references		20
6	3 Terms and definitions		24
7	3.1 Electric supply equipment		24
8	3.2 Insulation		26
9	3.3 Modes and functions		33
10	3.4 Vehicle		38
11	3.5 Cords, cables and connection means		39
12	3.6 Service and usage		41
13	3.7 General terms		43
14	4 General requirements		53
15	5 Classification		54
16	5.1 Characteristics of side A		54
17	5.2 Normal environmental conditions		54
18	5.3 Special environmental conditions		54
19	5.4 Mechanical resistance		54
20	5.5 Mounting method		55
21	5.6 Protection against electric shock		55
22	5.7 Charging modes		55
23	5.8 Separation type		55
24	5.9 Control system		55
25	5.10 System		55
26	5.11 Thermal management system		56
27	5.12 Power distribution system		56
28	5.13 Ability of RPT		56
29	5.14 Voltage operating range		56
30	6 Charging modes and functions		56
31	6.1 General		56
32	6.2 Charging Mode 4		56
33	6.3 Functions provided in Mode 4		57
34	6.3.1 Mandatory functions in Mode 4		57
35	6.3.2 Optional functions for Mode 4		76
36	7 Communications		77
37	7.1 Basic communication interface		77
38	7.2 Digital communication between the EVSE and the EV		77
39	8 Protection against electric shock		78
40	8.1 General provisions		78
41	8.1.1 General		78
42	8.1.2 Intended use and reasonably foreseeable misuse		78
43	8.1.3 Limitation of touch current or touch voltage		78
44	8.1.4 Threshold of perception and startle reaction		79
45	8.2 Basic protection		82
46	8.2.1 General		82
47	8.2.2 Protection by means of basic insulation of live parts		82

IEC CDV 61851-23 © IEC 2026

48	8.2.3	Protection by means of enclosures or barriers	82
49	8.2.4	Protection by means of limitation of voltage	82
50	8.2.5	Protection by means of limitation of steady-state touch current.....	84
51	8.3	Fault protection	84
52	8.3.1	General	84
53	8.3.2	Protective-equipotential-bonding.....	84
54	8.3.3	Effective protective conductor continuity between the enclosure and the external protective circuit.....	84
56	8.3.4	Automatic disconnection of supply	85
57	8.3.5	Supplementary insulation.....	85
58	8.3.6	Electrically protective screening.....	85
59	8.3.7	Fault protection in grid forming mode	85
60	8.4	Enhanced protective provision	85
61	8.4.1	General	85
62	8.4.2	Double or reinforced insulation	85
63	8.4.3	Protective separation between circuits.....	85
64	8.5	Requirements for separated EVSE	86
65	8.5.1	General	86
66	8.5.2	Equipotential bonding on side B.....	88
67	8.5.3	Impedance to protective conductor on side B.....	88
68	8.5.4	Degrees of protection against access to hazardous-live-parts.....	89
69	8.5.5	Insulation barriers	90
70	8.5.6	Stored energy	92
71	8.5.7	Disconnection from vehicle	92
72	8.5.8	Protective (earthing) conductor from the supply network.....	92
73	8.5.9	Residual current protective devices	93
74	8.5.10	Safety requirements for auxiliary circuits between the EVSE and the EV	94
75	8.5.11	Protective conductor dimension cross-sectional area.....	94
76	9	Conductive electrical interface requirements.....	94
77	9.1	General.....	94
78	9.7	Wiring of the neutral conductor	94
79	9.8	Avoidance of breaking under load	94
80	10	Cable assembly requirements.....	95
81	10.1	General.....	95
82	10.2	Dielectric withstand characteristics	95
83	10.3	Cable dimensions	95
84	10.4	Strain relief	95
85	10.4.1	General	95
86	10.4.2	Strain relief of the side B cable assembly of the EVSE	95
87	10.4.3	Test of the anchorage of the side B cable assembly	96
88	10.5	Cable management and storage means for cables assemblies.....	98
89	10.6	Cable breakaway	98
90	10.7	Surface temperature of the side B cable assembly.....	99
91	11	EVSE constructional requirements and tests	99
92	11.1	General.....	99
93	11.2	Characteristics of mechanical switching devices	99
94	11.2.1	General	99
95	11.2.2	Circuit-breaker.....	99
96	11.3	Clearances and creepage distances.....	100

IEC CDV 61851-23 © IEC 2026

97	11.4	IP degrees	100
98	11.4.1	Degrees of protection against solid foreign objects and water for the	
99		enclosures	100
100	11.4.2	Degrees of protection against solid foreign objects and water for vehicle	
101		connectors	101
102	11.5	Insulation resistance	101
103	11.6	Touch current	101
104	11.6.1	Touch current limit	101
105	11.6.2	Test	102
106	11.6.3	Protection measures for the test touch current more than 3,5 mA	102
107	11.7	Dielectric withstand voltage	103
108	11.7.1	AC or DC withstand voltage	103
109	11.7.2	Impulse dielectric withstand (1,2 µs/50 µs)	104
110	11.7.3	Suppression of transient overvoltage at side A (insulation coordination)	104
111	11.7.4	Protection against transient overvoltages of atmospheric origin or due	
112		to switching	104
113	11.8	Temperature rise	108
114	11.9	Damp heat functional test	108
115	11.10	Minimum temperature functional test	108
116	11.11	Side A current	108
117	11.12	Power supply cords	108
118	11.12.1	General	108
119	11.12.2	Cross-sectional area	109
120	11.12.3	Cord anchorages and strain relief for non-detachable power supply	
121		cords	110
122	11.13	Stress relief test	111
123	11.14	Abnormal operation and simulated fault condition tests	112
124	11.14.1	General	112
125	11.14.2	Pass criteria	112
126	11.14.3	Breakdown of components test	113
127	11.14.4	Loss of AC supply phase test	113
128	11.14.5	Inoperative blower/fan motor test	113
129	11.14.6	Clogged filter test	114
130	11.15	Protection against electrically caused fire	114
131	11.15.1	General	114
132	11.15.2	Fire enclosure	114
133	11.16	Protection against chemical hazards	114
134	11.16.1	Type of coolant	114
135	11.16.2	Flammability	115
136	11.16.3	Material compatibility	115
137	11.17	Enclosures	115
138	11.17.1	General	115
139	11.17.2	Strength of materials and parts	115
140	11.17.3	Enclosure integrity tests	116
141	11.18	Components bridging insulation	116
142	11.18.1	General	116
143	11.18.2	Capacitors	116
144	11.19	Isolating transformers	116
145	11.20	Protection against corrosion	117
146	11.20.1	General	117

IEC CDV 61851-23 © IEC 2026

147	11.20.2	Protection against corrosion test.....	118
148	12	Overload and short-circuit protection	119
149	12.1	General.....	119
150	12.2	Short-circuit protection of the DC connection during energy transfer	119
151	12.3	Protection against thermal effect due to short circuit during grid forming	
152		mode	121
153	13	Emergency switching (optional)	121
154	14	Marking and instructions.....	121
155	14.1	Installation manual of EV charging stations	121
156	14.2	User manual for EVSE	123
157	14.3	Marking of EVSE.....	123
158	14.4	Durability test for marking	124
159	15	Specific requirements for EVSE	124
160	15.1	Specific requirements for separated EVSE.....	124
161	15.1.1	Operating ranges for voltage, current, and power at side B.....	124
162	15.1.2	Voltage and current tolerance at side B	125
163	15.1.3	Control delay of present current at side B in CCM.....	127
164	15.1.4	Descending rate of present current at side B	131
165	15.1.5	Periodic and random deviation (current ripple at side B during CCM).....	131
166	15.1.6	Periodic and random deviation (voltage ripple at side B during CVM)	132
167	15.1.7	Load dump	133
168	15.1.8	Side B inductance.....	134
169	15.1.9	Limitation of dynamic behaviour during normal operation.....	136
170	15.2	Specific requirement for energy transfer with a thermal management system	
171		or thermal sensing only	137
172	15.2.1	General	137
173	15.2.2	Temperature limits and self-diagnostics	137
174	15.2.3	Temperature monitoring.....	138
175	15.2.4	Tests for thermal management system performance of the EVSE	139
176	15.3	Specific requirements for temperature-controlled energy transfer with rated	
177		boost current.....	149
178	16	Test methods.....	150
179	16.1	Technical data	150
180	16.2	General test conditions	150
181	16.2.1	Ambient test conditions.....	150
182	16.2.2	Measuring instruments.....	151
183	16.2.3	Test setups.....	151
184	16.2.4	Test load	156
185	16.2.5	Operating points for tests	157
186	Annex A (normative)	EVSE of system A.....	159
187	A.1	General.....	159
188	A.2	Circuit diagram	159
189	A.3	Specific safety requirements	162
190	A.3.1	Fault protection in side B	162
191	A.3.2	De-energization of the power supply to the EV	166
192	A.3.3	Voltage measurement of side B live parts (DC+/DC-) for vehicle	
193		connector unlatch	166
194	A.3.4	Overcurrent protection of side B	167
195	A.3.5	Short-circuit protection of side B	167

IEC CDV 61851-23 © IEC 2026

196	A.3.6	Latch monitoring for the vehicle connector	168
197	A.3.7	Protection of the EV disconnection device	169
198	A.3.8	Fault conditions and criteria for transfer to error and emergency shutdown	169
200	A.3.9	Inrush current limitation by the EVSE	174
201	A.3.10	Regulation of the present current at side B in CCM	174
202	A.3.11	Periodic and random deviation (current ripple at side B during CCM)	175
203	A.3.12	Overvoltage protection including load dump	176
204	A.3.13	Power supply to the EV for the actuation of EV disconnection device	177
205	A.3.14	Impedance of the side B circuit	178
206	A.3.15	Assistance of welding detection	178
207	A.3.16	Specific requirements for temperature-controlled energy transfer	178
208	A.4	FPT process and communication between the EVSE and the EV for energy transfer control	179
210	A.4.1	Forward power transfer states	179
211	A.4.2	Communication measures	181
212	A.4.3	Forward power transfer control process	181
213	A.4.4	Measuring current and voltage at side B	188
214	A.5	Response to an EV command on charge current	190
215	A.6	Bidirectional power transfer (optional)	192
216	A.6.1	General	192
217	A.6.2	Circuit diagram	192
218	A.6.3	Functional requirements	194
219	A.6.4	Bidirectional power transfer control process	196
220	A.7	Optional functions	201
221	A.7.1	General	201
222	A.7.2	Compatibility check	201
223	A.7.3	Dynamic control	201
224	A.7.4	High-current control	202
225	A.7.5	High-voltage control	202
226	A.8	Compliance test for user-initiated shutdown	202
227	A.9	Specific requirement for energy transfer with thermal management system	202
228	Annex B (normative)	EVSE of upgraded system B	204
229	B.1	General	204
230	B.2	Circuit diagrams	204
231	B.2.1	Circuit diagram	204
232	B.2.2	Requirements of IMD and discharge circuit	206
233	B.2.3	Requirements of auxiliary power supply circuit	206
234	B.3	Parameters of control pilot circuit	206
235	B.4	Process of FPT	208
236	B.4.1	General	208
237	B.4.2	Normal startup	208
238	B.4.3	Normal shutdown and error shutdown	210
239	B.4.4	Emergency shutdown	212
240	B.4.5	Backward compatibility (optional)	216
241	B.5	Energy transfer requirements	219
242	B.5.1	Side B regulation	219
243	B.5.2	Measuring current and voltage	219
244	B.5.3	Vehicle coupler mating confirmation	221

IEC CDV 61851-23 © IEC 2026

245	B.5.4	Insulation resistance check before energy transfer	221
246	B.5.5	Normal shutdown	222
247	B.5.6	Error handling	223
248	B.5.7	Emergency handling	225
249	B.6	Specific requirements	226
250	B.6.1	Electronic lock and latch monitoring for vehicle connector	226
251	B.6.2	Manual emergency unlocking mechanism	227
252	B.6.3	Insulation monitoring function at power supply mode	227
253	B.6.4	Welding detection	228
254	B.6.5	Load dump	228
255	B.6.6	Overcurrent protection of side B	229
256	B.6.7	Short-circuit protection of side B	229
257	B.6.8	Overvoltage fault	230
258	B.6.9	Power failure protection	230
259	B.6.10	Minimum cross-sectional area of the protective conductor	231
260	B.6.11	Side B current regulation in CCM	231
261	B.6.12	Side B voltage regulation in CVM	233
262	B.6.13	Periodic and random deviation (voltage ripple at side B in CVM)	235
263	B.6.14	Energy transfer control mode	235
264	B.7	Additional functions	237
265	B.7.1	Pause function	237
266	B.7.2	Automatic restore communication	238
267	B.7.3	Restart and sleep mode	238
268	Annex C (normative)	EVSE of system C	239
269	C.1	General	239
270	C.2	Circuit diagrams	239
271	C.2.1	General	239
272	C.2.2	Circuit diagram for configuration EE	239
273	C.2.3	Circuit diagram for configuration FF	242
274	C.2.4	Control pilot function requirements	245
275	C.2.5	Disabled side B	245
276	C.3	Process of energy transfer	246
277	C.3.1	General	246
278	C.3.2	Normal startup	248
279	C.3.3	Normal shutdown or pause after energy transfer	258
280	C.3.4	Error and emergency handling	263
281	C.3.5	Pause by EVSE using ISO 15118	276
282	C.3.6	Renegotiation initiated by EV or EVSE	291
283	C.3.7	Additional parameters in HLC	295
284	C.4	Safety related functions	296
285	C.4.1	Safety measures for side B	296
286	C.4.2	Vehicle coupler latching function	300
287	C.4.3	Loss of electrical continuity of the control pilot conductor	300
288	C.4.4	Loss of electrical continuity of the proximity detection conductor	300
289	C.4.5	Minimum cross-sectional area of the protective conductor	300
290	C.4.6	Loss of electrical continuity of the protective conductor	300
291	C.5	Additional functions	300
292	C.5.1	Pre-charge	300
293	C.5.2	Sleep mode and communication session restart methods	303

IEC CDV 61851-23 © IEC 2026

294	C.5.3	Configuration EE vehicle connector latch position switch (S_{S3})	
295		activation	309
296	C.5.4	Configuration EE vehicle connector latch position switch (S_{S3})	
297		verification	309
298	C.5.5	Handling of operating ranges	310
299	C.5.6	Compatibility check	319
300	C.5.7	Considerations for CCM, CVM and CPM (informative)	331
301	C.6	Specific requirements	332
302	C.6.1	Requirements for load dump	332
303	C.6.2	Side B current regulation	332
304	C.6.3	Measuring current and voltage at side B	333
305	C.6.4	Overcurrent protection of side B	333
306	C.7	General test conditions	333
307	C.7.1	Operating points – Definitions	333
308	C.7.2	Standard test setup	335
309	C.7.3	Definition of measured values at side B	335
310	C.7.4	Exemplary approach to set a test point in CCM	335
311	C.7.5	Test cases	338
312	Annex D (normative)	EVSE of system D	396
313	D.1	General	396
314	D.2	Circuit diagrams	396
315	D.2.1	General	396
316	D.2.2	Circuit diagram for configuration GG	396
317	D.2.3	Disabled side B	405
318	D.3	Process of energy transfer	407
319	D.3.1	General	407
320	D.3.2	Normal startup	408
321	D.3.3	Normal shutdown during energy transfer	415
322	D.3.4	Error and emergency handling	418
323	D.3.5	Pause by EVSE	428
324	D.4	Safety related functions	428
325	D.4.1	Safety measures for side B	428
326	D.4.2	Vehicle coupler latching function	432
327	D.4.3	Loss of electrical continuity of the control pilot conductor	432
328	D.4.4	Loss of electrical continuity of the proximity detection conductor	432
329	D.4.5	Voltage check at initialization	432
330	D.4.6	Minimum cross-sectional area of the protective conductor	432
331	D.4.7	Loss of electrical continuity of the protective conductor	433
332	D.5	Additional functions	433
333	D.5.1	Pre-charge	433
334	D.5.2	Handling of operating ranges	433
335	D.5.3	Compatibility check (Parameter configuration)	433
336	D.6	Specific requirements	433
337	D.6.1	Requirements for load dump	433
338	D.6.2	Side B current regulation	434
339	D.6.3	Measuring current and voltage at side B	434
340	D.6.4	Overcurrent protection of side B	434
341	D.6.5	AC/DC overlay	435
342	D.7	Compatibility requirements	435

IEC CDV 61851-23 © IEC 2026

343	D.8	General test conditions	435
344	D.8.1	Operating points – Definitions	436
345	D.8.2	Standard test setup	437
346	D.8.3	Definition of measured values at side B	437
347	D.8.4	Exemplary approach to set a test point in CCM	437
348	D.8.5	Test cases	439
349	Annex E (normative)	Behaviour and requirements at side B to support grid code	
350		compliance for system C	464
351	E.1	General	464
352	E.1.1	Applicability	464
353	E.1.2	Priority of requirements on side B	464
354	E.2	Immunity to Disturbances	464
355	E.2.1	Introduction to grid code requirements on side A	464
356	E.2.2	Effect of grid events on side B	465
357	E.2.3	EVSE requirements at side B in support of grid code compliance	465
358	E.3	Active power response to frequency deviation	466
359	E.3.1	Introduction to grid code requirement on side A	466
360	E.3.2	Effect of grid events on side B	466
361	E.3.3	EVSE requirements at Side B in support of grid code compliance	466
362	E.4	Interface Protection	467
363	E.4.1	Introduction to grid code requirement on side A	467
364	E.4.2	Effect of grid events on side B	467
365	E.4.3	EVSE requirements at Side B in support of grid code compliance	467
366	E.4.4	Additional Requirements	467
367	E.5	Voltage support by reactive power	468
368	E.5.1	Introduction to grid code requirement on side A	468
369	E.5.2	Effect of grid events on side B	468
370	E.5.3	EVSE requirements at Side B in support of grid code compliance	468
371	E.6	Voltage related active power adaption	468
372	E.6.1	Introduction of grid code requirement on side A	468
373	E.6.2	Effect of grid events on side B	469
374	E.6.3	EVSE requirements at Side B in support of grid code compliance	469
375	E.7	Connection and starting to generate electrical power	469
376	E.7.1	Introduction to grid code requirement on side A	469
377	E.7.2	Effect of grid events on side B	470
378	E.7.3	EVSE requirements at Side B in support of grid code compliance	470
379	E.8	Ceasing and reduction of active power on set point	470
380	E.8.1	Introduction to grid code requirement on side A	470
381	E.8.2	Effect of grid events on side B	470
382	E.8.3	EVSE requirements at Side B in support of Grid Code compliance	471
383	E.9	Power import/export limits at the Point of Connection	471
384	E.9.1	Introduction to grid code requirement on side A	471
385	E.9.2	Effect of grid events on side B	471
386	E.9.3	EVSE requirements at Side B in support of Grid Code compliance	471
387	E.10	Event Notification	471
388	E.10.1	General	471
389	E.10.2	Event Notification for System C	472
390	E.11	Technical Limits of the EV	472
391	E.12	EV immunity, capability and behaviour	472

IEC CDV 61851-23 © IEC 2026

392	E.12.1	General	472
393	E.12.2	Immunity of the EV	472
394	E.12.3	Capability of the EV	473
395	E.12.4	Behaviour of the EV	473
396	Annex F (normative)	Test load impedance verification	474
397	F.1	General.....	474
398	F.2	Response curve verification	474
399	F.3	Test setup for test load verification (informative).....	477
400	F.4	Result	477
401	Annex G (normative)	Multi-side B separated EVSE	479
402	G.1	General.....	479
403	G.2	Classification and use case of multi-side B EVSE	479
404	G.2.1	System operation.....	479
405	G.2.2	Side B system	479
406	G.2.3	Configuration	479
407	G.3	Constructional requirements of a side B system.....	481
408	G.3.1	Constructional requirements of a side B system according to Annex A.....	481
409	G.3.2	Constructional requirements of a side B system according to Annex B.....	482
410	G.3.3	Constructional requirements of a side B system according to Annex C	482
411	G.3.4	Constructional requirements of a side B system according to Annex D	482
412	G.4	Side B system performance	482
413	G.4.1	General performance requirements.....	482
414	G.4.2	Performance of multi-side B EVSE providing simultaneous operation	482
415	G.5	Safety requirements.....	483
416	G.5.1	General safety requirements.....	483
417	G.5.2	Short-circuit protection	483
418	G.5.3	Overload protection	483
419	G.5.4	Access to live parts through an unmated vehicle connector during	
420		energy transfer	483
421	G.5.5	Additional safety requirements for multi-side B EVSE providing	
422		simultaneous operation.....	484
423	G.5.6	Diagnostic check of mechanical disconnection device in the side B	
424		system.....	484
425	G.5.7	Interconnected side B live parts (DC+/DC-) in multi-side B EVSE.....	484
426	Annex H (informative)	Communication and energy transfer process between the	
427		EVSE and the EV	485
428	H.1	General.....	485
429	H.2	System configuration	485
430	H.3	Energy transfer control process and state	485
431	H.3.1	General	485
432	H.3.2	Description of the initialization stage.....	486
433	H.3.3	Description of the energy transfer stage	486
434	H.3.4	Description of the shutdown stage	486
435	Annex I (informative)	Touch current and touch impulse current.....	487
436	I.1	General.....	487
437	I.2	Current through the human body.....	492
438	I.3	Conditional dependent thresholds	493
439	I.4	Hazards due to leakage between side B live parts and the protective	
440		conductor.....	493

IEC CDV 61851-23 © IEC 2026

441	I.5	Balanced versus unbalanced voltages at side B live parts (DC+/DC–).....	494
442	I.6	Insulation monitoring device.....	495
443	I.7	IMD reaction time.....	495
444	I.8	Conclusion.....	496
445	Annex J (informative)	Considerations for EVs with multiple vehicle inlets.....	497
446	Annex K (normative)	Evaluation of heat welding or other thermal wear of contact	
447	surfaces	498	
448	Annex L (normative)	Error codes for EVSE, EV and CSMS	499
449	L.1	General.....	499
450	L.2	Errors reported by the EVSE.....	500
451	L.3	Errors reported by the EV	504
452	L.4	Performance evaluation	504
453	Bibliography.....	506	
454			
455	Figure 1 – Case A connection	29	
456	Figure 2 – Case B connection	29	
457	Figure 3 – Case C connection.....	30	
458	Figure 4 – Example of a coupling session	40	
459	Figure 5 – Voltage V_{T8} to apply to simulate short period overvoltage at side B between		
460	DC+ and DC–	71	
461	Figure 6 – Typical voltages between side B live parts (DC+/DC–) and protective		
462	conductor under normal operation.....	74	
463	Figure 7 – IMD connection which results in a voltage more than the maximum voltage		
464	limits.....	75	
465	Figure 8 – Example of a fault between the secondary circuit and the protective		
466	conductor.....	78	
467	Figure 9 – Measurement of the touch leakage current.....	85	
468	Figure 10 – Touch time – DC voltage under single fault condition (water wet, fingertip		
469	to feet).....	87	
470	Figure 11 – Example of protective barriers.....	94	
471	Figure 12 – Apparatus to test the side B cable assembly anchorage	101	
472	Figure 13 – Test setup the side B cable assembly anchorage	102	
473	Figure 14 – Example of a side B cable assembly equipped with handle and a warning		
474	label attached to the cable	104	
475	Figure 15 – Example of an SPD-assembly having one voltage switching type SPD		
476	between side B live conductors (DC+/DC–) and protective conductor	111	
477	Figure 16 – Example setup of SPD for the protection of the EVSE against transients.....	112	
478	Figure 17 – Symbol ISO 7000-0434B:2004-01	127	
479	Figure 18 – Side B voltage tolerances in CVM	132	
480	Figure 19 – Current control delay for an increasing current request	134	
481	Figure 20 – Current control delay for a decreasing current control request.....	135	
482	Figure 21 – Voltage at side B in CVM operation in steady state with ripple	138	
483	Figure 22 – Setup to measure the maximum side B inductance.....	140	
484	Figure 23 – Reference device (RD) A_0.....	145	
485	Figure 24 – Test arrangement A_0.....	146	
486	Figure 25 – Reference device RD A_1	146	

487	Figure 26 – Test arrangement A_1	147
488	Figure 27 – Reference device RD C_0	148
489	Figure 28 – Test arrangement C_0	149
490	Figure 29 – Reference device RD C_1	149
491	Figure 30 – Test arrangement C_1	150
492	Figure 31 – Test procedure for EVSE with temperature-controlled energy transfer	152
493	Figure 32 – General test setup for system A	158
494	Figure 33 – General test setup for system B	159
495	Figure 34 – General test setup for system C	160
496	Figure 35 – General test setup for system D	161
497	Figure 36 – Test load example	162
498	Figure 37 – Operating points	164
499	Figure A.1 – Overall circuit diagram of system A EVSE and EV	166
500	Figure A.2 – Failure detection principle by detection of DC leakage current	170
501	Figure A.3 – Example of vehicle connector latch monitoring circuit	174
502	Figure A.4 – Example of vehicle inlet with the latch holder covered by a metal plate	
503	that inhibits latch holding	175
504	Figure A.5 – Flow diagram for forward power transfer	188
505	Figure A.6 – Sequence diagram for forward power transfer	189
506	Figure A.7 – Representation of the delay between the measurement and the digital	
507	communication transmission for system A	195
508	Figure A.8 – Acceptable range of the measured current at side B (target current of the	
509	EV $I_{EV_trg} = 50$ A)	196
510	Figure A.9 – Change in the target current requested by the EV	197
511	Figure A.10 – Side B performance of EVSE	198
512	Figure A.11 – Circuit diagram of a system A BPT EVSE and EV	199
513	Figure A.12 – Flow diagram for bidirectional power transfer	205
514	Figure A.13 – Sequence diagram for bidirectional power transfer	206
515	Figure A.14 – Transition of applicable maximum current of the EVSE at side B and	
516	target current of the EV during dynamic control	207
517	Figure B.1 – Upgraded system B EVSE circuit diagram	212
518	Figure B.2 – Sequence diagram for normal startup	215
519	Figure B.3 – Sequence diagram for normal shutdown and error shutdown	217
520	Figure B.4 – Sequence diagram for emergency shutdown triggered by the EV	219
521	Figure B.5 – Sequence diagram for emergency shutdown triggered by the EVSE	221
522	Figure B.6 – Sequence diagram for the EV compatible with the legacy EVSE	223
523	Figure B.7 – Sequence diagram for the EVSE compatible with the legacy EV	225
524	Figure B.8 – Representation of delay between the measures current and voltage at	
525	side B and the digital communication transmission for system B	227
526	Figure B.9 – Operating points and test points for side B current regulation in CCM	239
527	Figure B.10 – Operating points and test points for side B voltage regulation in CVM	242
528	Figure B.11 – Definition of CCM, CVM and CPM	243
529	Figure B.12 – Typical FPT process	244
530	Figure C.1 – Circuit diagram for a system C EVSE of configuration EE	247

IEC CDV 61851-23 © IEC 2026

531	Figure C.2 – Circuit diagram of a system C EVSE of configuration FF.....	250
532	Figure C.3 – Equivalent disabled side B of the EVSE.....	252
533	Figure C.4 – Example of a sequence diagram.....	255
534	Figure C.5 – Sequence diagram for normal startup	256
535	Figure C.6 – Sequence diagram for normal shutdown or pause after energy transfer by	
536	EV or EVSE	266
537	Figure C.7 – Sequence diagram for EVSE and EV initiated error shutdown.....	272
538	Figure C.8 – Sequence diagram for EV initiated error shutdown based on DIN TS	
539	70121 during energy transfer	275
540	Figure C.9 – Sequence diagram for an emergency shutdown executed by the EV	278
541	Figure C.10 – Sequence diagram for an emergency shutdown executed by the EVSE	281
542	Figure C.11 – Sequence diagram for pause before cable-check phase by EVSE using	
543	ISO 15118-2:2026 or ISO 15118-20:2022	284
544	Figure C.12 – Sequence diagram for pause after pre-charge phase and before energy	
545	transfer stage by the EVSE using ISO 15118-2:2014, ISO 15118-2:2026 or ISO 15118-	
546	20:2022 and ISO 15118-20:2022/AMD1:2025	290
547	Figure C.13 – Sequence diagram for renegotiation initiated by EV or EVSE using	
548	ISO 15118-2:2014 or ISO 15118-2:2026	299
549	Figure C.14 – Worst case equivalent circuit during pre-charge.....	308
550	Figure C.15 – Normal startup and restart methods sequence for the EVSE	311
551	Figure C.16 – Restart method verification on the EVSE	312
552	Figure C.17 – Example of a B1 – B2 transition.....	313
553	Figure C.18 – Example of a B1 – E – B1 – B2 transition.....	314
554	Figure C.19 – Example of a B1 – F – B1 – B2 transition.....	314
555	Figure C.20 – Normal startup and restart methods sequence for the EV	315
556	Figure C.21 – Example of a B – C – B toggle	316
557	Figure C.22 – Operating points	342
558	Figure C.23 – Approaching a single test point TP in CCM (example 1).....	345
559	Figure C.24 – Approaching multiple test points TP_n CCM (example 2)	346
560	Figure C.25 – Test points TP_n	355
561	Figure C.26 – Voltage at the vehicle connector	363
562	Figure C.27 – Test points TP_n for the load dump test.....	366
563	Figure C.28 – Test point matrix for side B current regulation in CCM including static	
564	deviation and ripple	370
565	Figure C.29 – Test point sequence for side B current regulation in CCM.....	373
566	Figure C.30 – Test point matrix for 0 A mode during energy transfer.....	374
567	Figure C.31 – Test point matrix for side B voltage regulation in CVM during pre-charge.....	377
568	Figure C.32 – Test point matrix for control delay of charging current in CCM	383
569	Figure C.33 – Test point sequence	385
570	Figure C.34 – Test points for voltage measurement during welding detection.....	395
571	Figure C.35 – Test setup for IMD measurement connections	402
572	Figure D.1 – Circuit diagram for an EVSE of configuration GG	406
573	Figure D.2 – Example of a circuit diagram for SRN1 (switched resistor network) in the	
574	EVSE of configuration GG.....	406