SLOVENSKI STANDARD
oSIST prEN IEC 62680-1-2:2026

01-december-2026

Vmesniki univerzalnega serijskega vodila za podatke in napajanje - 1-2. del: Skupne komponente - Specifikacija za zagotavljanje napajanja prek USB (hitri postopek)

Universal serial bus interfaces for data and power - Part 1-2: Common components - USB power delivery specification (Fast track)

Sample Document
get full document from standards.iteh.ai

Ta slovenski standard je istoveten z: **prEN IEC 62680-1-2:2026**

ICS:

35.200	Vmesniška in povezovalna oprema	Interface and interconnection equipment

oSIST prEN IEC 62680-1-2:2026 **en,fr,de**

2003-01.Slovenski inštitut za standardizacijo. Razmnoževanje celote ali delov tega standarda ni dovoljeno.

Sample Document

get full document from standards.iteh.ai

oSIST prEN IEC 62680-1-2:2026

100/4611/CDV

COMMITTEE DRAFT FOR VOTE (CDV)

PROJECT NUMBER:	
IEC 62680-1-2 ED9	
DATE OF CIRCULATION:	CLOSING DATE FOR VOTING:
2026-11-20	**2027-02-12**
SUPERSEDES DOCUMENTS:	

IEC TC 100 : AUDIO, VIDEO AND MULTIMEDIA SYSTEMS AND EQUIPMENT	
SECRETARIAT: Japan	SECRETARY: Ms Mahiru Uehara
OF INTEREST TO THE FOLLOWING COMMITTEES:	HORIZONTAL FUNCTION(S):
ASPECTS CONCERNED:	
☒ SUBMITTED FOR CENELEC PARALLEL VOTING **ATTENTION IEC-CENELEC PARALLEL VOTING** THE ATTENTION OF IEC NATIONAL COMMITTEES, MEMBERS OF CENELEC, IS DRAWN TO THE FACT THAT THIS COMMITTEE DRAFT FOR VOTE (CDV) IS SUBMITTED FOR PARALLEL VOTING. THE CENELEC MEMBERS ARE INVITED TO VOTE THROUGH THE CENELEC ONLINE VOTING SYSTEM.	☐ NOT SUBMITTED FOR CENELEC PARALLEL VOTING

Sample Document
Document from standards.iteh.ai

This document is still under study and subject to change. It should not be used for reference purposes.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Recipients of this document are invited to submit, with their comments, notification of any relevant "In Some Countries" clauses to be included should this proposal proceed. Recipients are reminded that the CDV stage is the final stage for submitting ISC clauses. (SEE AC/22/2007 OR NEW GUIDANCE DOC).

TITLE:

Universal Serial Bus interfaces for data and power - Part 1-2: Common components - USB Power Delivery specification (Fast track)

PROPOSED STABILITY DATE: 2031

Copyright © 2026 International Electrotechnical Commission, IEC. All rights reserved. It is permitted to download this electronic file, to make a copy and to print out the content for the sole purpose of preparing National Committee positions. You may not copy or "mirror" the file or printed version of the document, or any part of it, for any other purpose without permission in writing from IEC.

oSIST prEN IEC 62680-1-2:2026 • https://standards.iteh.ai/catalog/standards/sist/11980a8b-9a5c-46fa-927e-29ae15821360/osist-pren-iec-62680-1-2-2026

NOTE FROM TC/SC OFFICERS:

This is a fast-track process offered by USB-IF. The supplementing document, PDUSB Status Reporting and Device States Revision 1.1 is also subject to approval.

Sample Document

get full document from standards.iteh.ai

Sample Document

get full document from standards.iteh.ai

oSIST prEN IEC 62680-1-2:2026

Universal Serial Bus
Power Delivery Specification

Release 3.2, Version 1.2

May 20, 2026

Sample Document

get full document from standards.iteh.ai

oSIST prEN IEC 62680-1-2:2026 • https://standards.iteh.ai/catalog/standards/sist/11980a8b-9a5c-46fa-927e-29ae15821360/osist-pren-iec-62680-1-2-2026

oSIST prEN IEC 62680-1-2:2026

Universal Serial Bus Power Delivery Specification

Release 3.2, Version 1.2

Copyright © 2026 USB 3.0 Promoter Group: Apple Inc., Hewlett-Packard Inc., Intel Corporation, Microsoft Corporation, Renesas, STMicroelectronics, and Texas Instruments.

LIMITED COPYRIGHT LICENSE

The USB 3.0 Promoters grant a conditional copyright license under the copyrights embodied in the USB Power Delivery Specification to use and reproduce the specification for the sole purpose of, and solely to the extent necessary for, evaluating whether to implement the specification in products that would comply with the specification. Without limiting the foregoing, use of the specification for the purpose of filing or modifying any patent application to target the specification or USB-compliant products is not authorized. Except for this express copyright license, no other rights or licenses are granted, including without limitation any patent licenses. In order to obtain any additional intellectual property licenses or licensing commitments associated with the specification, a party must execute the USB 3.0 Adopters Agreement. Note: By using the specification, you accept these license terms on your own behalf and, in the case where you are doing this as an employee, on behalf of your employer.

INTELLECTUAL PROPERTY DISCLAIMER

This specification is provided to you "as is" with no warranties whatsoever, including any warranty of merchantability, non-infringement, or fitness for any particular purpose. The authors of this specification disclaim all liability, including liability for infringement of any proprietary rights, relating to use or implementation of information in this specification. The provision of this specification to you does not provide you with any license, express or implied, by estoppel or otherwise, to any intellectual property rights.

- USB Type-C®, USB-C®, and USB4® are trademarks of the Universal Serial Bus Implementers Forum (USB-IF). DisplayPort® is a registered trademark of VESA. Thunderbolt™ is a trademark of Intel Corporation. All product names are trademarks, registered trademarks, or service marks of their respective owners.
- You may only use the Thunderbolt™ trademark or logo in conjunction with products designed to this specification that complete proper certification and execute a Thunderbolt™ trademark license. See usb.org/compliance for further information.
- All rights reserved.
- Please send comments via electronic mail to techsup@usb.org.
- For industry information, refer to the USB Implementers Forum website at http://www.usb.org/.

Sample Document
get full document from standards.iteh.ai

oSIST prEN IEC 62680-1-2:2026 • https://standards.iteh.ai/catalog/standards/sist/11980a8b-9a5c-46fa-927e-29ae15821360/osist-pren-iec-62680-1-2-2026

oSIST prEN IEC 62680-1-2:2026

Table of Contents

1. Introduction 21
1.1. Cable and Connectors 21
1.2. Operational Overview 21
1.3. USB PD Roles 21
1.3.1. Source Port 21
1.3.2. Sink Port 22
1.3.3. Downstream Facing Port (DFP) 22
1.3.4. Upstream Facing Port (UFP) 22
1.3.5. Dual-Role Power (DRP) Ports 22
1.3.6. Dual-Role Data (DRD) Ports 22
1.3.7. VCONN Source 22
1.3.8. Cable Plugs 22
1.4. Power Delivery Operational Contracts 22
1.5. Source and Sink Operation in USB PD 23
1.5.1. General Source-to-Sink Initial Interaction 23
1.6. Common PD Device Types 24
1.7. USB-PD Architectural Overview 24
2. Glossary and Info 26
2.1. Conventions 26
2.1.1. Precedence 26
2.1.2. Keywords 26
2.1.3. Numbering 27
2.2. Related Documents 27
2.3. Terms and Abbreviations 27
3. Port Power Requirements 37
3.1. Introduction 37
3.2. Source Port Power Requirements 37
3.2.1. General Source Port Requirements 37
3.2.2. Guaranteed Capability Port 37
3.2.3. Managed Capability Port 38
3.2.4. Source Voltage and Current Requirements 38
3.2.5. **Optional** Source Voltage/Currents 41
3.2.5.1. Fixed, Variable and Battery Supply 41
3.2.5.2. SPR Programmable Power Supply (PPS) 42
3.2.5.3. Extended Power Range (EPR) 42
3.3. **Dynamic** Power Supply (DPS) 45
3.4. Sink Power Requirements 46
3.4.1. Sink Power Rule Considerations 46
3.4.2. Sink Requirements 47
3.5. Sink with Acessory Support 47
3.6. PDUSB Device Requirements 47
4. Power Delivery Electrical Requirements 48
4.1. Source Requirements 48
4.1.1. Behavioral Aspects 48
4.1.2. Source Bulk Capacitance 48
4.1.2.1. Source PDOs or APDOs 49
4.1.3. Source Transitions 50
4.1.3.1. Fixed Voltage Transitions 50
4.1.3.2. AVS/PPS Transitions 52
4.1.4. Non-application of VBUS Slew Rate Limits 58
4.1.5. Robust Source Operation 59
4.1.5.1. Output Over-Current Protection 59

Sample Document
Get full document from standards.iteh.ai

oSIST prEN IEC 62680-1-2:2026 • https://standards.iteh.ai/catalog/standards/sist/11980a8b-9a5c-46fa-927e-29ae15821360/osist-pren-iec-62680-1-2-2026

oSIST prEN IEC 62680-1-2:2026

4.1.5.2. Output Over-Voltage Protection 59
4.1.5.3. Over-Temperature Protection 59
4.1.5.4. vSafe5V Externally Applied to Ports Supplying vSafe5V 59
4.1.5.5. Detach 60
4.1.6. Source Peak Current Operation 60
4.1.7. Source Capabilities Extended Parameters 60
4.1.7.1. Load Step Slew Rate 61
4.1.7.2. Load Step Magnitude 61
4.1.7.3. Holdup Time Field 61
4.1.7.4. Compliance Field 61
4.1.7.5. Batteries 61
4.2. Sink Requirements 62
4.2.1. Behavioral Aspects 62
4.2.2. Sink Bulk Capacitance 62
4.2.3. Sink Standby 63
4.2.4. Suspend Power Consumption 63
4.2.5. Zero Negotiated Power 63
4.2.6. Transient Load Behavior 63
4.2.7. Considerations for Current Limit in PPS Mode 63
4.2.8. Sink Peak Current Operation 64
4.2.9. Robust Sink Operation 64
4.2.9.1. Sink Bulk Capacitance Discharge at Detach 64
4.2.9.2. Sink Over-Current Protection 64
4.2.9.3. Sink Over-Voltage Protection 65
4.2.9.4. Sink Over-Temperature Protection 65
4.3. Dual Role Ports 65
4.3.1. Swap Standby for the Initial Source 65
4.3.2. Swap Standby for the Initial Sink 65
4.3.3. Power Role Swap Sequence 66
4.4. Response to Hard Resets 67
4.4.1. Hard Reset Sequence 68
4.5. Transitions 69
4.5.1. Fixed and AVS transitions 69
4.5.1.1. Large-step voltage increases (Fixed or AVS) 69
4.5.1.2. Small-step voltage increases (AVS) 71
4.5.1.3. Unchanged or decreased voltage transitions (current unchanged, increased, or decreased) 72
4.5.2. PPS voltage or current changes 74
4.5.2.1. PPS voltage transitions (CV Mode) 74
4.5.2.2. PPS current transitions (CL Mode) 76
4.6. VCONN Power Cycle 78
4.7. Electrical Parameters 78
4.7.1. Source Electrical Parameters 78
4.7.2. Sink Electrical Parameters 83
4.7.3. Common Electrical Parameters 84
5. PD Communications Physical Layer 85
5.1. Overview 85
5.2. Signaling Through DC Biasing 85
5.2.1. Power Role Indication 85
5.2.2. Collision Avoidance 85
5.2.2.1. Definition of Idle 86
5.3. BMC Signaling 86
5.3.1. Transmission 86
5.3.1.1. Packet Formation 87
5.3.1.2. Resets 90

Preview Document
Click to view the full PDF of oSIST prEN IEC 62680-1-2:2026
Document from standards.iteh.ai

oSIST prEN IEC 62680-1-2:2026 • https://standards.iteh.ai/catalog/standards/sist/11980a8b-9a5c-46fa-927e-29ae15821360/osist-pren-iec-62680-1-2-2026

oSIST prEN IEC 62680-1-2:2026

5.3.2. Reception 91
5.3.2.1. Preamble 94
5.3.2.2. Ordered Sets (K-codes) 94
5.3.2.3. Payload Processing 94
5.3.3. Electrical Characteristics for Transmission and Reception 95
5.3.4. Encoding and Signaling 95
5.3.4.1. Transmit Mask 98
5.3.4.2. Receive Masks 100
5.3.4.3. Transmit Load Model 105
5.3.4.4. Cable Plug Transceivers 106
5.3.4.5. Transceiver with VCONN Source Capability 107
5.3.4.6. Capacitance when not transmitting 108
5.3.4.7. Source Output Impedance 108
5.3.4.8. Bit Rate Drift 108
5.3.4.9. Inter-Frame Gap 109
5.3.4.10. Shorting of Transmitter Output 109
5.4. Built in Self-Test (BIST) 109
5.4.1. BIST Carrier Mode 109
5.5. PD Communications Physical Layer Parameters 110
5.5.1. BMC Common Parameters 110
5.5.2. BMC Transmitter Parameters 110
5.5.3. BMC Receiver Parameters 110
6. PD Communications Protocol Message Definitions 112
6.1. Overview 112
6.1.1. Message Types 112
6.1.2. Message ID 112
6.1.3. Specification Revision 112
6.1.3.1. SOP Specification Revision Detection Process 113
6.1.3.2. SOP' Specification Revision Detection Process 113
6.1.4. Chunking 114
6.1.5. Vendor and Product IDs 115
6.2. Message Construction 116
6.2.1. Message Header 116
6.2.2. Number of Data Objects 117
6.3. Control Message 118
6.3.1. GoodCRC Message 119
6.3.2. GotoMin Message (**Deprecated**) 119
6.3.3. Accept Message 119
6.3.4. Reject Message 119
6.3.5. Ping Message (**Deprecated**) 120
6.3.6. PS_RDY Message 120
6.3.7. Get_Source_Cap Message 120
6.3.8. Get_Sink_Cap Message 121
6.3.9. DR_Swap Message 121
6.3.10. PR_Swap Message 121
6.3.11. VCONN_Swap Message 121
6.3.12. Wait Message 121
6.3.13. Soft_Reset Message 122
6.3.14. Data_Reset Message 122
6.3.15. Data_Reset_Complete Message 122
6.3.16. Not_Supported Message 122
6.3.17. Get_Source_Cap_Extended Message 123
6.3.18. Get_Status Message 123
6.3.19. FR_Swap Message 123
6.3.20. Get_PPS_Status 123

Sample Document
Get full document from standards.iteh.ai

oSIST prEN IEC 62680-1-2:2026 • https://standards.iteh.ai/catalog/standards/sist/11980a8b-9a5c-46fa-927e-29ae15821360/osist-pren-iec-62680-1-2-2026

oSIST prEN IEC 62680-1-2:2026

6.3.21. Get_Country_Codes 123
6.3.22. Get_Sink_Cap_Extended Message 124
6.3.23. Get_Source_Info Message 124
6.3.24. Get_Revision Message 124
6.4. Data Message 124
6.4.1. Capabilities Messages 125
6.4.1.1. Source_Capabilities Message 125
6.4.1.2. Sink_Capabilities Message 126
6.4.1.3. Power Data Objects 126
6.4.2. Request Message 136
6.4.2.1. Sink Request Data Objects 137
6.4.3. BIST Message 140
6.4.3.1. BIST Test Data Mode 140
6.4.3.2. BIST Shared Capacity Test Mode 140
6.4.3.3. BIST Shared Test Mode Entry 140
6.4.3.4. BIST Shared Test Mode Exit 141
6.4.4. Battery_Status Message 141
6.4.5. Alert Message 142
6.4.5.1. Power State Change Extended Event 144
6.4.5.2. Power Button Press Extended Event 144
6.4.5.3. Power Button Release Extended Event 144
6.4.5.4. Controller Initiated Wake Extended Event 144
6.4.5.5. Source Reducing Capabilities Extended Event 144
6.4.6. Get_Country_Info Message 144
6.4.7. Enter_USB Message 145
6.4.8. EPR_Request Message 146
6.4.9. EPR_Mode Message 147
6.4.10. Source_Info Message 148
6.4.11. Revision Message 149
6.4.12. Vendor Defined Message 150
6.4.12.1. Unstructured VDM 151
6.4.12.2. Structured VDM 151
6.4.12.3. Discover Identity 154
6.4.12.4. Discover SVIDs 168
6.4.12.5. Discover Mode 170
6.4.12.6. Enter Mode 170
6.4.12.7. Exit Mode 170
6.4.12.8. Attention 171
6.5. Extended Message 171
6.5.1. Extended Message Header 172
6.5.1.1. Chunked 172
6.5.2. Source_Capabilities_Extended Message 173
6.5.2.1. Touch Current Field 175
6.5.2.2. Peak Current Fields 176
6.5.3. Status Message 176
6.5.4. Get_Battery_Cap Message 181
6.5.5. Get_Battery_Status Message 181
6.5.6. Battery_Capabilities Message 182
6.5.7. Get_Manufacturer_Info Message 182
6.5.8. Manufacturer_Info Message 183
6.5.9. Security_Request Message 183
6.5.10. Security_Response Message 183
6.5.11. Firmware_Update_Request Message 184
6.5.12. Firmware_Update_Response Message 184
6.5.13. PPS_Status Message 184

Preview Document
Document from standards.iteh.ai

oSIST prEN IEC 62680-1-2:2026 • https://standards.iteh.ai/catalog/standards/sist/11980a8b-9a5c-46fa-927e-29ae15821360/osist-pren-iec-62680-1-2-2026

oSIST prEN IEC 62680-1-2:2026

6.5.14. Country_Info Message 185
6.5.15. Country_Codes Message 186
6.5.16. Sink_Capabilities_Extended Message 186
6.5.16.1. Minimum PDP 189
6.5.16.2. Operational PDP 189
6.5.16.3. Maximum PDP 190
6.5.17. Extended_Control Message 190
6.5.17.1. EPR_Get_Source_Cap Message 190
6.5.17.2. EPR_Get_Sink_Cap Message 190
6.5.17.3. EPR_Keep_Alive Message 191
6.5.17.4. EPR_Keep_Alive_Ack Message 191
6.5.18. EPR_Source_Capabilities Message 191
6.5.19. EPR_Sink_Capabilities Message 192
6.5.20. Vendor_Defined_Extended Message 192
6.6. Value Parameters 193
7. PD Communications Protocol Message Usage 194
7.1. Reset 194
7.1.1. Soft Reset and Protocol Error 194
7.1.2. Data Reset 196
7.1.3. Hard Reset 196
7.1.3.1. Cable Plugs and Hard Reset 197
7.1.3.2. Modal Operation and Hard Reset 197
7.1.4. Cable Reset 197
7.2. Collision Avoidance 197
7.3. Message Discarding 198
7.4. Common Messages 198
7.4.1. Accept 198
7.4.2. Reject 198
7.4.3. Wait 199
7.5. Applicability Tables 199
7.6. AMS Usages 204
7.6.1. Basic Message Exchange 204
7.6.2. Possible Points of Failure for Message Delivery 205
7.7. Soft Reset AMS 206
7.8. Data Reset AMS 206
7.9. Power Negotiation (SPR) AMS 207
7.9.1. Source_Capabililties Message 207
7.9.1.1. Power Data Objects 207
7.9.1.2. USB Suspend Supported 207
7.9.1.3. Unconstrained Power 207
7.9.1.4. EPR Mode Capable 208
7.9.1.5. Source Offering No Capabilities 208
7.9.2. Request Message 208
7.9.2.1. Capability Mismatch 208
7.9.2.2. Wait in Response to Request Message 209
7.9.3. PS_Rdy 209
7.10. Power Role Swap AMS 209
7.10.1. Wait in response to a PR_Swap Message 210
7.11. Fast Role Swap AMS 210
7.12. Data Role Swap AMS 210
7.12.1. DR_Swap 210
7.12.2. Wait in response to a DR_Swap Message 211
7.13. VCONN Swap AMS 211
7.13.1. Wait in response to a VCONN_Swap Message 212
7.14. Alert AMS Message 212

Sample Document
Get full document from standards.iteh.ai

oSIST prEN IEC 62680-1-2:2026 • https://standards.iteh.ai/catalog/standards/sist/11980a8b-9a5c-46fa-927e-29ae15821360/osist-pren-iec-62680-1-2-2026

oSIST prEN IEC 62680-1-2:2026

7.14.1. Alert Types 212
7.15. Get Status AMS 212
7.16. Get PPS Status AMS 213
7.17. Get Source Capabilities (SPR) AMS 213
7.18. Get Sink Capabilities (SPR) AMS 213
7.19. Extended Capabilities AMS 213
7.19.1. Get_Source_Cap_Extended 213
7.19.2. Source_Capabilities_Extended 213
7.19.2.1. Touch Current Field 213
7.19.2.2. Peak Current Field 213
7.19.2.3. Number of Batteries/Battery Slots Field 214
7.19.3. Get_Sink_Cap_Extended 214
7.19.4. Sink_Capabilities_Extended 214
7.19.4.1. XID Field 214
7.19.4.2. Battery Info 214
7.19.4.3. Sink Modes 214
7.20. Battery Capabilities AMS 214
7.20.1. Get_Battery_Cap Message 214
7.21. Battery Status AMS 214
7.21.1. Get_Battery_Status Message 214
7.21.2. Battery Status Message 214
7.22. Manufacturer Information AMS 215
7.22.1. Get_Manufacturer_Info Message 215
7.22.2. Manufacturer_Info Message 215
7.23. Country Codes AMS 215
7.23.1. Get_Country_Codes Message 215
7.23.2. Country Codes Message 215
7.24. Country Information AMS 215
7.24.1. Country_Info Message 215
7.25. Revision Information AMS 215
7.25.1. Get_Revision Message 215
7.25.2. Revision Message 215
7.26. Source Information AMS 215
7.26.1. Get_Source_Info Message 215
7.26.2. Source_Info Message 215
7.26.2.1. Port Maximum PDP Field 216
7.26.2.2. Port Present PDP Field 216
7.26.2.3. Port Guaranteed PDP Field 216
7.27. Security AMS 216
7.28. Firmware Update AMS 216
7.29. Enter USB AMS 217
7.29.1. Wait in Response to an Enter_USB Message 217
7.30. EPR Mode AMS 217
7.30.1. Process to Enter EPR Mode AMS 217
7.30.2. EPR_Source_Capabilities Message 221
7.30.3. EPR_Request Message 221
7.30.4. EPR_Sink_Capabilities Message 222
7.30.5. Operation in EPR Mode 222
7.30.6. EPR_Keep_Alive Message 222
7.30.7. Exiting EPR Mode 222
7.30.7.1. Commanded Exit 222
7.30.7.2. Implicit Exit 223
7.30.7.3. Exits due to errors 223
7.30.8. EPR_Get_Source_Cap Message 223
7.30.9. EPR_Get_Sink_Cap Message 223

iTeh Standards
(https://standards.iteh.ai)
Document Preview

oSIST prEN IEC 62680-1-2:2026 • https://standards.iteh.ai/catalog/standards/sist/11980a8b-9a5c-46fa-927e-29ae15821360/osist-pren-iec-62680-1-2-2026

oSIST prEN IEC 62680-1-2:2026

7.31. Timers 224
7.31.1. CRCReceiveTimer 224
7.31.2. SenderResponseTimer 224
7.31.3. Capability Timers 224
7.31.3.1. SourceCapabilityTimer 225
7.31.3.2. SinkWaitCap Timer 225
7.31.3.3. tFirstSourceCap 225
7.31.4. Wait Timers and Times 225
7.31.4.1. SinkRequestTimer 225
7.31.4.2. tPRSwapWait 226
7.31.4.3. tDRSwapWait 226
7.31.4.4. tVconnSwapWait 226
7.31.4.5. tVconnSwapDelayDFP 226
7.31.4.6. tVconnSwapDelayUFP 226
7.31.4.7. tEnterUSBWait 226
7.31.5. Power Supply Timers 226
7.31.5.1. PSTransition Timer 226
7.31.5.2. PSSourceOffTimer 227
7.31.5.3. PSSourceOnTimer 227
7.31.5.4. NoResponseTimer 228
7.31.6. BIST Timers 228
7.31.6.1. tBISTCarrierMode 228
7.31.6.2. BISTContModeTimer 228
7.31.6.3. tBISTSharedTestMode 228
7.31.7. Power Role Swap Timers 229
7.31.7.1. SwapSourceStartTimer 229
7.31.8. Soft Reset Timers 229
7.31.8.1. tSoftReset 229
7.31.8.2. tProtErrSoftReset 229
7.31.9. Data Reset Timers 229
7.31.9.1. VCONNDischargeTimer 229
7.31.9.2. tDataReset 229
7.31.9.3. DataResetFailTimer 229
7.31.9.4. DataResetFailUFPTimer 229
7.31.10. Hard Reset Timers 230
7.31.10.1. HardResetCompleteTimer 230
7.31.10.2. PSHardResetTimer 230
7.31.10.3. tDRSwapHardReset 230
7.31.10.4. tProtErrHardReset 230
7.31.10.5. tSendHardReset 230
7.31.10.6. tInitiateErrorRecovery 230
7.31.11. Structured VDM Timers 230
7.31.11.1. VDMResponseTimer 230
7.31.11.2. VDMModeEntryTimer 231
7.31.11.3. VDMModeExitTimer 231
7.31.11.4. tVDMBusy 231
7.31.12. VCONN Timers 231
7.31.12.1. VconnOnTimer 231
7.31.12.2. tVconnSourceOff 232
7.31.12.3. tCableMessage 232
7.31.12.4. DiscoverIdentityTimer 232
7.31.13. Collision Avoidance Timers 232
7.31.13.1. SinkTxTimer 232
7.31.13.2. tSrcHoldsBus 232
7.31.14. Fast Role Swap Timers 232

Sample Document
Text extracted from standards.iteh.ai

oSIST prEN IEC 62680-1-2:2026 • https://standards.iteh.ai/catalog/standards/sist/11980a8b-9a5c-46fa-927e-29ae15821360/osist-pren-iec-62680-1-2-2026

oSIST prEN IEC 62680-1-2:2026

7.31.14.1. tFRSwap5V 232
7.31.14.2. tFRSwapComplete 233
7.31.14.3. tFRSwapInit 233
7.31.15. Chunking Timers 233
7.31.15.1. ChunkingNotSupportedTimer 233
7.31.15.2. ChunkSenderRequestTimer 233
7.31.15.3. ChunkSenderResponseTimer 234
7.31.16. Programmable Power Supply Timers 234
7.31.16.1. SinkPPSPeriodicTimer 234
7.31.16.2. SourcePPSCommTimer 234
7.31.17. tEnterUSB 235
7.31.18. EPR Timers 235
7.31.18.1. SinkEPREnterTimer 235
7.31.18.2. SourceEPRKeepAlive Timer 235
7.31.18.3. tEPRSourceCableDiscovery 235
7.31.19. Time Values and Timers 236
7.32. Counters 238
7.32.1. MessageID Counter 238
7.32.2. Transmitter Usage 238
7.32.3. Receiver Usage 239
7.32.4. Retry Counter 239
7.32.5. Hard Reset Counter 239
7.32.6. Capabilities Counter 239
7.32.7. Discover Identity Counter 240
7.32.8. VDMBusyCounter 240
7.32.9. Counter Values and Counters 240
8. Vendor Defined Message Usage and Alternate Modes 241
8.1. Overview 241
8.2. Alternate Modes 241
8.3. General VDM Rules 241
8.4. Unstructured VDM Rules 241
8.5. Structured VDM Rules 242
8.5.1. Structured VDM Version 242
8.5.2. Object Position 242
8.5.3. SVID 242
8.6. Command Usage 242
8.6.1. Discover Identity 244
8.6.1.1. SOP Use 244
8.6.1.2. SOP' Usage 244
8.6.2. Discover SVIDs 245
8.6.2.1. SOP' Usage 246
8.6.3. Discover Modes 246
8.6.4. Enter Mode Command 246
8.6.5. Exit Mode Command 248
8.6.6. Attention 249
8.7. Command Processes 250
8.7.1. Discovery Process 250
8.7.1.1. Port Partner Discovery 250
8.7.1.2. Cable Plug Discovery 251
8.7.2. Entering Alternate Modes 251
8.7.3. Exiting Alternate Modes 251
9. State Machine Diagrams 254
9.1. Protocol Layer State Diagrams 254
9.1.1. Introduction to Protocol Layer State Diagrams 254
9.1.2. State Operation 255

Sample Document
Document from standards.iteh.ai

oSIST prEN IEC 62680-1-2:2026 • https://standards.iteh.ai/catalog/standards/sist/11980a8b-9a5c-46fa-927e-29ae15821360/osist-pren-iec-62680-1-2-2026