



**SLOVENSKI STANDARD**  
**oSIST prEN IEC 62955:2025**  
**01-november-2025**

---

**Naprava za zaznavanje preostalega enosmernega toka (RDC-DD) za uporabo pri polnjenju električnih vozil v načinu 3**

Residual direct current detecting device (RDC-DD) to be used for mode 3 charging of electric vehicles

Dispositif de détection à courant différentiel résiduel continu (DD-CDC) à utiliser pour la charge en mode 3 des véhicules électriques

**Ta slovenski standard je istoveten z: prEN IEC 62955:2025**

---

<https://standards.iteh.ai/catalog/standards/sist/8b73a114-ccb1-448f-9bf0-50d3fd777806/osist-pren-iec-62955-2025>

**ICS:**

29.120.50	Varovalke in druga nadtokovna zaščita	Fuses and other overcurrent protection devices
-----------	---------------------------------------	--

**oSIST prEN IEC 62955:2025**

**en,fr,de**





# 23E/1403/CDV

## COMMITTEE DRAFT FOR VOTE (CDV)

PROJECT NUMBER: <b>IEC 62955 ED2</b>	
DATE OF CIRCULATION: <b>2025-09-05</b>	CLOSING DATE FOR VOTING: <b>2025-11-28</b>
SUPERSEDES DOCUMENTS: <b>23E/1356/CD, 23E/1398/CC</b>	

IEC SC 23E : CIRCUIT-BREAKERS AND SIMILAR EQUIPMENT FOR HOUSEHOLD USE	
SECRETARIAT: Italy	SECRETARY: Mr Sergio Bossi
OF INTEREST TO THE FOLLOWING COMMITTEES: TC 69	HORIZONTAL FUNCTION(S):
ASPECTS CONCERNED: Electromagnetic Compatibility, Safety	
<input checked="" type="checkbox"/> SUBMITTED FOR CENELEC PARALLEL VOTING	<input type="checkbox"/> NOT SUBMITTED FOR CENELEC PARALLEL VOTING
<p><b>Attention IEC-CENELEC parallel voting</b></p> <p>The attention of IEC National Committees, members of CENELEC, is drawn to the fact that this Committee Draft for Vote (CDV) is submitted for parallel voting.</p> <p>The CENELEC members are invited to vote through the CENELEC online voting system.</p>	

<https://standards.iteh.ai/catalog/standards/sist/8b73a114-ccb1-448f-9bf0-50d3fd777806/osist-pren-iec-62955-2025>

This document is still under study and subject to change. It should not be used for reference purposes.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Recipients of this document are invited to submit, with their comments, notification of any relevant "In Some Countries" clauses to be included should this proposal proceed. Recipients are reminded that the CDV stage is the final stage for submitting ISC clauses. (SEE [AC/22/2007](#) OR [NEW GUIDANCE DOC](#)).

TITLE:

**Residual direct current detecting device (RDC-DD) to be used for mode 3 charging of electric vehicles**

PROPOSED STABILITY DATE: 2029

NOTE FROM TC/SC OFFICERS:

**Copyright © 2025 International Electrotechnical Commission, IEC.** All rights reserved. It is permitted to download this electronic file, to make a copy and to print out the content for the sole purpose of preparing National Committee positions. You may not copy or "mirror" the file or printed version of the document, or any part of it, for any other purpose without permission in writing from IEC.

## IEC CDV 62955 Ed2 © IEC 2025

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44

## CONTENTS

FOREWORD.....	8
INTRODUCTION.....	10
1 Scope.....	11
2 Normative references .....	11
3 Terms and definitions .....	13
3.1 Terms and definitions relating to RDC-DDs.....	13
3.2 Symbols.....	13
4 Classification.....	13
4.1 RDC-DDs are classified according to the type of construction .....	13
4.1.1 RDC-DD consisting of an RDC-DD module electrically coupled to a separate switching device (contactor or relay according to IEC 61851-1) and intended to be integrated into the EVSE.....	13
4.1.2 RDC-DD with integrated AC, pulsating DC detection, evaluation and mechanical switching, suitable for isolation, in one device .....	14
4.2 According to the number of poles.....	14
4.3 According to the method of connection .....	14
4.4 According to the type of terminals.....	14
4.4.1 RDC-DD with screw-type terminals for external copper conductors;.....	14
4.4.2 RDC-DD with screwless type terminals for external copper conductors;.....	14
4.4.3 RDC-DD with flat quick-connect terminals for external copper conductors;.....	14
4.4.4 RDC-DD with screw-type terminals for external aluminium conductors;.....	14
4.4.5 RDC-DD without terminals for external conductors. ....	14
4.5 According to the range of ambient air temperature.....	14
4.5.1 Ambient air temperature range $-5\text{ }^{\circ}\text{C}$ up to $40\text{ }^{\circ}\text{C}$ .....	14
4.5.2 Ambient air temperature range $-25\text{ }^{\circ}\text{C}$ up to $40\text{ }^{\circ}\text{C}$ .....	14
5 Characteristics of RDC-DDs .....	14
5.1 Summary of characteristics .....	14
5.2 Rated quantities and other characteristics.....	15
5.2.1 Rated voltages .....	15
5.2.2 Rated current ( $I_n$ ).....	15
5.2.3 Rated DC residual operating current ( $I_{\Delta\text{dc}}$ ) .....	15
5.2.4 Rated DC residual non-operating current ( $I_{\Delta\text{ndc}}$ ) .....	16
5.2.5 Rated frequency .....	16
5.2.6 Rated making and breaking capacity ( $I_m$ ).....	16
5.3 Standard and preferred values .....	16
5.3.1 Preferred values of rated operational voltage ( $U_e$ ).....	16
5.3.2 Preferred values of rated current ( $I_n$ ).....	16
5.3.3 Standard value of rated DC residual operating current ( $I_{\Delta\text{dc}}$ ) .....	17
5.3.4 Standard value of DC residual non-operating current ( $I_{\Delta\text{ndc}}$ ) .....	17
5.3.5 Preferred values of rated frequency .....	17
5.3.6 Minimum value of the rated making and breaking capacity ( $I_m$ ).....	17

## IEC CDV 62955 Ed2 © IEC 2025

45	5.3.7	Standard and preferred values of the rated conditional short-circuit current ( $I_{nc}$ ).....	17
46			
47	5.3.8	Standard and preferred values of the rated conditional residual short-circuit current ( $I_{\Delta c}$ ).....	17
48			
49	5.3.9	Limiting values of break time .....	18
50	5.3.10	Standard value of rated impulse withstand voltage ( $U_{imp}$ ) .....	18
51	5.4	Coordination with short-circuit protective devices (SCPDs) .....	19
52	5.4.1	General .....	19
53	5.4.2	Rated conditional short-circuit current ( $I_{nc}$ ) .....	19
54	5.4.3	Rated conditional residual short-circuit current ( $I_{\Delta c}$ ).....	19
55	6	Marking and other product information.....	19
56	7	Standard conditions for operation in service and for installation .....	20
57	7.1	Standard conditions .....	20
58	7.2	Conditions for installations .....	21
59	7.3	Pollution degree.....	21
60	8	Requirements for construction and operation .....	21
61	8.1	Design requirements .....	21
62	8.1.1	General .....	21
63	8.1.2	Mechanism .....	22
64	8.1.3	Clearances and creepage distances .....	23
65	8.1.4	Screws, current-carrying parts and connections .....	26
66	8.1.5	RDC-DD provided with terminals for external conductors .....	27
67	8.1.6	Requirements for electrical circuits and connections for RDC-DD according 4.1.1 .....	30
68			
69	8.2	Protection against electric shock.....	30
70	8.3	Dielectric properties .....	30
71	8.4	Temperature rise .....	31
72	8.4.1	Temperature rise limits .....	31
73	8.4.2	Ambient air temperature .....	31
74	8.5	Operating characteristics .....	31
75	8.6	Electrical endurance .....	31
76	8.7	Performance at short-circuit currents .....	32
77	8.8	Resistance to mechanical shock and impact .....	32
78	8.9	Resistance to heat .....	32
79	8.10	Resistance to abnormal heat and to fire .....	32
80	8.11	Performance of the test function .....	32
81	8.12	Behaviour of RDC-DD in the case of current surges caused by impulse voltages .....	33
82			
83	8.13	Reliability.....	33
84	8.14	Electromagnetic compatibility (EMC).....	33
85	9	Tests .....	33
86	9.1	General.....	33
87	9.1.1	Type Tests .....	33
88	9.1.2	Testing procedure for the different type of RDC-DDs .....	33
89	9.1.3	Routine tests .....	34
90	9.2	Test conditions .....	34
91	9.2.1	General test conditions .....	34
92	9.2.2	RDC-DD classified according to 4.1.1 .....	34

## IEC CDV 62955 Ed2 © IEC 2025

93	9.2.3	RDC-DD classified according to 4.1.2 .....	34
94	9.3	Test of indelibility of marking .....	35
95	9.4	Test of reliability of screws, current-carrying parts and connections .....	35
96	9.5	Tests of reliability of screw-type terminals for external copper conductors.....	37
97	9.6	Verification of protection against electric shock.....	38
98	9.7	Test of dielectric properties.....	39
99	9.7.1	Resistance to humidity.....	39
100	9.7.2	Insulation resistance of the main circuit .....	39
101	9.7.3	Dielectric strength of the main circuit .....	40
102	9.7.4	Insulation resistance and dielectric strength of secondary circuits and	
103		control circuits .....	41
104	9.7.5	Secondary circuit of detection transformers .....	42
105	9.7.6	Capability of control circuits connected to the main circuit withstanding	
106		high DC voltages due to insulation measurements .....	42
107	9.7.7	Verification of impulse withstand voltages (across clearances and	
108		across solid insulation) .....	42
109	9.8	Test of temperature-rise.....	45
110	9.8.1	Ambient air temperature .....	45
111	9.8.2	Test procedure .....	46
112	9.8.3	Measurement of the temperature of parts .....	46
113	9.8.4	Temperature rise of a part .....	46
114	9.9	Verification of the operating characteristics .....	46
115	9.9.1	Test circuit and test procedure.....	46
116	9.9.2	Verification of correct operation of RDC-DD with smooth DC residual	
117		current.....	47
118	9.9.3	Verification of non-operating time for alternating residual currents.....	49
119	9.10	Verification of mechanical and electrical endurance .....	49
120	9.10.1	General test conditions.....	49
121	9.10.2	Test procedure.....	50
122	9.10.3	Condition of the RDC-DD after test.....	51
123	9.11	Verification of the behaviour of the RDC-DD under short-circuit conditions .....	51
124	9.11.1	List of the short-circuit tests.....	51
125	9.11.2	Short-circuit tests .....	51
126	9.12	Verification of resistance to mechanical shock and impact .....	59
127	9.12.1	General .....	59
128	9.12.2	Mechanical shock .....	59
129	9.12.3	Mechanical impact.....	60
130	9.13	Test of resistance to heat.....	62
131	9.13.1	Resistance to high temperature .....	62
132	9.13.2	Ball pressure test at 125 °C.....	62
133	9.13.3	Ball pressure test at temperature lower than 125 °C .....	63
134	9.14	Test of resistance to abnormal heat and to fire .....	63
135	9.15	Verification of the trip-free function .....	64
136	9.15.1	General test conditions .....	64
137	9.15.2	Test procedure .....	64
138	9.16	Verification of the operation of the test function at the limits of rated	
139		operational voltage .....	64
140	9.17	Verification of behaviour of RDC-DD in case of current surges caused by	
141		impulse voltages .....	65
142	9.17.1	General .....	65

## IEC CDV 62955 Ed2 © IEC 2025

143	9.17.2	Current surge test for all RDC-DD (0,5 $\mu$ s/100 kHz ring wave test) .....	65
144	9.17.3	Verification of behaviour at surge currents up to 3 000 A (8/20 $\mu$ s surge	
145		current test).....	65
146	9.18	Verification of reliability .....	66
147	9.18.1	General .....	66
148	9.18.2	Climatic test.....	66
149	9.18.3	Test with temperature of 40 °C .....	68
150	9.19	Verification of withstand against ageing .....	68
151	9.20	Electromagnetic compatibility (EMC) .....	69
152	9.20.1	General .....	69
153	9.20.2	Electromagnetic emission of RDC-DD.....	69
154	9.20.3	Electromagnetic immunity of RDC-DD .....	69
155	9.21	Test of resistance to rusting .....	70
156	9.22	Verification of behaviour in case of disconnection of the current transformer .....	71
157	Annex A (normative)	Test sequences and number of samples to be submitted for	
158		certification purposes .....	94
159	A.1	Test sequences .....	94
160	A.2	Number of samples to be submitted for full test procedure .....	95
161	A.3	Number of samples to be submitted for simplified test procedures in the	
162		case of submitting simultaneously a range of RDC-DDs of the same	
163		fundamental design.....	96
164	Annex B (normative)	Determination of clearances and creepage distances .....	99
165	B.1	General.....	99
166	B.2	Orientation and location of a creepage distance.....	99
167	B.3	Creepage distances where more than one material is used .....	99
168	B.4	Creepage distances split by floating conductive part .....	99
169	B.5	Measurement of creepage distances and clearances .....	99
170	Annex C (normative)	Arrangement for the detection of the emission of ionized gases	
171		during short-circuit tests .....	104
172	Annex D (normative)	Routine tests.....	107
173	D.1	General.....	107
174	D.2	Tripping test.....	107
175	D.3	Electric strength test .....	107
176	D.4	Performance of the test device.....	107
177	Annex E (informative)	Methods for determination of short-circuit power factor .....	108
178	E.1	General.....	108
179	E.2	Method I – Determination from DC components .....	108
180	E.3	Method II – Determination with pilot generator .....	108
181	Annex F (informative)	Examples of terminal designs .....	110
182	Annex G (informative)	Correspondence between ISO and AWG copper conductors .....	113
183	Annex H (informative)	SCPDs for short-circuit tests .....	114
184	H.1	Introductory remark.....	114
185	H.2	Silver wires .....	114
186	H.3	Fuses.....	114
187	H.4	Other means .....	115
188	Annex I (normative)	RDC-DD with integrated AC, pulsating DC detection, evaluation	
189		and mechanical switching, suitable for isolation, in one device according to	
190		classification 4.1.2.....	116
191	I.1	Scope .....	116