



SLOVENSKI STANDARD

SIST EN 12896-8:2026

01-december-2026

Nadomešča:
SIST EN 12896-8:2019

Javni prevoz - Referenčni podatkovni model - 8. del: Informacije o upravljanju in statistika

Public transport - Reference data model - Part 8: Management information & statistics

Öffentlicher Verkehr - Referenzdatenmodell - Teil 8: Managementinformationen und Statistiken

Transports publics - Modèle de données de référence - Partie 8 : tableaux de bord et statistiques

Ta slovenski standard je istoveten z: EN 12896-8:2026

ICS:

35.240.60	Uporabniške rešitve IT v prometu	IT applications in transport
-----------	----------------------------------	------------------------------

SIST EN 12896-8:2026

en,fr,de

Sample Document

get full document from standards.iteh.ai

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 12896-8

September 2026

ICS 35.240.60

Supersedes EN 12896-8:2019

English Version

**Public transport - Reference data model - Part 8:
Management information & statistics**

Transports publics - Modèle de données de référence -
Partie 8 : tableaux de bord et statistiques

Öffentlicher Verkehr - Referenzdatenmodell - Teil 8:
Managementinformationen und Statistiken

This European Standard was approved by CEN on 28 September 2026.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and United Kingdom.

get full document from standards.iteh.ai



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

© 2026 CEN All rights of exploitation in any form and by any means reserved
worldwide for CEN national Members.

Ref. No. EN 12896-8:2026 E

Contents

Page

European foreword	7
1 Scope.....	9
2 Normative references.....	9
3 Terms, definitions and abbreviations	9
3.1 Terms and definitions	9
3.2 Abbreviations.....	10
3.3 General information	11
4 Management Information and Statistics Domain.....	11
4.1 Introduction.....	11
4.2 Data Preparedness Levels.....	11
4.2.1 Preparedness level raw	13
4.2.2 Preparedness level cleansed	13
4.2.3 Preparedness level processed.....	14
4.3 Recording Service and Vehicle Performance Events	14
4.3.1 Introduction.....	14
4.3.2 Journey monitoring.....	15
4.3.3 Recorded Passing Times	16
4.3.4 Recorded Stops	16
4.3.5 Boarding and Alighting	16
4.3.6 Impeded Time	17
4.3.7 Status of Planned Interchanges	17
4.3.8 Disturbances.....	18
4.4 Statistical Concepts and Methods in OpRa.....	18
4.4.1 Introduction.....	18
4.4.2 Distribution analysis support	19
4.4.3 Distribution of duration type indicators	20
4.5 Conceptual data model	21
4.5.1 Introduction.....	21
4.5.2 Explicit Frames	23
4.5.3 Loggable Object Model	27
4.5.4 Logging Time and Place	29
4.5.5 Temporal and contextual structures	30
4.5.6 Indicators.....	34
4.5.7 Service dimensions	37
4.5.8 Fleet dimensions	39
4.5.9 Offered capacity.....	41
4.5.10 Measured number of passengers	44
4.5.11 Expected number of passengers.....	50
4.5.12 Service intensity.....	52
4.5.13 Delayed and early vehicle journeys	53
4.5.14 Cancelled vehicle journeys.....	57
4.5.15 Query Model.....	60
Annex A (normative) Data dictionary.....	65
A.1 Introduction.....	65

A.2	Data dictionary — Management information and statistics	69
A.2.1	Part 8 - Management Information & Statistics (MI)	69
A.2.2	Part 8 - Management Information & Statistics (MI)::EF Explicit Frame MODELS	69
A.2.3	Part 8 - Management Information & Statistics (MI)::EF Explicit Frame MODELS::AF Actual Frame MODEL	69
A.2.3.1	ACTUAL FRAME	69
A.2.4	Part 8 - Management Information & Statistics (MI)::EF Explicit Frame MODELS::CI Contextual Indicator Frame MODEL	70
A.2.4.1	CONTEXTUAL INDICATOR	70
A.2.4.2	CONTEXTUAL INDICATOR FRAME	70
A.2.4.3	CONTEXT KEYLIST	70
A.2.4.4	GENERIC CONTEXTUAL INDICATOR	71
A.2.5	Part 8 - Management Information & Statistics (MI)::EF Explicit Frame MODELS::PF Planned Frame MODEL	71
A.2.5.1	PLANNED FRAME	71
A.2.6	Part 8 - Management Information & Statistics (MI)::EF Explicit Frame MODELS::RF Indicator Frame MODEL	71
A.2.6.1	INDICATOR FRAME	71
A.2.6.2	PreparednessLevel	72
A.2.7	Part 8 - Management Information & Statistics (MI)::ID Indicator MODELS	72
A.2.7.1	INDICATOR	72
A.2.7.2	INDICATOR LOG ENTRY	72
A.2.8	Part 8 - Management Information & Statistics (MI)::ID Indicator MODELS::CJ Cancelled Dated Vehicle Journeys MODELS	73
A.2.8.1	CANCELLED DATED VEHICLE JOURNEY COUNT	73
A.2.8.2	CANCELLED DATED VEHICLE JOURNEY ENTRY	73
A.2.8.3	CANCELLED JOURNEY OCCURRENCE	74
A.2.9	Part 8 - Management Information & Statistics (MI)::ID Indicator MODELS::EX Expected Number of Passengers MODELS	74
A.2.9.1	EXPECTED PASSENGER COUNT	74
A.2.9.2	EXTERNAL PASSENGER COUNT	74
A.2.10	Part 8 - Management Information & Statistics (MI)::ID Indicator MODELS::FD Fleet Dimensions Indicators MODELS	75
A.2.10.1	ACTUAL FLEET DIMENSIONS	75
A.2.10.2	FLEET DIMENSIONS	75
A.2.10.3	PLANNED FLEET DIMENSIONS	75
A.2.11	Part 8 - Management Information & Statistics (MI)::ID Indicator MODELS::LJ Late Dated Vehicle Journeys MODELS	76
A.2.11.1	LATE DATED VEHICLE JOURNEY COUNT	76
A.2.11.2	LATE DATED VEHICLE JOURNEY ENTRY	76
A.2.11.3	LATE JOURNEY INTERVAL	77
A.2.11.4	LATE JOURNEY OCCURENCE CAUSE	77

EN 12896-8:2026 (E)

A.2.11.5	LATE JOURNEY OCCURRENCES	77
A.2.11.6	MEAN DELAY	78
A.2.12	Part 8 - Management Information & Statistics (MI)::ID Indicator MODELS::OC Offered Capacity MODELS.....	78
A.2.12.1	ACTUAL CAPACITY	78
A.2.12.2	OFFERED CAPACITY.....	78
A.2.12.3	CAPACITY SPECIFICATION ENUMERATION.....	78
A.2.12.4	PLANNED CAPACITY	79
A.2.12.5	Part 8 - Management Information & Statistics (MI)::ID Indicator MODELS::OC Offered Capacity MODELS::UC Use Cases	79
A.2.12.5.1	VEHICLE SEAT COUNT	79
A.2.13	Part 8 - Management Information & Statistics (MI)::ID Indicator MODELS::PX Measured Number of Passengers MODELS.....	79
A.2.13.1	AGGREGATED BOARDING AND ALIGHTING ENTRY	79
A.2.13.2	AGGREGATED ONBOARD DEVICE BASED PASSENGER COUNT	80
A.2.13.3	AGGREGATED TICKETING BASED PASSENGER COUNT	80
A.2.13.4	BOARDING AND ALIGHTING BASED PASSENGER COUNT	81
A.2.13.5	ONBOARD DEVICE BASED PASSENGER COUNT	81
A.2.13.6	TICKETING BASED PASSENGER COUNT	81
A.2.14	Part 8 - Management Information & Statistics (MI)::ID Indicator MODELS::SD Service Dimensions Indicator MODELS	82
A.2.14.1	ACTUAL SERVICE DIMENSIONS.....	82
A.2.14.2	PLANNED SERVICE DIMENSIONS.....	82
A.2.14.3	SERVICE DIMENSIONS	83
A.2.14.4	Part 8 - Management Information & Statistics (MI)::ID Indicator MODELS::SD Service Dimensions Indicator MODELS::UC Use Cases	84
A.2.15	Part 8 - Management Information & Statistics (MI)::ID Indicator MODELS::SI Service Intensity Indicators MODELS.....	84
A.2.15.1	ACTUAL SERVICE INTENSITY.....	84
A.2.15.2	AVERAGE COMMERCIAL SPEED	84
A.2.15.3	CAPACITY OVER DISTANCE	84
A.2.15.4	EXPECTED SERVICE INTENSITY.....	85
A.2.15.5	LOAD OVER JOURNEY DISTANCE	85
A.2.15.6	MEAN CAPACITY OVER JOURNEY DISTANCE	85
A.2.15.7	MEAN CAPACITY OVER NETWORK DISTANCE.....	86
A.2.15.8	MEAN CAPACITY OVER ROUTE DISTANCE.....	86
A.2.15.9	PLANNED SERVICE INTENSITY.....	86
A.2.15.10	SERVICE INTENSITY	87
A.2.15.11	TRANSPORT PERFORMANCE.....	87

A.2.15.12	TRANSPORT PERFORMANCE PER VEHICLE	87
A.2.16	Part 8 - Management Information & Statistics (MI)::RC Reusable Components MODELS	88
A.2.17	Part 8 - Management Information & Statistics (MI)::RC Reusable Components MODELS::DM Data Managed Object MODEL	88
A.2.17.1	DATA MANAGED OBJECT	88
A.2.17.2	KEY LIST.....	88
A.2.17.3	KEY VALUE.....	88
A.2.18	Part 8 - Management Information & Statistics (MI)::RC Reusable Components MODELS::FS Filtering Support MODELS	89
A.2.18.1	CALENDAR AWARE PT SCOPE.....	89
A.2.18.2	FLEET SCOPE.....	89
A.2.19	Part 8 - Management Information & Statistics (MI)::RC Reusable Components MODELS::GA Generic Aggregations MODELS.....	89
A.2.19.1	DURATION DISTRIBUTION	89
A.2.19.2	DURATION INTERVAL.....	90
A.2.19.3	OCCURRENCE	90
A.2.20	Part 8 - Management Information & Statistics (MI)::RC Reusable Components MODELS::RT Recorded Trip MODEL.....	91
A.2.20.1	RECORDED LEG	91
A.2.20.2	RECORDED TRIP	91
A.2.21	Part 8 - Management Information & Statistics (MI)::RC Reusable Components MODELS::LT Logging Time and Place MODEL.....	91
A.2.21.1	LOCATED EVENT	91
A.2.22	Part 8 - Management Information & Statistics (MI)::RC Reusable Components MODELS::RV Recorded Vehicle MODELS.....	92
A.2.22.1	RECORDED STOP	92
A.2.22.2	BOARDING AND ALIGHTING.....	92
A.2.22.3	INTERCHANGE STATUS	93
A.2.23	Part 8 - Management Information & Statistics (MI)::QM Query MODEL.....	93
A.2.23.1	OPRA FUNCTIONAL REQUEST	93
A.2.23.2	OPRA FUNCTIONAL DELIVERY	93
A.2.23.3	GROUPING INSTRUCTION.....	94
A.2.23.4	PARTICIPANT SYSTEM	94
A.2.23.5	AGGREGATE FUNCTION.....	94
A.2.23.6	AGGREGATION INSTRUCTIONS	95
Annex B (informative)	Data Model Evolutions.....	96
B.1	Introduction	96
B.2	Diagrams with additional concepts and relationships with other Parts.....	96
Table B.1	— List of diagrams with additional concepts and relationships to other Parts	96
B.3	Diagrams with additional relationships	100

EN 12896-8:2026 (E)

Annex C (informative) Significant technical changes between this document and the previous edition	102
Bibliography	103

Sample Document

get full document from standards.iteh.ai

European foreword

This document (EN 12896-8:2026) has been prepared by Technical Committee CEN/TC 278 “Intelligent transport systems”, the secretariat of which is held by NEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by March 2027, and conflicting national standards shall be withdrawn at the latest by March 2027.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 12896-8:2019.

Annex C provides details of the significant technical changes between this document and EN 12896-8:2019.

This document is part of the European standard series EN 12896, known as “Transmodel”. This is a series of documents that comprises the following parts:

- EN 12896-1, Public transport - Reference data model - Part 1: Common concepts
- EN 12896-2, Public transport - Reference data model - Part 2: Public transport network
- EN 12896-3, Public transport - Reference data model - Part 3: Timing information and vehicle scheduling
- EN 12896-4, Public transport - Reference data model - Part 4: Operations monitoring and control
- EN 12896-5, Public transport - Reference data model - Part 5: Fare management
- EN 12896-6, Public transport - Reference data model - Part 6: Passenger information
- EN 12896-7, Public transport - Reference data model - Part 7: Driver management
- EN 12896-8, Public transport - Reference data model - Part 8: Management information and statistics
- EN 12896-10, Public transport - Reference data model - Part 10: Alternative Modes

Together these documents create Transmodel version 6.2 and thus replace Transmodel V6.0.

In addition to the nine normative parts of this series, a Technical Report (Public Transport – Reference Data Model – Informative Documentation) was published in 2016 under the reference CEN/TR 12896-9. It provides additional information to help those implementing projects involving the use of Transmodel. It is intended that this Technical Report will be extended and republished as soon as all the normative parts are revised.

For information on the conventions, methodology, and notations for conceptual modelling and the core principles of Transmodel, refer to EN 12896-1.

Any feedback and questions on this document should be directed to the users’ national standards body. A complete listing of these bodies can be found on the CEN website.

EN 12896-8:2026 (E)

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.

Sample Document

get full document from standards.iteh.ai

1 Scope

The present document is composed of the following data packages:

- Indicators;
- Reusable components;
- Explicit frames for statistics
- Query.

This document itself is composed of the following parts:

- main document representing the conceptual foundations and corresponding data model (normative);
- Annex A containing the data dictionary and attribute tables, i.e. the list of all the concepts presented in the main document together with their definitions (normative);
- Annex B presenting the model evolution (informative);
- Annex C, providing details of the significant technical changes between this document and EN 12896-8:2019 (informative)

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 12896-1, *Public transport - Reference data model - Part 1: Common concepts*

3 Terms, definitions and abbreviations

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 12896-1 and the following apply.

3.1.1

aggregation frame

data structure within which the data values are grouped and used for a formula to provide an indicator

3.1.2

indicator

set of data (calculated or measured) which may be either qualitative or quantitative that is used to provide information on the status (may be a measure, a functional state, etc.) or the quality of a service or a function

3.1.3

indicator type

category of a given indicator, e.g. time, length, passenger count, price, vehicle, etc.

3.1.4

indicator unit

measurement unit (e.g. metres, seconds, passengers, etc.) in which a specific indicator is measured

EN 12896-8:2026 (E)**3.1.5****formula**

method to calculate indicators that are based on other indicators or on a set of raw data

3.1.6**granularity**

input for calculation processes representing the smallest unit(s) to generate output indicator(s)

3.1.7**O/D matrix**

tabular structure describing data by origin/destination parameters (e.g. daily traffic volume between zones)

3.1.8**indicator parameter type**

category of a given indicator parameter, e.g. time, length, passenger count, price, vehicle, etc.

3.1.9**indicator parameter unit**

measurement unit (e.g. meters, seconds, passengers, etc.) in which a specific indicator parameter is measured

3.2 Abbreviations

API	Application Programming Interface
AVM	Automatic Vehicle Monitoring
AVMS	Automatic Vehicle Monitoring System
GIS	Geographical Information System
GPS	Global Positioning System
HTTP	Hypertext Transfer Protocol
IFOPT	Identification of Fixed Objects in Public Transport
ISO	International Standards Organization
IT	Information Technology
NeTEx	Network and Timetable Exchange
PT	Public Transport
PTO	Public Transport Operator
OJP	Open API for Distributed Journey Planning
OpRa	Operating Raw Data and statistics exchange
SIRI	Service Interface for Real-time Information
TM	Transmodel
UML	Unified Modelling Language
URI	Uniform Resource Identifier
URL	Universal Resource Locator
VDV	Verband Deutscher Verkehrsunternehmen (Germany)

WGS World Geodetic Standard

3.3 General information

The following standards are based on the Transmodel conceptual data model for public transport domain to provide a harmonized, interoperable, and consistent approach for public transport data, service interfaces, and journey planning across Europe:

- EN 15531 (series) [10] to [16] – Service interfaces for real-time public transport operations.
- CEN/TS 16614 (series) (NeTEx) [17] to [22] – Network and timetable data exchange, including passenger information and accessibility.
- CEN/TS 17118 [23] – Open API for distributed journey planning.

4 Management Information and Statistics Domain

4.1 Introduction

Management information deals with functions analysing production data to evaluate the service quality or to take corrective measures in planning and managing operations. In public transport, for instance, the study of operational data (e.g. observed passing times, passenger load, delays and cancellations) collected during service operations is an input for strategic planning (e.g. how and when to amend the schedules), tactical planning (e.g. when to undertake a certain control action), quality follow-up, etc.

Management information uses therefore three main types of data:

- data resulting from the planning stages, i.e. theoretical data on the production orders (e.g. timetables, target passing times, driver rosters, etc.);
- data describing the daily actual production (e.g. observed passing times, actual number of passengers, number of late or cancelled journeys, etc.);
- data aggregations and calculated statistics (late journey duration intervals, number and percentage of late and cancelled journey occurrences)

Advances in technology for data capture, exchange, storage and analysis make it possible to make these data available in operational and management information systems for use by a broad range of stakeholders, such as PT operators, authorities, system suppliers, and analysts. Consistent data structures make it easier to define interoperable queries and data exchanges for specific tasks such as performance monitoring, service quality assessment, delay and cancellation analysis, capacity and passenger-demand evaluation, operational control, reporting to authorities, and service planning and optimisation.

4.2 Data Preparedness Levels

Many use cases in OpRa use data sources that can have various levels of reliability. Informing the consumer of a dataset about the reliability of the raw data and other indicators being exchanged an important block of metadata. For example, if an onboard data aggregator device, acting as a producer, states that the data has been fully processed and cleaned, the consumer side is not required to develop and maintain data cleansing functionality.

To be able to calculate the metrics transferred, using OpRa will require, depending on the data about a metric being transferred, access to the raw unprocessed data for both planned and unplanned service operations as well as processed clean data.

EN 12896-8:2026 (E)

For example, in the scenario where data is being exchanged between a PTO unit and a PTO server there are three stages of preparedness of the data:

- Raw;
- Cleansed;
- Processed.

To illustrate the differences between the preparedness states, the following table (Table 1) sums the roles of a producer and a consumer system, and lists some consequences which would trigger some architecture planning considerations in an OpRa-using environment.

Table 1 — Data preparedness Concepts

	Preparedness: Raw	Preparedness: Cleansed	Preparedness: Processed
Producer / Consumer roles	Producer states that the data contains the whole measurement, but it may contain erroneous data. It is up to the Consumer to get rid of measurement errors if needed	Producer states that erroneous data was removed from the measurement. Consumer may further investigate errors if required, but that's not mandatory	Producer states that validating the data had been finished and shall not be modified. Consumer can use the data without further examination of quality
Consequences	Consumer needs to develop data cleansing methods Consumer may not be aware of measurement characteristics (error probabilities) of Producer's equipment Consumer is responsible for calculating statistics	Producer can hide measurement equipment's characteristics (error probabilities) Producer has larger responsibilities depending on regulatory environment Quality of the Producer system might affect overall performance, since it filters out data Consumer software can be simpler, focusing more on higher-level tasks Consumer is responsible for calculating statistics	

A sample data flow diagram (Figure 1) shows how the level of preparedness may change as data moves between IT systems and organisations:




Figure 1 — Data preparedness stages for a PTO - PTA environment

4.2.1 Preparedness level raw

In the scenario where data is being exchanged between a PTO unit and PTO server data for the use case Number of cancelled journeys, the following data may be needed:

- Planned service;
- Requires actual service: control actions (PARTIAL / JOURNEY CANCELLATION);
- DATED VEHICLE JOURNEY reference;
- Cancellation type (PARTIAL / full);
- Control action metadata.

This data may contain partial or unchecked data which originates from a given person on duty at a given place.

No checking or processing of data has occurred. This data can be referred to as raw.

4.2.2 Preparedness level cleansed

Where data goes through some cross-checking before transferring, for example it may go through some integration process combining from multiple sources (e.g. workstations).

Where there is an obvious error, or the data value is outside of expected and or allowed values this data element may have been removed.

This data is the same as the raw data values except false data has been removed. This data can be referred to as cleansed.