



**SLOVENSKI STANDARD**  
**SIST EN 300 392-12-16 V1.4.1:2026**  
**01-september-2026**

---

**Prizemni snopovni radio (TETRA) - Govor in podatki (V+D) - 12. del: Dopolnilne storitve stopnje 3 - 16. poddel: Prednostni klic s predpravico (PPC)**

Terrestrial Trunked Radio (TETRA) - Voice plus Data (V+D) - Part 12: Supplementary services stage 3 - Sub-part 16: Pre-emptive Priority Call (PPC)

Sample Document

**Ta slovenski standard je istoveten z: ETSI EN 300 392-12-16 V1.4.1 (2026-07)**

get full document from [standards.iteh.ai](https://standards.iteh.ai)

**ICS:**

33.070.10	Prizemni snopovni radio (TETRA)	Terrestrial Trunked Radio (TETRA)
-----------	---------------------------------	-----------------------------------

**SIST EN 300 392-12-16 V1.4.1:2026**      **en**

2003-01.Slovenski inštitut za standardizacijo. Razmnoževanje celote ali delov tega standarda ni dovoljeno.

# Sample Document

get full document from [standards.iteh.ai](https://standards.iteh.ai)

# ETSI EN 300 392-12-16 V1.4.1 (2026-07)



EUROPEAN STANDARD

**Terrestrial Trunked Radio (TETRA);  
Voice plus Data (V+D);  
Part 12: Supplementary services stage 3;  
Sub-part 16: Pre-emptive Priority Call (PPC)**

get full document from [standards.iteh.ai](https://standards.iteh.ai)

---

**Reference**REN/TCCE-03278

---

**Keywords**data, radio, speech, stage 3,  
supplementary service, TETRA, V+D**ETSI**650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

---

**Important notice**

---

The present document can be downloaded from the  
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our [Coordinated Vulnerability Disclosure \(CVD\)](#) program.

---

**Notice of disclaimer & limitation of liability**

---

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.  
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

---

**Copyright Notification**

---

No part of this document may be reproduced in any form, by any means and in any media, without the prior written authorization of ETSI and except as expressly permitted below.

By way of exception and when the document is a normative deliverable (European Standard (EN), Technical Specification (TS), Group Specification (GS) or ETSI Standard (ES)), ETSI authorizes to reproduce and incorporate into products, services and technical documentation only those extracts (e.g. templates) that are strictly necessary for the technical implementation of the normative deliverable, to ensure compliance with the latter. Nothing in this notice shall be construed as limiting any mandatory exceptions to copyright provided by applicable law.

© ETSI 2026.  
All rights reserved.

# Contents

Intellectual Property Rights .....	6
Foreword.....	6
Modal verbs terminology.....	8
1 Scope .....	9
2 References .....	9
2.1 Normative references .....	9
2.2 Informative references.....	10
3 Definition of terms, symbols and abbreviations.....	10
3.1 Terms.....	10
3.2 Symbols.....	11
3.3 Abbreviations .....	11
4 SS-PPC service primitives.....	11
4.1 General .....	11
4.2 SS-PPC services offered over the TNSS-SAP.....	12
4.2.0 General.....	12
4.2.1 DEFINE request.....	12
4.2.2 DEFINE confirm .....	13
4.2.3 ASSIGN indication.....	13
4.2.4 ASSIGN response.....	13
4.2.5 INTERROGATE request.....	14
4.2.6 INTERROGATE confirm.....	14
4.2.7 REMOVE indication.....	14
4.2.8 REMOVE response.....	15
4.2.9 WITHDRAW request.....	15
4.2.10 WITHDRAW confirm.....	15
4.2.11 IMPENDING-PRE-EMPTION indication .....	15
4.2.12 USER-PRE-EMPTED indication .....	16
4.3 SS-PPC services offered over the TNCC-SAP.....	16
4.3.0 General.....	16
4.3.1 PRIORITY1 request - SS-PPC invocation.....	16
4.3.2 PRIORITY2 confirm/indication - SS-PPC operation .....	16
4.3.3 PRE-EMPTION .....	16
4.4 Parameter descriptions .....	16
5 SS-PPC protocol description .....	19
5.1 General .....	19
5.2 SS-PPC protocol states .....	19
5.2.0 General.....	19
5.2.1 Protocol states of FE1 .....	19
5.2.2 Protocol states of CCA to which FE1 is collocated .....	19
5.2.2.1 State IDLE.....	19
5.2.2.2 MO-CALL-SETUP.....	19
5.2.3 Protocol states of FE21 .....	20
5.2.3.0 General.....	20
5.2.3.1 State IDLE.....	20
5.2.4 Protocol states of CC to which FE21 is collocated.....	20
5.2.4.0 General .....	20
5.2.4.1 State ANY-STATE .....	20
5.2.4.2 State PARTIES-PRE-EMPTED.....	21
5.2.4.3 State SETUP-STARTED .....	21
5.2.5 Protocol states of FE3 .....	22
5.2.6 Protocol states of visited SwMI FE25.....	22
5.2.7 Protocol states of CC to which FE25 is collocated.....	22
5.2.7.0 General .....	22
5.2.7.1 State ANY-STATE .....	22

5.2.7.2	State PARTIES-PRE-EMPTED.....	23
5.2.7.3	State SETUP-STARTED .....	23
5.2.8	Protocol states of FE5 .....	23
5.2.9	Protocol states of CCA to which FE5 is collocated .....	24
5.2.9.1	ANY STATE.....	24
5.2.9.2	MT-CALL-SETUP .....	24
5.2.10	Protocol states of FE8 .....	24
5.2.11	Protocol states of CCA to which FE8 is collocated .....	25
5.3	SS-PPC signalling procedures.....	25
5.3.0	General.....	25
5.3.1	Procedures for FE1 .....	25
5.3.2	Procedures for FE21 .....	25
5.3.2.1	Definition in FE21 .....	25
5.3.2.2	Distribution in FE21 .....	25
5.3.2.3	Interrogation in FE21 .....	26
5.3.3	Procedures for CC to which FE21 is collocated .....	26
5.3.3.1	Verify priority in CC to which FE21 is collocated.....	26
5.3.4	Procedures for FE3 .....	27
5.3.4.1	Verification in FE3.....	27
5.3.5	Procedures for visited SwMI FE25.....	27
5.4	PDU descriptions.....	27
5.4.0	General.....	27
5.4.1	ASSIGN PDU .....	28
5.4.2	ASSIGN ACK PDU.....	28
5.4.3	DEFINE PDU .....	29
5.4.4	DEFINE ACK PDU.....	29
5.4.5	INTERROGATE PDU .....	29
5.4.6	INTERROGATE-ACK PDU.....	30
5.4.7	REMOVE PDU .....	30
5.4.8	REMOVE ACK PDU .....	30
5.4.9	WITHDRAW PDU.....	31
5.4.10	WITHDRAW ACK PDU .....	31
5.4.11	Pre-emption.....	31
5.4.11.1	D-RELEASE PDU .....	31
5.4.12	Priority 1 and Priority 2 .....	31
5.4.12.1	D-CONNECT PDU.....	31
5.4.12.2	D-SETUP PDU .....	31
5.4.12.3	U-SETUP PDU .....	32
5.4.13	IMPENDING-PRE-EMPTION PDU .....	32
5.4.14	USER-PRE-EMPTED PDU .....	32
5.5	Information element coding .....	32
5.5.0	General.....	32
5.5.1	Basic service(s).....	32
5.5.2	Number of pre-empted parties .....	33
5.5.3	Number of SS-PPC definitions .....	33
5.5.4	PPC PDU type .....	34
5.5.5	Pre-empted party.....	34
5.5.6	Range type .....	35
5.5.7	Result for definition .....	35
5.5.8	Result for interrogation .....	35
5.5.9	Result for withdrawal.....	36
5.5.10	SS-PPC assignment .....	36
5.5.11	SS-PPC definition.....	36
5.5.12	SS-PPC priority, Call priority and Non group member SS-PPC priority .....	37
5.5.13	Subscriber extension present.....	37
5.5.14	Subscriber identity .....	37
5.5.15	Time to pre-emption .....	38
6	SS-PPC FE behaviour .....	38
6.0	General .....	38
6.1	Behaviour of FE1 (SS entity of user A) .....	39
6.1.1	Service interaction for FE1 .....	39

6.1.2	Process description for FE1 .....	40
6.2	Behaviour of CCA to which FE1 is collocated .....	41
6.2.1	Service interaction for CCA to which FE1 is collocated .....	41
6.2.2	Process description for CCA to which FE1 is collocated .....	42
6.3	Behaviour of FE21 .....	43
6.3.1	Service interaction for FE21 .....	43
6.3.2	Process description for FE21 .....	44
6.4	Behaviour of CC to which FE21 is collocated .....	45
6.4.1	Service interaction for CC to which FE21 is collocated .....	45
6.4.2	Process description for CC to which FE21 is collocated .....	46
6.5	Behaviour of FE3 (SS entity of authorized user).....	49
6.5.1	Service interaction for FE3 .....	49
6.5.2	Process description for FE3 .....	50
6.6	Behaviour of visited SwMI FE25 .....	51
6.6.1	Service interaction for FE25 .....	51
6.6.2	Process description for visited SwMI FE25 .....	52
6.7	Behaviour of CC to which FE25 is collocated .....	53
6.8	Behaviour of FE5 .....	54
6.8.1	Service interaction for FE5 .....	54
6.8.2	Process description for FE5 .....	55
6.9	Behaviour of CCA to which FE5 is collocated .....	56
6.9.0	General.....	56
6.9.1	Service interaction for CCA to which FE5 is collocated .....	56
6.9.2	Process description for CCA collocated to FE5.....	57
6.10	Behaviour of FE8 .....	59
6.10.1	Service interaction for FE8 .....	59
6.10.2	Process description for FE8 .....	60
6.11	Behaviour of CCA to which FE8 is collocated .....	61
6.11.1	Service interaction for CCA to which FE8 is collocated .....	61
6.11.2	Process description for CCA collocated to FE8.....	62
6.12	Inter-working considerations.....	62
<b>Annex A (informative): Mapping of SS-PPC priorities received from the user application to priorities in basic service PDUs (for the MS) .....</b>		<b>63</b>
<b>Annex B (informative): Bibliography .....</b>		<b>64</b>
<b>Annex C (informative): Change requests .....</b>		<b>65</b>
History .....		66

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables (European Standard (EN), Technical Specification (TS), Group Specification (GS) or ETSI Standard (ES)) may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

## Foreword

This European Standard (EN) has been produced by ETSI Technical Committee TETRA and Critical Communications Evolution (TCCE).

### National transposition dates

Date of adoption of this EN:	3 July 2026
Date of latest announcement of this EN (doa):	31 October 2026
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 April 2027
Date of withdrawal of any conflicting National Standard (dow):	30 April 2027

The present document is part 12, sub-part 16 of a multi-part deliverable covering Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D), as identified below:

- Part 1: "General network design";
- Part 2: "Air Interface (AI)";
- Part 3: "Interworking at the Inter-System Interface (ISI)";
- Part 4: "Gateways basic operation";
- Part 5: "Peripheral Equipment Interface (PEI)";
- Part 7: "Security";

Part 9: "General requirements for supplementary services";

Part 10: "Supplementary services stage 1";

Part 11: "Supplementary services stage 2";

**Part 12: "Supplementary services stage 3";**

Sub-part 1: "Call Identification (CI)";

Sub-part 2: "Call Report (CR)";

Sub-part 3: "Talking Party Identification (TPI)";

Sub-part 4: "Call Forwarding (CF)";

Sub-part 5: "List Search Call (LSC)";

Sub-part 6: "Call Authorized by Dispatcher (CAD)";

Sub-part 7: "Short Number Addressing (SNA)";

Sub-part 8: "Area Selection (AS)";

Sub-part 9: "Access Priority (AP)";

Sub-part 10: "Priority Call (PC)";

Sub-part 11: "Call Waiting (CW)";

Sub-part 12: "Call Hold (HOLD)";

Sub-part 13: "Call Completion to Busy Subscriber (CCBS)";

Sub-part 14: "Late Entry (LE)";

**Sub-part 16: "Pre-emptive Priority Call (PPC)";**

Sub-part 17: "Include Call (IC)";

Sub-part 18: "Barring of Outgoing Calls (BOC)";

Sub-part 19: "Barring of Incoming Calls (BIC)";

Sub-part 20: "Discreet Listening (DL)";

Sub-part 21: "Ambience Listening (AL)";

Sub-part 22: "Dynamic Group Number Assignment (DGNA)";

Sub-part 23: "Call Completion on No Reply (CCNR)";

Sub-part 24: "Call Retention (CRT)";

Part 13: "SDL model of the Air Interface (AI)";

Part 14: "Protocol Implementation Conformance Statement (PICS) proforma specification";

Part 15: "TETRA frequency bands, duplex spacings and channel numbering";

Part 16: "Network Performance Metrics";

Part 17: "TETRA V+D and DMO specifications";

Part 18: "Air interface optimized applications";

Part 19: "Interworking between TETRA and Broadband systems".

NOTE 1: Part 3, sub-parts 6 and 7 (Speech format implementation), part 4, sub-part 3 (Data networks gateway), part 10, sub-part 15 (Transfer of control), part 13 (SDL) and part 14 (PICS) of this multi-part deliverable are in status "historical" and are not maintained.

NOTE 2: Some parts are also published as Technical Specifications such as ETSI TS 100 392-2 and those may be the latest version of the document.

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Sample Document

get full document from [standards.iteh.ai](https://standards.iteh.ai)

---

# 1 Scope

The present document defines the stage 3 specifications of the Supplementary Service Pre-emptive Priority Call (SS-PPC) for the Terrestrial Trunked Radio (TETRA).

SS-PPC enables a user to have preferential access to the network resources in a TETRA system in times of congestion including pre-emption of calls. SS-PPC is applicable for pre-emptive priorities including the emergency priority. SS-PPC includes the capability to pre-empt resources needed for higher priority calls and the capability to pre-empt users from ongoing calls in order to move them to higher priority calls. SS-PPC specifies the definition, activation, deactivation and interrogation for the usage of pre-emptive call priorities in the TETRA system. The Switching and Management Infrastructure (SwMI) applies the SS-PPC priorities when it allocates the resources for calls. The SS-PPC operations are defined for the SwMI and for the Mobile Station (MS).

SS-PPC is defined to subscribers of one TETRA system, but the subscribers may be located in several TETRA systems and the information flows may be delivered over the Inter System Interface (ISI). SS-PPC is invoked for calls within one TETRA system or for calls that extend over ISI to several TETRA systems.

Man-Machine Interface (MMI) and charging principles are outside the scope of the present document.

Supplementary Service stage 3 specification is preceded by the stage 1 and the stage 2 specifications of the service. Stage 1 describes the functional capabilities from the user's point of view. Stage 2 defines the functional behaviour in terms of Functional Entities (FEs) and information flows. Stage 3 gives a precise description of the supplementary service from the implementation point of view. It defines the protocol for the service and the encoding rules for the information flows. It defines the processes for the FEs and their behaviour. The described protocols and behaviour apply to the SwMI, for the MS and may be applied over the ISI between TETRA systems. Aspects relating to all supplementary services are detailed in ETSI EN 300 392-9 [3].

---

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found in the [ETSI docbox](#).

NOTE 1: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

NOTE 2: Note that for the TETRA standards, the reference is always to a European Standard (ETSI EN 300 xxx) if such has been published, but the latest version of that standard can be either an EN or a Technical Specification (ETSI TS 100 xxx), even if this is not visible in the reference list.

The following referenced documents are necessary for the application of the present document.

- [1] [ETSI EN 300 392-2](#): "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)".
- [2] [ETSI EN 300 392-1 \(V1.2.1\)](#): "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 1: General network design".
- [3] [ETSI EN 300 392-9](#): "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 9: General requirements for supplementary services".
- [4] [ETSI EN 300 392-3-1](#): "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 1: General design".
- [5] [Recommendation ITU-T Z.100](#): "Specification and Description Language - Overview of SDL-2010".

- [6] [ETSI EN 300 392-12-10](#): "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 12: Supplementary services stage 3; Sub-part 10: Priority Call (PC)".

## 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE 1: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

NOTE 2: Note that for the TETRA standards, the reference is always to a European Standard (ETSI EN 300 xxx) if such has been published, but the latest version of that standard can be either an EN or a Technical Specification (ETSI TS 100 xxx), even if this is not visible in the reference list.

The following referenced documents may be useful in implementing an ETSI deliverable or add to the reader's understanding, but are not required for conformance to the present document.

Not applicable.

---

## 3 Definition of terms, symbols and abbreviations

### 3.1 Terms

For the purposes of the present document, the following terms apply:

**authorized user:** user who is authorized to define, activate, deactivate and interrogate SS-PPC

**Call Control Agent (CCA):** Call Control sub-entity for Supplementary Service Pre-emptive Priority Call in Circuit Mode Control Entity in Mobile Station

**emergency priority:** highest pre-emptive priority level

**Functional Entity (FE):** functional characteristics of the SS sub-entity within an MS or a SwMI related to an SS-PPC action, e.g. definition or invocation

**SS-PPC call:** basic service (call) to which the defined SS-PPC priority is applied

**SS-PPC invocation:** sending of priority request to infrastructure

NOTE: The SS-PPC invocation is done with the basic service invocation request.

**SS-PPC operation:** usage of SS-PPC priority for and in a basic service set-up

**SS-PPC pre-emption:** exclusion of one or more parties from an ongoing basic service due an SS-PPC operation for another basic service

NOTE: The pre-emption may be done due to the lack of resources or due to the need to join a called party to a higher priority pre-emptive call.

**SS-PPC priority:** any pre-emptive priority invoked and operated for an SS-PPC call

**user A:** calling party, the party that invokes or generates invocation of SS-PPC

**user B:** called party in a call in which SS-PPC is operated

**user C:** pre-empted user, a user that is involved in a call, which is pre-empted due to lack of resources for a SS-PPC

NOTE: There may be one, two or more pre-empted users due to a pre-empted call.

**user D:** remaining user or users in a call from which a user or users have been pre-empted

**visited SwMI:** TETRA system of which the Mobile Network Identity (MNI) is not equal to the MNI of the user

## 3.2 Symbols

Void.

## 3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CC	Call Control sub-entity for SS-PPC in CMCE in SwMI
CCA	Call Control Agent
CMCE	Circuit Mode Control Entity
FE	Functional Entity
GTSI	Group TETRA Subscriber Identity
ISI	Inter System Interface
ITSI	Individual TETRA Subscriber Identity
LS	Line connected Station
MCC	Mobile Country Code
MNC	Mobile Network Code
MNI	Mobile Network Identity
MO	Mobile station Originating
MS	Mobile Station
MT	Mobile station Terminating
PDU	Protocol Data Unit
SS	Supplementary Service sub-entity within CMCE
SSI	Short Subscriber Identity
SS-PC	Supplementary Service Priority Call
SS-PPC	Supplementary Service Pre-emptive Priority Call
SwMI	Switching and Management Infrastructure
TETRA	TERrestrial TRunked RADio
TNCC-SAP	TETRA Network layer Call Control Service Access Point
TNSS-SAP	TETRA Network layer Supplementary Service Service Access Point
TSI	TETRA Subscriber Identity

---

## 4 SS-PPC service primitives

### 4.1 General

This clause describes the SS-PPC services offered by Supplementary Service (SS) and call control sub entities of CMCE of the TETRA voice plus data layer 3 service boundary in the MS. The SS-PPC services shall be offered at the Supplementary Service Service Access Point (TNSS-SAP) and the Call Control Service Access Point (TNCC-SAP). The SS-PPC services described in this clause shall be applicable for the MS.

**NOTE:** The SS-PPC services within the SwMI are outside the scope of the present document.

The SS-PPC services specified in the present document shall complement the Supplementary services and Call control services specified in ETSI EN 300 392-2 [1], clauses 12 and 11 respectively and the Supplementary Services general design standard ETSI EN 300 392-9 [3]. The SS-PPC services shall act as sub-services within the general supplementary services and call control services.

SS-PPC shall be an optional supplementary service for TETRA voice plus data layer 3. If SS-PPC is supported, this clause shall specify the services and their availability.

## 4.2 SS-PPC services offered over the TNSS-SAP

### 4.2.0 General

When the optional SS-PPC definition, user definition, activation, deactivation, interrogation, impending pre-emption indication and pre-empted party indication are supported, they shall be provided at TNSS-SAP.

NOTE: As the present document only deals with the SS-PPC all the service primitives have been shown without a TNSS-PPC-prefix e.g. the TNSS-PPC-ASSIGN request is shortened into an ASSIGN request.

The SS-PPC primitives for the user A (FE1) at the MS TNSS-SAP shall be:

- a) INTERROGATE request;
- b) INTERROGATE indication;
- c) ASSIGN indication;
- d) ASSIGN response.

The SS-PPC primitives for the authorized user (FE3) at the MS TNSS-SAP shall be:

- a) DEFINE request;
- b) DEFINE indication;
- c) INTERROGATE request;
- d) INTERROGATE indication.

The SS-PPC primitives for the pre-empted called user (FE5) at the MS TNSS-SAP shall be:

- a) IMPENDING-PRE-EMPTION indication.

The SS-PPC primitives for the pre-empted user (FE8) at the MS TNSS-SAP shall be:

- a) IMPENDING-PRE-EMPTION indication.

The SS-PPC primitives for the user (FE9) remaining in a call after pre-emption at the MS TNSS-SAP shall be:

- a) USER-PRE-EMPTED indication.

The activation and deactivation shall be done with the DEFINE request; the acknowledgement for activation and deactivation shall be done with DEFINE indication.

The information contained in the following primitive description tables correspond to the following key:

- Remark: comment;
- C: conditional;
- O: optional;
- M: mandatory.

### 4.2.1 DEFINE request

Optional DEFINE request primitive may be offered from the user application to FE3 over TNSS-SAP. The primitive shall contain the SS-PPC information parameters listed in table 1.

The subscriber identity parameter(s) shall indicate the subscriber identities on which the following definition shall be made.

**Table 1: DEFINE request contents**

Parameter	Request	Remark
Subscriber identity	M	Repeatable
Activated/deactivated	M	Note 1
Basic service	M	Repeatable
SS-PPC priority	M	Repeatable
Delivered to user A(s)	M	
Acknowledgement from user A(s)	C	Note 2
NOTE 1: Shall be used to indicate whether or not this PDU is used to activate a new PPC value or to deactivate an existing PPC value. When a PPC value is de-activated, a pre-programmed default value may then apply.		
NOTE 2: Conditional on the information element "Delivered to user A(s)".		

## 4.2.2 DEFINE confirm

If DEFINE request primitive is supported, then DEFINE confirm primitive shall be offered from FE3 to the user application over TNSS-SAP as an acknowledgement to a previously made definition request. The primitive shall contain the SS-PPC information parameters listed in table 2.

The Result for definition parameter shall indicate the result for all listed subscriber numbers and all basic service types.

NOTE 1: If the acknowledgements are different for different subscriber identities, FE3 may deliver several DEFINE confirm primitives to the user application.

NOTE 2: If the result for definition/activation/deactivation is "accepted, but some values changed by SwMI", the interrogation can be used to interrogate the values.

**Table 2: DEFINE confirm contents**

Parameter	Indication	Remark
Subscriber identity	M	Repeatable
Activated/deactivated	M	
Result for definition	M	

## 4.2.3 ASSIGN indication

Optional ASSIGN indication primitive may be offered from FE1 to the user application over TNSS-SAP. The primitive shall contain the SS-PPC information parameters listed in table 3.

FE1 shall only consider definitions made to a group number of which the subscriber is a member.

**Table 3: ASSIGN indication contents**

Parameter	Indication	Remark
Subscriber identity	M	
Activated/deactivated	M	
Basic service	M	Repeatable
SS-PPC priority	M	Repeatable
Acknowledgement from user A(s)	M	Note
NOTE: Parameter shall indicate if FE1 shall acknowledge the reception of the definition.		

## 4.2.4 ASSIGN response

If ASSIGN indication primitive is supported, then ASSIGN response primitive shall be offered from the user application to FE1 over TNSS-SAP as an acknowledgement to a previously received ASSIGN request, if acknowledgement was requested. The primitive shall contain the SS-PPC information parameters listed in table 4.