
Prizemni snopovni radio (TETRA) - Govor in podatki (V+D) - 12. del: Dopolnilne storitve stopnje 3 - 22. poddel: Dinamično dodeljevanje skupinskih števil (DGNA)

Terrestrial Trunked Radio (TETRA) - Voice plus Data (V+D) - Part 12: Supplementary services stage 3 - Sub-part 22: Dynamic Group Number Assignment (DGNA)

Sample Document

Ta slovenski standard je istoveten z: ETSI EN 300 392-12-22 V1.7.1 (2026-07)

ICS:

33.070.10	Prizemni snopovni radio (TETRA)	Terrestrial Trunked Radio (TETRA)
-----------	---------------------------------	-----------------------------------

SIST EN 300 392-12-22 V1.7.1:2026 **en**

Sample Document

get full document from standards.iteh.ai

ETSI EN 300 392-12-22 V1.7.1 (2026-07)



**Terrestrial Trunked Radio (TETRA);
Voice plus Data (V+D);
Part 12: Supplementary services stage 3;
Sub-part 22: Dynamic Group Number Assignment (DGNA)**

get full document from standards.iteh.ai

Reference

REN/TCCE-03280

Keywords

data, radio, speech, stage 3, supplementary
service, TETRA, V+D

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part of this document may be reproduced in any form, by any means and in any media, without the prior written authorization of ETSI and except as expressly permitted below.

By way of exception and when the document is a normative deliverable (European Standard (EN), Technical Specification (TS), Group Specification (GS) or ETSI Standard (ES)), ETSI authorizes to reproduce and incorporate into products, services and technical documentation only those extracts (e.g. templates) that are strictly necessary for the technical implementation of the normative deliverable, to ensure compliance with the latter. Nothing in this notice shall be construed as limiting any mandatory exceptions to copyright provided by applicable law.

© ETSI 2026.
All rights reserved.

Contents

Intellectual Property Rights	6
Foreword.....	6
Modal verbs terminology.....	8
1 Scope	9
2 References	9
2.1 Normative references	9
2.2 Informative references.....	10
3 Definition of terms, symbols and abbreviations.....	10
3.1 Terms.....	10
3.2 Symbols.....	10
3.3 Abbreviations	11
4 Functional model.....	11
4.1 Functional entities	11
4.2 Mapping of functional entities to Circuit Mode Control Entities (CMCEs).....	11
4.3 Protocol structure and protocol stack	12
5 SS-DGNA service description.....	12
5.1 General	12
5.2 SS-DGNA services offered over the TNSS-SAP	12
5.3 SS-DGNA primitives	13
5.3.0 Introduction.....	13
5.3.1 ASSIGN indication.....	14
5.3.2 ASSIGN response.....	14
5.3.3 DEASSIGN indication.....	14
5.3.4 DEASSIGN response.....	15
5.3.5 DEFINE indication	15
5.3.6 DEFINE request.....	16
5.3.7 DELETE indication	16
5.3.8 DELETE request.....	16
5.3.9 INTERROGATE GROUP request	17
5.3.10 INTERROGATE GROUP indication	17
5.3.11 INTERROGATE GROUP MEMBERS request	17
5.3.12 INTERROGATE GROUP MEMBERS indication.....	18
5.3.13 INTERROGATE MS GROUPS indication	18
5.3.14 INTERROGATE MS GROUPs response/confirm	18
5.3.15 INTERROGATE MS GROUPS request.....	19
5.3.16 MODIFY request	19
5.3.17 MODIFY indication.....	19
5.4 Primitive parameter descriptions.....	20
6 Signalling protocol for support of SS-DGNA	23
6.1 Operational requirements	23
6.1.1 Affected user MS	23
6.1.2 Group home SwMI	23
6.1.3 Home SwMI of the affected user	24
6.1.4 Affected user SwMI.....	24
6.1.5 Authorized user MS	24
6.1.6 Authorized user SwMI.....	24
6.2 PDU descriptions.....	24
6.2.1 General on PDU descriptions.....	24
6.2.2 ASSIGN.....	25
6.2.3 ASSIGN ACK	25
6.2.4 DEASSIGN.....	25
6.2.5 DEASSIGN ACK	26
6.2.6 DEFINE	26

6.2.7	DEFINE ACK.....	27
6.2.8	DELETE	27
6.2.9	DELETE ACK.....	28
6.2.10	INTERROGATE GROUP	28
6.2.11	INTERROGATE GROUP ACK.....	29
6.2.12	INTERROGATE GROUP MEMBERS.....	29
6.2.13	INTERROGATE GROUP MEMBERS ACK	30
6.2.14	INTERROGATE MS GROUPS	30
6.2.15	INTERROGATE MS GROUPS ACK.....	30
6.2.16	MODIFY	31
6.2.17	MODIFY ACK	32
6.2.18	General DGNA not supported	32
6.2.19	Requested SS-DGNA action not supported	33
6.3	Element coding.....	33
6.3.1	Acknowledgement complete.....	33
6.3.2	Acknowledgement requested from affected user(s).....	33
6.3.3	Additional group information	33
6.3.4	Affected user extension	33
6.3.5	Affected user identity.....	34
6.3.6	Affected user identity range type	34
6.3.7	Affected user SSI	34
6.3.8	Assigned user identity range type	34
6.3.9	Call identifier	34
6.3.10	Call related DGNA creation.....	35
6.3.11	Class of usage	35
6.3.12	Deassigned user identity range type.....	35
6.3.13	Group assignment	35
6.3.14	Group assignment ack.....	36
6.3.15	Group deassignment	36
6.3.16	Group deassignment ack.....	36
6.3.17	Group extension.....	36
6.3.18	Group extension present	37
6.3.19	Group identity attachment mode.....	37
6.3.20	Group information	37
6.3.21	Group SSI	38
6.3.22	Group status.....	38
6.3.23	Interrogation type for group.....	38
6.3.24	Interrogation type for group members	39
6.3.25	Interrogation type for MS groups	39
6.3.26	Length of additional group information element	39
6.3.27	Length of security related information element.....	40
6.3.27a	Maximum Number of interrogated MS groups.....	40
6.3.28	Mnemonic group name	40
6.3.29	Number of affected user identities	40
6.3.30	Number of groups	41
6.3.31	Number of groups in deassign ack.....	41
6.3.32	Number of groups in deassign request.....	41
6.3.32a	PDU sequence number.....	42
6.3.33	Result of assignment.....	42
6.3.34	Result of attachment	42
6.3.35	Result of deassignment	43
6.3.36	Result of definition	43
6.3.37	Result of deletion	44
6.3.38	Result of interrogation	44
6.3.39	Result of modification	45
6.3.40	Result of MS group interrogation	45
6.3.41	Security related information	45
6.3.42	Set reference	46
6.3.43	SS-DGNA PDU type	46
6.3.44	Visitor Group Short Subscriber Identity (V)GSSI	46
6.4	SS-DGNA protocol states	47
6.4.1	Protocol states of FE1	47

6.4.2	Protocol states of FE2	47
6.4.3	Protocol states of FE3	47
6.4.4	Protocol states of FE2 in visited SwMI	47
6.5	SS-DGNA signalling procedures	47
6.5.1	PDU addressing	47
6.5.2	Signalling procedures of FE1 (affected user).....	47
6.5.2.1	Assignment.....	47
6.5.2.2	Deassignment	48
6.5.2.3	Interrogation of group parameters.....	49
6.5.2.4	Interrogation of MS groups by SwMI	49
6.5.3	Signalling procedures of FE2 (SwMI).....	50
6.5.3.1	General on procedures for FE2	50
6.5.3.2	Definition	50
6.5.3.3	Deletion.....	51
6.5.3.4	Modification.....	51
6.5.3.5	Assignment.....	52
6.5.3.6	Deassignment	52
6.5.3.7	Interrogation of group information	52
6.5.3.8	Interrogation of group members.....	52
6.5.3.9	Interrogation of MS groups from affected user.....	53
6.5.3.10	Interrogation of MS groups request from authorized user	53
6.5.4	Signalling procedures of FE3 (authorized user).....	54
6.5.4.1	Definition	54
6.5.4.2	Modification.....	54
6.5.4.3	Deletion.....	55
6.5.4.4	Interrogation of group members.....	55
6.5.4.5	Interrogation of MS groups.....	55
6.5.4.6	Interrogation of group information	55
6.5.5	Signalling procedures of FE2 in a visited SwMI	55
6.6	Protocol timers	56
6.7	Inter-working considerations.....	56
6.7.1	Inter system interface.....	56
6.7.1.1	Basic requirements to ISI support	56
6.7.1.2	Assignment.....	56
6.7.1.3	Deassignment	56
6.7.1.4	Definition, deletion, modification	57
6.7.1.5	Interrogation.....	57
6.7.2	Gateways	57
Annex A (informative):	Bibliography.....	58
Annex B (informative):	Change requests	59
History		60

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables (European Standard (EN), Technical Specification (TS), Group Specification (GS) or ETSI Standard (ES)) may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee TETRA and Critical Communications Evolution (TCCE).

National transposition dates	
Date of adoption of this EN:	23 June 2026
Date of latest announcement of this EN (doa):	30 September 2026
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 March 2027
Date of withdrawal of any conflicting National Standard (dow):	31 March 2027

The present document is part 12, sub-part 22 of a multi-part deliverable covering Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D), as identified below:

- Part 1: "General network design";
- Part 2: "Air Interface (AI)";
- Part 3: "Interworking at the Inter-System Interface (ISI)";
- Part 4: "Gateways basic operation";
- Part 5: "Peripheral Equipment Interface (PEI)";
- Part 7: "Security";

Part 9: "General requirements for supplementary services";

Part 10: "Supplementary services stage 1";

Part 11: "Supplementary services stage 2";

Part 12: "Supplementary services stage 3";

Sub-part 1: "Call Identification (CI)";

Sub-part 2: "Call Report (CR)";

Sub-part 3: "Talking Party Identification (TPI)";

Sub-part 4: "Call Forwarding (CF)";

Sub-part 5: "List Search Call (LSC)";

Sub-part 6: "Call Authorized by Dispatcher (CAD)";

Sub-part 7: "Short Number Addressing (SNA)";

Sub-part 8: "Area Selection (AS)";

Sub-part 9: "Access Priority (AP)";

Sub-part 10: "Priority Call (PC)";

Sub-part 11: "Call Waiting (CW)";

Sub-part 12: "Call Hold (HOLD)";

Sub-part 13: "Call Completion to Busy Subscriber (CCBS)";

Sub-part 14: "Late Entry (LE)";

Sub-part 16: "Pre-emptive Priority Call (PPC)";

Sub-part 17: "Include Call (IC)";

Sub-part 18: "Barring of Outgoing Calls (BOC)";

Sub-part 19: "Barring of Incoming Calls (BIC)";

Sub-part 20: "Discreet Listening (DL)";

Sub-part 21: "Ambience Listening (AL)";

Sub-part 22: "Dynamic Group Number Assignment (DGNA)";

Sub-part 23: "Call Completion on No Reply (CCNR)";

Sub-part 24: "Call Retention (CRT)";

Part 13: "SDL model of the Air Interface (AI)";

Part 14: "Protocol Implementation Conformance Statement (PICS) proforma specification";

Part 15: "TETRA frequency bands, duplex spacings and channel numbering";

Part 16: "Network Performance Metrics";

Part 17: "TETRA V+D and DMO specifications";

Part 18: "Air interface optimized applications";

Part 19: "Interworking between TETRA and Broadband systems".

NOTE 1: Part 3, sub-parts 6 and 7 (Speech format implementation), part 4, sub-part 3 (Data networks gateway), part 10, sub-part 15 (Transfer of control), part 13 (SDL) and part 14 (PICS) of this multi-part deliverable are in status "historical" and are not maintained.

NOTE 2: Some parts are also published as Technical Specifications such as ETSI TS 100 392-2 and those may be the latest version of the document.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Sample Document

get full document from standards.iteh.ai

1 Scope

The present document defines the stage 3 specifications of the Supplementary Service Dynamic Group Number Assignment (SS-DGNA) for the Terrestrial Trunked Radio (TETRA).

The SS-DGNA enables a user to dynamically define group identities and group related parameters to the TETRA system and to the subscribers in the system. These definitions are used to enable group call invocations to dynamically defined groups. The SS-DGNA specification defines the creation, modification, deletion and interrogation of group definitions in the Switching and Management Infrastructure (SwMI), in the Mobile Station (MS).

The present document does not include the specification for access priority used for random access in uplink and call priority used by SwMI for resource allocation in a group call. Access priority and call priority can be specified and applied for groups using Supplementary Services Access Priority (SS-AP), Priority Call (SS-PC) and Pre-emptive Priority Call (SS-PPC). Thus, the definition procedure of these priorities is outside the scope of the present document.

Man Machine Interface (MMI) and charging principles are also outside the scope of the present document.

Supplementary service stage 3 specification is preceded by the stage 1 and the stage 2 specifications of the service. Stage 1 describes the functional capabilities from the user's point of view. Stage 2 defines the functional behaviour in terms of functional entities and information flows. Stage 3 gives the precise description of the supplementary service from the implementation point of view. It defines the protocols for the service and the encoding rules for the information flows. It defines the processes for the functional entities and their behaviour. The described protocols and their behaviour apply for the SwMI and for the MS and can be applied over the Inter-System Interface (ISI) between TETRA systems.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found in the [ETSI docbox](#).

NOTE 1: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

NOTE 2: Note that for the TETRA standards, the reference is always to a European Standard (ETSI EN 300 xxx) if such has been published, but the latest version of that standard can be either an EN or a Technical Specification (ETSI TS 100 xxx), even if this is not visible in the reference list.

The following referenced documents are necessary for the application of the present document.

- [1] [ISO/IEC 8859-1](#): "Information technology -- 8-bit single-byte coded graphic character sets -- Part 1: Latin alphabet No. 1".
- [2] [ETSI ETS 300 392-11-22](#): "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 11: Supplementary services stage 2; Sub-part 22: Dynamic Group Number Assignment (DGNA)".
- [3] [ETSI EN 300 392-2](#): "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)".
- [4] [ETSI EN 300 392-1](#): "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 1: General network design".
- [5] [ETSI EN 300 392-7](#): "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 7: Security".

- [6] [ETSI EN 300 392-9](#): "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 9: General requirements for supplementary services".
- [7] [ETSI EN 300 392-3-5](#): "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 5: Additional Network Feature for Mobility Management (ANF-ISIMM)".
- [8] [ETSI EN 300 392-3-3](#): "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 3: Additional Network Feature Group Call (ANF-ISIGC)".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE 1: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

NOTE 2: Note that for the TETRA standards, the reference is always to a European Standard (ETSI EN 300 xxx) if such has been published, but the latest version of that standard can be either an EN or a Technical Specification (ETSI TS 100 xxx), even if this is not visible in the reference list.

The following referenced documents may be useful in implementing an ETSI deliverable or add to the reader's understanding, but are not required for conformance to the present document.

Not applicable.

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the following terms apply:

affected user: identified MS user to whom the group is assigned (added to) or deassigned (removed from)

NOTE: Affected user can also interrogate group information based on group numbers. Also SwMI can interrogate group information from affected user.

authorized user: user who is able to define, modify and delete a group and interrogate group information based on group numbers/affected user identities

call related SS-DGNA: creation of a group whose members (affected users) are based on the participants of a referenced call and possibly also based on given affected user identities

call unrelated SS-DGNA: creation of a group whose members (affected users) are solely based on given affected user identities

3.2 Symbols

Void.

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

(V)GSSI Visiting Short Subscriber Group Identity or Visitor GSSI

(V)GTSI	Visiting TETRA Subscriber Group Identity or Visitor GTSI
ACK	ACKnowledgement
CC	Call Control
CMCE	Circuit Mode Control Entity
DGNA	Dynamic Group Number Assignment
DMO	Direct Mode Operation
FE	Functional Entities
GCK	Group Cipher Key
GSSI	Group Short Subscriber Identity
GTSI	Group TETRA Subscriber Identity
ISI	Inter-System Interface
ITSI	Individual TETRA Subscriber Identity
MLE	Mobile Link Entity
MMI	Man Machine Interface
MNI	Mobile Network Identity
MS	Mobile Station
PC	Protocol Control
PDU	Protocol Data Unit
PICS	Protocol Implementation Conformance Statement
SDL	Specification and Description Language
SS	Supplementary Services
SS-AP	Access Priority
SS-DGNA	Dynamic Group Number Assignment
SSI	Short Subscriber Identity
SS-PC	Priority Call
SS-PDU	Protocol Data Unit
SS-PPC	Pre-emptive Priority Call

NOTE: The abbreviation SS is only used when referring to a specific supplementary service.

SwMI	Switching and Management Infrastructure
TNSS-SAP	Supplementary Services Service Access Point
TSI	TETRA Subscriber Identity

4 Functional model

4.1 Functional entities

The functional model for SS-DGNA consists of Functional Entities FE1 to FE3 as defined in ETSI ETS 300 392-11-22 [2], clause 4.1. Refer to ETSI EN 300 392-9 [6] for Inter-System Interface model (ISI).

These functional entities can, for one action, be located in different TETRA SwMIs as defined in ETSI ETS 300 392-11-22 [2], clause 4.

4.2 Mapping of functional entities to Circuit Mode Control Entities (CMCEs)

FEs, CCs and PCs correspond to sub-entities in the Circuit Mode Control Entity (CMCE) described in ETSI EN 300 392-2-2 [3] according to the following definitions:

- FE1: Supplementary Service (SS) sub-entity in CMCE in affected user's MS.
- FE2: SS sub-entity in CMCE in SwMI.
- FE3: SS sub-entity in CMCE in authorized user's MS.
- CC: Call Control (CC) sub-entity in CMCE in SwMI or in MS.
- PC: Protocol Control (PC) sub-entity in CMCE in MS.

4.3 Protocol structure and protocol stack

The MS protocol stack is defined in ETSI EN 300 392-2 [3].

SS-DGNA PDUs shall be routed as specified in ETSI EN 300 392-9 [6], at the air interface in U/D-FACILITY PDUs and using ANF-ISISS for conveying SS-DGNA PDUs over the ISI.

5 SS-DGNA service description

5.1 General

Clauses 5.2 to 5.4 describe SS-DGNA specific services offered by the CMCE at the Supplementary Services Service Access Point (TNSS-SAP) to application, or vice versa, of the TETRA Voice plus Data (V+D) layer 3 service boundary.

NOTE: As the present document only deals with the SS-DGNA all the service primitives has been shown without a TNSS-DGNA-prefix e.g. the TNSS-DGNA-DEFINE request is shortened into a DEFINE request.

Refer to ETSI EN 300 392-9 [6] for general information on supplementary services.

In this protocol model the application is considered to manage group information in the MS. The management mechanisms and a detailed information exchange between MS protocol layers are outside the scope of the present document.

5.2 SS-DGNA services offered over the TNSS-SAP

The services offered to users of SS-DGNA are defined as service primitives containing service parameters. The service primitives are defined in clause 5.3 and the parameter in the service primitives are defined in clause 5.4.

In addition to the defined service primitives a SwMI/MS may response by a supplementary service not supported or an action not supported primitives as appropriate, refer ETSI EN 300 392-9 [6] and clauses 6.2.18 and 6.2.19 of the present document.

NOTE: As the Man Machine Interface or user application are outside the scope of the present document service primitives are used to define information exchange to and from the standardized part of the MS. Those primitives may be only indirectly accessible.

5.3 SS-DGNA primitives

5.3.0 Introduction

This clause lists the SS-DGNA primitives, which are then described in the following clauses.

The SS-DGNA service primitives at the Affected user MS (FE1) TNSS-SAP are:

- a) ASSIGN indication.
- b) ASSIGN response.
- c) DEASSIGN indication.
- d) DEASSIGN response.
- e) INTERROGATE GROUP request.
- f) INTERROGATE GROUP indication.
- g) INTERROGATE MS GROUPS indication.

- h) INTERROGATE MS GROUPS response.

The SS-DGNA service primitives at the authorized user MS (FE3) TNSS-SAP are:

- a) DEFINE request.
- b) DEFINE indication.
- c) DELETE request.
- d) DELETE indication.
- e) INTERROGATE GROUP request;
- f) INTERROGATE GROUP indication.
- g) INTERROGATE GROUP MEMBERS request.
- h) INTERROGATE GROUP MEMBERS indication.
- i) MODIFY request.
- j) MODIFY indication.
- k) INTERROGATE MS GROUPS request.
- l) INTERROGATE MS GROUPS confirm.

The service primitives such as MODIFY request and MODIFY indication are related to each other by the group identity, if available. There can be more than one indication primitive related to a single request primitive.

5.3.1 ASSIGN indication

ASSIGN indication primitive shall be offered from FE1 to application over TNSS-SAP in order to assign group identities and/or parameters related to the group to the database in the affected user's MS. The primitive shall contain the SS-DGNA parameters listed in table 1.

Table 1: ASSIGN indication contents

Parameter	Indication	Remark
Group identity/identities	M	
Acknowledgement requested	M	
Group identity attachment mode	O	
Class of usage	O	
Mnemonic group name	O	
Security related information	O	
Additional group information	O	

5.3.2 ASSIGN response

ASSIGN response primitive shall be offered from application to FE1 over TNSS-SAP. The primitive shall be used to acknowledge one or more group assignments made to affected user. The primitive shall contain the SS-DGNA parameters listed in table 2. The primitive shall be used only, if the acknowledgement was requested in an ASSIGN request.