
Digitalne izboljšane brezvrvične telekomunikacije (DECT) - Harmonizirani standard za dostop do radijskega spektra - 1. del: DECT, razvoj DECT in DECT ULE

Digital Enhanced Cordless Telecommunications (DECT) - Harmonised Standard for access to radio spectrum - Part 1: DECT, DECT Evolution and DECT ULE

Sample Document

Ta slovenski standard je istoveten z: ETSI EN 301 406-1 V3.2.1 (2026-08)

ICS:

33.070.30	Digitalne izboljšane brezvrvične telekomunikacije (DECT)	Digital Enhanced Cordless Telecommunications (DECT)
-----------	--	--

SIST EN 301 406-1 V3.2.1:2026**en**

Sample Document

get full document from standards.iteh.ai

ETSI EN 301 406-1 V3.2.1 (2026-08)



**Digital Enhanced Cordless Telecommunications (DECT);
Harmonised Standard for access to radio spectrum;
Part 1: DECT, DECT Evolution and DECT ULE**

get full document from standards.iteh.ai

ReferenceREN/DECT-00411

KeywordsDECT, digital, generic, radio, regulation, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part of this document may be reproduced in any form, by any means and in any media, without the prior written authorization of ETSI and except as expressly permitted below.

By way of exception and when the document is a normative deliverable (European Standard (EN), Technical Specification (TS), Group Specification (GS) or ETSI Standard (ES)), ETSI authorizes to reproduce and incorporate into products, services and technical documentation only those extracts (e.g. templates) that are strictly necessary for the technical implementation of the normative deliverable, to ensure compliance with the latter. Nothing in this notice shall be construed as limiting any mandatory exceptions to copyright provided by applicable law.

© ETSI 2026.
All rights reserved.

Contents

Intellectual Property Rights	11
Foreword.....	11
Modal verbs terminology.....	12
1 Scope	13
2 References	13
2.1 Normative references	13
2.2 Informative references.....	14
3 Definition of terms, symbols and abbreviations.....	15
3.1 Terms.....	15
3.2 Symbols.....	18
3.3 Abbreviations	18
4 Technical requirements specifications	20
4.1 Environmental profile.....	20
4.2 Overview	20
4.2.0 General.....	20
4.2.1 Test suites	20
4.2.2 Test groups.....	20
4.2.3 Test cases	20
4.3 Product information for testing	21
4.3.1 Information on capabilities and options implemented	21
4.3.2 Additional information on implementation for testing	21
4.4 Applicability of tests	22
4.4.0 Introduction.....	22
4.4.1 Equipment that includes only a DECT RF receiver.....	22
4.4.2 Equipment that includes a radio transmitter	22
4.4.3 Void	22
4.4.4 Equipment with combined FT and PT functionality.....	22
4.4.4.0 General	22
4.4.4.1 Wireless Relay Station	22
4.4.4.2 Direct PP to PP communication	23
4.4.4.3 Distributed Communications.....	23
4.4.5 Equipment that is capable of using higher level modulation	23
4.5 Conformance requirements	23
4.5.1 Accuracy and stability of RF carriers	23
4.5.1.1 Designation of RF carriers	23
4.5.1.2 Limits	24
4.5.1.3 Conformance.....	24
4.5.2 Accuracy and stability of timing parameters	24
4.5.2.0 General	24
4.5.2.1 Definitions.....	24
4.5.2.1.1 Slot structure.....	24
4.5.2.1.2 Definition of the position of p0	24
4.5.2.1.3 Definition of reference timer	24
4.5.2.2 Limits	25
4.5.2.2.1 Reference timer accuracy and stability.....	25
4.5.2.2.2 RFP transmission jitter	25
4.5.2.2.3 PP reference timer synchronization.....	25
4.5.2.3 Conformance.....	25
4.5.3 Transmission burst.....	26
4.5.3.1 Definitions.....	26
4.5.3.1.0 Introduction	26
4.5.3.1.1 Physical packets.....	26
4.5.3.1.2 Transmitted power.....	26
4.5.3.1.3 Normal Transmitted Power (NTP)	26

4.5.3.1.4	Transmitter attack time.....	27
4.5.3.1.5	Transmitter release time	27
4.5.3.1.6	Minimum power	27
4.5.3.1.7	Maximum power	27
4.5.3.1.8	Maintenance of transmission after packet end.....	27
4.5.3.1.9	Transmitter idle power output	27
4.5.3.2	Limits	27
4.5.3.2.1	Transmitter attack time.....	27
4.5.3.2.2	Transmitter release time	27
4.5.3.2.3	Minimum power	27
4.5.3.2.4	Maximum power	27
4.5.3.2.5	Maintenance of transmission after packet end.....	28
4.5.3.2.6	Transmitter idle power output	28
4.5.3.3	Conformance.....	28
4.5.4	Transmitted power	28
4.5.4.1	Definitions.....	28
4.5.4.1.0	Transceiver and P_{NTP} definitions.....	28
4.5.4.2	Limits	29
4.5.4.2.0	P_{NTP} Limit	29
4.5.4.2.1	PP and RFP with an integral antenna	29
4.5.4.2.2	PP and RFP with external connections for all antennas	29
4.5.4.2.3	PP and RFP with both integral and external antennas	29
4.5.4.3	Conformance.....	29
4.5.4.4	Multi-transceiver systems	29
4.5.5	RF carrier modulation	29
4.5.5.1	Definition	29
4.5.5.1.1	GFSK modulation.....	29
4.5.5.1.2	Non-constant envelope modulation	30
4.5.5.2	Limit.....	30
4.5.5.2.1	GFSK modulation.....	30
4.5.5.2.2	Non-constant envelope modulation	30
4.5.5.3	Conformance.....	31
4.5.6	Unwanted RF power radiation	31
4.5.6.1	General	31
4.5.6.2	Emissions due to modulation	31
4.5.6.2.1	Definition.....	31
4.5.6.2.2	Limits	31
4.5.6.2.3	Conformance	31
4.5.6.3	Emissions due to transmitter transients	31
4.5.6.3.1	Definition.....	31
4.5.6.3.2	Limits	31
4.5.6.3.3	Conformance	32
4.5.6.4	Emissions due to intermodulation	32
4.5.6.4.1	Definition.....	32
4.5.6.4.2	Limits	32
4.5.6.4.3	Conformance	32
4.5.6.5	Spurious emissions when allocated a transmit channel.....	32
4.5.6.5.1	Definition.....	32
4.5.6.5.2	Limits	32
4.5.6.5.3	Conformance	33
4.5.7	Radio receiver requirements	33
4.5.7.1	Radio receiver sensitivity	33
4.5.7.1.1	Definition.....	33
4.5.7.1.2	Limits	33
4.5.7.1.3	Conformance	33
4.5.7.2	Radio receiver reference BER and FER.....	33
4.5.7.2.1	Definition.....	33
4.5.7.2.2	Limits	33
4.5.7.2.3	Conformance	34
4.5.7.3	Radio receiver interference performance	34
4.5.7.3.1	Definition.....	34

4.5.7.3.2	Limits	34
4.5.7.3.3	Conformance	34
4.5.7.4	Radio receiver blocking case 1: owing to signals occurring at the same time but on other frequencies	34
4.5.7.4.1	Definition.....	34
4.5.7.4.2	Limits	34
4.5.7.4.3	Conformance	35
4.5.7.5	Radio receiver blocking case 2: owing to signals occurring at a different time.....	35
4.5.7.5.1	Definition.....	35
4.5.7.5.2	Limits	35
4.5.7.5.3	Conformance	35
4.5.7.6	Receiver intermodulation performance	35
4.5.7.6.1	Definition.....	35
4.5.7.6.2	Limits	35
4.5.7.6.3	Conformance	35
4.5.7.7	Spurious emissions when the PP has no allocated transmit channel	35
4.5.7.7.1	Definition.....	35
4.5.7.7.2	Limits	35
4.5.7.7.3	Conformance	36
4.5.8	Channel access.....	36
4.5.8.1	Channel selection	36
4.5.8.2	Channel confirmation.....	36
4.5.8.2.1	For the PT	36
4.5.8.2.2	For the FT	36
4.5.8.3	Channel release	37
4.5.8.4	General	37
4.5.8.5	Channel selection and confirmation for DECT ULE	37
4.5.8.5.1	General	37
4.5.8.5.2	For the PT	37
4.5.8.5.3	For the FT	37
4.5.9	WRS.....	37
4.5.9.0	General requirements	37
4.5.9.1	PP operation	38
4.5.9.2	RFP operation	38
4.5.9.3	Additional requirements.....	38
4.5.9.4	Conformance.....	39
4.5.10	Direct PP to PP communication.....	39
4.5.10.1	General requirements	39
4.5.10.2	Conformance.....	39
4.5.11	Distributed communications	39
4.5.11.0	General requirements	39
4.5.11.1	PP operation	39
4.5.11.2	RFP operation	39
4.5.11.3	Conformance.....	40
4.5.12	Higher level modulation options.....	40
4.5.12.0	Requirements	40
4.5.12.1	Conformance.....	40
5	Testing for compliance with technical requirements.....	41
5.0	Environmental conditions for testing	41
5.1	General test requirements	41
5.1.1	Test philosophy.....	41
5.1.1.1	General	41
5.1.1.2	Lower Tester (LT).....	41
5.1.1.3	Non-signalling test mode	42
5.1.1.4	Test environment.....	43
5.1.1.4.1	General	43
5.1.1.4.2	Conducted test	43
5.1.1.4.3	Radiated test	43
5.1.2	Test site.....	43
5.1.2.1	Open air test site.....	43
5.1.2.1.1	Description	43

5.1.2.2	Anechoic chamber.....	44
5.1.2.2.1	General	44
5.1.3	Standard position	44
5.1.4	Test antenna of the LT.....	44
5.1.5	Substitution antenna.....	44
5.1.6	Test fixture.....	45
5.1.7	Equipment with a temporary or internal permanent antenna connector.....	45
5.1.7.1	General	45
5.1.7.2	Equipment with a temporary antenna connector.....	45
5.1.8	Void	45
5.1.9	Lower Tester (LT)	45
5.1.9.1	Description	45
5.1.9.2	Connections between the EUT and the LT	46
5.1.9.3	Functions and abilities.....	46
5.1.9.4	Signal generation uncertainty.....	47
5.1.9.5	Modulated DECT-like carrier	47
5.1.9.6	CW interferers.....	47
5.1.9.7	DECT RF signal.....	47
5.1.9.8	Test modulation signals.....	47
5.1.10	Upper Tester (UT)	47
5.1.10.1	Description of the UT.....	47
5.1.10.2	The Test Standby Mode (TSM)	48
5.1.10.3	Test messages.....	48
5.1.10.4	Dummy setting when EUT is an RFP and is in Test Standby Mode (TSM).....	48
5.1.11	Description of the lower tester FT and PT	48
5.1.12	General test methods.....	49
5.1.12.1	General	49
5.1.12.2	Sampling the RF signal	49
5.1.12.2.1	Introduction	49
5.1.12.2.2	Sampling method.....	49
5.1.12.3	Determining the reference position	49
5.1.12.3.0	General	49
5.1.12.3.1	Case 1: EUTs that cannot transmit	49
5.1.12.3.2	Case 2: EUTs that can transmit	49
5.1.12.4	Bit Error Ratio (BER) and Frame Error Ratio (FER) measurements.....	49
5.1.13	Test setup	50
5.1.13.1	General	50
5.1.13.2	Test setup 1	50
5.1.13.3	Test setup 2	50
5.1.13.4	Test setup 3	51
5.1.13.5	Test setup 4	51
5.1.14	Test arrangements for intermodulation measurements	52
5.1.14.1	PT to PT arrangement	52
5.1.14.2	FT to FT arrangement	52
5.1.14.3	FT to PT arrangement	53
5.1.15	Test conditions, power supply and ambient temperatures	53
5.1.15.1	General	53
5.1.15.2	Nominal test conditions.....	53
5.1.15.3	Extreme test conditions	54
5.1.15.4	Test power source - general requirements.....	55
5.1.15.5	Nominal test power source.....	55
5.1.15.5.1	Mains voltage	55
5.1.15.5.2	Regulated lead acid battery power sources.....	55
5.1.15.5.3	Nickel cadmium or nickel metal hydride battery.....	55
5.1.15.5.4	Other power sources	55
5.1.15.6	Extreme test power source	55
5.1.15.6.1	Mains voltage	55
5.1.15.6.2	Regulated lead acid battery power sources.....	55
5.1.15.6.3	Nickel cadmium or nickel metal hydride battery.....	55
5.1.15.6.4	Other power sources	56
5.2	Interpretation of the measurement results	56
5.3	Radio test suites.....	56

5.3.1	Accuracy and stability of RF carriers	56
5.3.1.1	Test environment.....	56
5.3.1.2	Method of measurement.....	56
5.3.1.3	Verdict criteria when the EUT is an RFP	57
5.3.1.4	Verdict criteria when the EUT is a PP	57
5.3.2	Accuracy and stability of timing parameters	57
5.3.2.1	Measurement of packet timing jitter	57
5.3.2.1.1	Test environment.....	57
5.3.2.1.2	Method of measurement	57
5.3.2.1.3	Verdict criteria.....	58
5.3.2.2	Measurement of the reference timing accuracy of an RFP	58
5.3.2.2.1	Test environment.....	58
5.3.2.2.2	Method of measurement	58
5.3.2.2.3	Verdict criteria.....	58
5.3.2.3	Measurement of packet transmission accuracy of a PP.....	59
5.3.2.3.1	Test environment.....	59
5.3.2.3.2	Method of measurement	59
5.3.2.3.3	Verdict criteria.....	59
5.3.3	Transmission burst.....	60
5.3.3.1	Test environment.....	60
5.3.3.2	Method of measurement.....	60
5.3.3.3	Verdict criteria	60
5.3.4	Transmitted power	61
5.3.4.1	PP and RFP with an integral antenna	61
5.3.4.1.1	Test environment.....	61
5.3.4.1.2	Method of measurement	61
5.3.4.1.3	Verdict criteria for all EUTs.....	62
5.3.4.2	PP and RFP with external antenna connection(s).....	62
5.3.4.2.1	Test environment.....	62
5.3.4.2.2	Method of measurement	63
5.3.4.2.3	Verdict criteria for all EUTs.....	63
5.3.5	RF carrier modulation.....	63
5.3.5.1	Test environment.....	63
5.3.5.2	Method of measurement, GFSK parts 1 and 2	63
5.3.5.2.1	Introduction	63
5.3.5.2.2	Part 1	64
5.3.5.2.3	Part 2	64
5.3.5.3	Method of measurement, GFSK parts 3 and 4	64
5.3.5.3.0	General	64
5.3.5.3.1	Part 3	65
5.3.5.3.2	Part 4	65
5.3.5.4	Verdict criteria for GFSK part 1	65
5.3.5.5	Verdict criteria for GFSK part 2	65
5.3.5.6	Verdict criteria for GFSK part 3	65
5.3.5.7	Verdict criteria for GFSK part 4	66
5.3.5.8	Method of measurement for non-constant envelope modulation	67
5.3.5.9	Verdict criteria for non-constant envelope modulation.....	67
5.3.6	Unwanted RF power radiation.....	67
5.3.6.1	General test conditions	67
5.3.6.2	Emissions due to modulation	67
5.3.6.2.1	Test environment.....	67
5.3.6.2.2	Method of measurement	67
5.3.6.2.3	Verdict criteria.....	68
5.3.6.3	Emissions due to transmitter transients.....	68
5.3.6.3.1	Test environment.....	68
5.3.6.3.2	Method of measurement	69
5.3.6.3.3	Verdict criteria.....	69
5.3.6.4	Emissions due to intermodulation	69
5.3.6.4.1	Test environment.....	69
5.3.6.4.2	Method of measurement	70
5.3.6.4.3	Verdict criteria.....	70
5.3.6.5	Spurious emissions when allocated a transmit channel.....	71

5.3.6.5.1	Radiated emissions	71
5.3.6.5.2	Conducted spurious emissions when the EUT has a permanent external antenna connector	72
5.3.7	Radio receiver testing	72
5.3.7.0	General	72
5.3.7.1	Radio receiver sensitivity	72
5.3.7.1.1	Test environment	72
5.3.7.1.2	Method of measurement	72
5.3.7.1.3	Verdict criteria	73
5.3.7.2	Radio receiver reference BER and FER	73
5.3.7.2.1	Test environment	73
5.3.7.2.2	Method of measurement	73
5.3.7.2.3	Verdict criteria	73
5.3.7.3	Radio receiver interference performance	73
5.3.7.3.1	Test environment	73
5.3.7.3.2	Method of measurement	73
5.3.7.3.3	Verdict criteria	74
5.3.7.4	Radio receiver blocking case 1: owing to signals occurring at the same time but on other frequencies	74
5.3.7.4.1	Test environment	74
5.3.7.4.2	Method of measurement	74
5.3.7.4.3	Verdict criteria	75
5.3.7.5	Radio receiver blocking case 2: owing to signals occurring at a different time	75
5.3.7.5.1	Test environment	75
5.3.7.5.2	Method of measurement	76
5.3.7.5.3	Verdict criteria	76
5.3.7.6	Receiver intermodulation performance	76
5.3.7.6.1	Test environment	76
5.3.7.6.2	Method of measurement	76
5.3.7.6.3	Verdict criteria	77
5.3.7.7	Spurious emissions when the PP has no allocated transmit channel	77
5.3.7.7.1	Test environment	77
5.3.7.7.2	Method of measurement	77
5.3.7.7.3	Verdict criteria (outside the DECT band)	77
5.3.7.7.4	Verdict criteria (inside the DECT band)	77
5.3.8	Channel access	78
5.3.8.1	Test Environment	78
5.3.8.2	FT Test Setup	78
5.3.8.2.1	General	78
5.3.8.2.2	FT Method of Measurement	79
5.3.8.2.3	FT Verdict Criteria	79
5.3.8.3	PT Test Setup	79
5.3.8.3.1	General	79
5.3.8.3.2	PT Method of Measurement	80
5.3.8.3.3	PT Verdict Criteria	80
5.3.8.4	Channel Release	81
5.3.8.4.1	General	81
5.3.8.4.2	Method of Measurement	81
5.3.8.4.3	Channel Release Verdict Criteria	82
5.3.9	WRS testing	82
5.3.9.0	General	82
5.3.9.1	Test environment	82
5.3.9.2	Testing as a PP	82
5.3.9.3	Testing as an RFP	82
5.3.9.4	Additional requirements	83
5.3.9.5	Conformance	83
5.3.10	Direct PP to PP communication	83
5.3.10.0	General	83
5.3.10.1	Test environment	83
5.3.11	Distributed communications	83
5.3.11.0	General	83
5.3.11.1	Test environment	83
5.3.11.2	Testing as a PP	83

5.3.11.3	Testing as an RFP	84
5.3.11.4	Conformance	84
5.3.12	Higher level modulation options	84
5.3.12.0	General	84
5.3.12.1	Test environment	84
5.3.12.2	Activation of higher level modulations when EUT is in Test Standby Mode	84
5.3.12.3	Conformance	85
Annex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	86
Annex B (informative):	Maximum measurement uncertainty	88
Annex C (normative):	Test sites and arrangements for radiated measurements	89
C.1	Introduction	89
C.2	Radiation test sites	89
C.2.1	Open Area Test Site (OATS)	89
C.2.2	Semi Anechoic Room (SAR)	90
C.2.3	Fully Anechoic Room (FAR)	91
C.2.4	Measurement Distance	92
C.3	Antennas	93
C.3.1	Introduction	93
C.3.2	Measurement antenna	93
C.3.3	Substitution antenna	93
C.4	Test fixture	93
C.4.1	Introduction	93
C.4.2	Description of the test fixture	93
C.4.3	Using the test fixture for relative measurements	94
C.5	Guidance on the use of radiation test sites	94
C.5.1	Introduction	94
C.5.2	Power supplies for the battery powered EUT	94
C.5.3	Site preparation	95
C.6	Coupling of signals	95
C.6.1	General	95
C.6.2	Data Signals	95
C.7	Guidance for testing technical requirements	95
C.7.0	General	95
C.7.1	Radio test suites and corresponding test sites	95
Annex D (normative):	Procedures for radiated measurements	97
D.1	Introduction	97
D.2	Radiated measurements in an OATS or SAR	97
D.3	Radiated measurements in a FAR	98
D.4	Substitution measurement	98
Annex E (informative):	Procedure for measurement of conducted spurious emissions	99
E.1	Conducted spurious emissions	99
E.1.1	Definition	99
E.1.2	Method of measurement	99
Annex F (normative):	Measurement of BER and FER	100
Annex G (informative):	Procedures for the measurement of synchronization loss at the EUT by the LT	101

G.1	Description	101
G.2	Method	101
Annex H (informative):	Checklist	102
Annex I (informative):	Bibliography.....	103
Annex J (informative):	Change history	104
History		105

Sample Document

get full document from standards.iteh.ai

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables (European Standard (EN), Technical Specification (TS), Group Specification (GS) or ETSI Standard (ES)) may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Digital Enhanced Cordless Telecommunications (DECT).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.9] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.10].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

The present document is part 1 of a multi-part deliverable covering the access to radio spectrum of the different DECT radio interfaces:

Part 1: "DECT, DECT Evolution and DECT ULE";

Part 2: "DECT-2020 NR".

The present document covers DECT, DECT Evolution and DECT ULE as defined by the multi-part deliverable ETSI EN 300 175 (see [1] to [4] and [i.3] to [i.6]) and by the multi-part deliverable ETSI TS 102 939 (see [i.7] and [i.8]).

National transposition dates	
Date of adoption of this EN:	3 August 2026
Date of latest announcement of this EN (doa):	30 November 2026
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 May 2027
Date of withdrawal of any conflicting National Standard (dow):	31 May 2028

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Sample Document

get full document from standards.iteh.ai

1 Scope

The present document specifies technical characteristics and methods of measurements for equipment implementing the Digital Enhanced Cordless Telecommunications (DECT) common interface, as specified in the multi-part technical specification ETSI EN 300 175 including the variants DECT Evolution and DECT ULE (see ETSI EN 300 175-1 [i.3] for an overview).

The present document applies to the following equipment types:

- a) Fixed Part (FP);
- b) Portable Part (PP);
- c) Cordless Terminal Adapter (CTA);
- d) Wireless Relay Station (WRS) (FP and PP combined);
- e) Hybrid Part (HyP) (a PP with capability to act as a FP to provide PP to PP communication).

NOTE: This release of the standard covers the WRS type CRFP, but not the WRS type REP.

These radio equipment types are capable of operating in all or any part of the frequency bands given in table 1.

Table 1: Radiocommunications service frequency bands

	Radiocommunications service frequency bands
Transmit	1 880 MHz to 1 900 MHz
Receive	1 880 MHz to 1 900 MHz

The DECT service frequency band for transmitting and receiving for all elements is 1 880 MHz to 1 900 MHz. National regulation can allow additional frequency bands.

DECT equipment covered by the present document is operated in accordance with ERC Decision (98)22 [i.20].

Details of the DECT Common Interface may be found in the multi-part deliverable ETSI EN 300 175 (see [1] to [4] and [i.3] to [i.6]). Further details of the DECT system may be found in the ETSI TR 101 178 [i.1].

DECT ULE implements, in addition to the DECT Common Interface, the multi-part ETSI TS 102 939 (see ETSI TS 102 939-1 [i.7] and ETSI TS 102 939-2 [i.8]).

The present document contains requirements to demonstrate that radio equipment both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference.

NOTE: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.10] is given in annex A.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found in the [ETSI docbox](#).

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.