

---

**Naprave kratkega dosega (SRD), ki uporabljajo ultra širokopasovno tehnologijo (UWB) - Harmonizirani standard za dostop do radijskega spektra - 2. del: Radarska oprema za ugotavljanje ravni tekočine (LPR), ki deluje v frekvenčnih območjih od 75 GHz do 85 GHz za namestitev z nagibom navzdol**

Short Range Devices (SRD) using Ultra Wide Band technology (UWB) - Harmonised standard for access to radio spectrum - Part 2: Level Probing Radar (LPR) equipment operating in the frequency range 75 GHz to 85 GHz for tilted downward installation

# Sample Document

get full document from [standards.iteh.ai](https://standards.iteh.ai)

**Ta slovenski standard je istoveten z: ETSI EN 302 729-2 V3.1.1 (2026-05)**

---

**ICS:**

33.060.01	Radijske komunikacije na splošno	Radiocommunications in general
33.100.01	Elektromagnetna združljivost na splošno	Electromagnetic compatibility in general

**SIST EN 302 729-2 V3.1.1:2026**                      **en**

# Sample Document

get full document from [standards.iteh.ai](https://standards.iteh.ai)

# ETSI EN 302 729-2 V3.1.1 (2026-05)



HARMONISED EUROPEAN STANDARD

**Short Range Devices (SRD)  
using Ultra Wide Band technology (UWB);  
Harmonised standard for access to radio spectrum;  
Part 2: Level Probing Radar (LPR) equipment operating  
in the frequency range 75 GHz to 85 GHz  
for tilted downward installation**

---

**Reference**REN/ERM-TGUWB-590

---

**Keywords**EHF, harmonised standard, LPR, radar,  
short range, SRD, testing, UWB

---

**ETSI**650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

---

**Important notice**

---

The present document can be downloaded from the  
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to  
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our  
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

---

**Notice of disclaimer & limitation of liability**

---

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.  
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

---

**Copyright Notification**

---

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2026.  
All rights reserved.

# Contents

Intellectual Property Rights .....	7
Foreword.....	7
Modal verbs terminology.....	8
Introduction .....	8
1 Scope .....	9
2 References .....	9
2.1 Normative references .....	9
2.2 Informative references.....	9
3 Definition of terms, symbols and abbreviations.....	10
3.1 Terms.....	10
3.2 Symbols.....	11
3.3 Abbreviations .....	11
4 Technical requirements specifications .....	11
4.1 Environmental profile.....	11
4.2 Equipment categories .....	12
4.2.1 General.....	12
4.2.2 Categorization by tilting angle.....	12
4.2.3 Categorization by antenna connection .....	12
4.2.4 Summary equipment categories.....	12
4.3 Transmitter requirements .....	13
4.3.1 General.....	13
4.3.2 Operating Frequency Range (OFR).....	13
4.3.2.1 Applicability.....	13
4.3.2.2 Description .....	13
4.3.2.3 Limits .....	13
4.3.2.4 Conformance.....	14
4.3.3 Mean e.i.r.p. spectral density .....	14
4.3.3.1 Applicability.....	14
4.3.3.2 Description .....	14
4.3.3.3 Limits .....	14
4.3.3.4 Conformance.....	14
4.3.4 Peak e.i.r.p. spectral density.....	14
4.3.4.1 Applicability.....	14
4.3.4.2 Description .....	14
4.3.4.3 Limits .....	14
4.3.4.4 Conformance.....	15
4.3.5 Transmitter Unwanted Emissions (TXUE).....	15
4.3.5.1 Applicability.....	15
4.3.5.2 Description .....	15
4.3.5.3 Limits .....	15
4.3.5.4 Conformance.....	16
4.3.6 Radiation pattern.....	16
4.3.6.1 Applicability.....	16
4.3.6.2 Description .....	16
4.3.6.3 Limits .....	16
4.3.6.4 Conformance.....	18
4.3.7 Mitigation techniques .....	18
4.3.7.1 Combined mitigation factor .....	18
4.3.7.1.1 Applicability .....	18
4.3.7.1.2 Description .....	18
4.3.7.1.3 Limits .....	18
4.3.7.1.4 Conformance .....	19
4.3.7.2 Adaptive Power Control (APC) .....	19
4.3.7.2.1 Applicability.....	19

4.3.7.2.2	Description .....	19
4.3.7.2.3	Limits .....	19
4.3.7.2.4	Conformance .....	19
4.3.7.3	Duty cycle over signal repetition period ( $DC_{T_{rep}}$ ) .....	19
4.3.7.3.1	Applicability .....	19
4.3.7.3.2	Description .....	20
4.3.7.3.3	Limits .....	20
4.3.7.3.4	Conformance .....	20
4.3.7.4	Frequency Domain Mitigation (FDM) .....	20
4.3.7.4.1	Applicability .....	20
4.3.7.4.2	Description .....	20
4.3.7.4.3	Limits .....	21
4.3.7.4.4	Conformance .....	21
4.3.8	TX-behaviour under the complete environmental profile .....	21
4.3.8.1	Applicability .....	21
4.3.8.2	Description .....	22
4.3.8.3	Limits .....	22
4.3.8.3.1	Limits for radiated assessment of the TX-behaviour .....	22
4.3.8.3.2	Limits for conducted assessment of the TX-behaviour .....	22
4.3.8.4	Conformance .....	22
4.4	Receiver requirements .....	22
4.4.1	General .....	22
4.4.2	Wanted technical performance criteria .....	23
4.4.3	Receiver Baseline Sensitivity (RBS) .....	23
4.4.3.1	Applicability .....	23
4.4.3.2	Description .....	23
4.4.3.3	Limits .....	23
4.4.3.4	Conformance .....	23
4.4.4	Receiver Baseline Resilience (RBR) .....	23
4.4.4.1	Applicability .....	23
4.4.4.2	Description .....	24
4.4.4.3	Limits .....	24
4.4.4.4	Conformance .....	24
5	Testing for compliance with technical requirements .....	25
5.1	Environmental conditions for testing .....	25
5.1.1	General .....	25
5.1.2	Normal test conditions .....	25
5.1.3	Complete environmental profile test conditions .....	25
5.2	General conditions for testing .....	25
5.3	Conformance test suites .....	25
5.4	Conformance test methods for transmitter .....	26
5.4.1	Operating Frequency Range (OFR) .....	26
5.4.1.1	General .....	26
5.4.1.2	Conformance test for EUTs with antenna connector .....	26
5.4.1.3	Conformance test for EUTs with integral antennas .....	26
5.4.2	Mean e.i.r.p. spectral density .....	26
5.4.2.1	General .....	26
5.4.2.2	Conformance test for EUTs with antenna connector .....	26
5.4.2.3	Conformance test for EUTs with integral antennas .....	27
5.4.3	Peak e.i.r.p. spectral density .....	27
5.4.3.1	General .....	27
5.4.3.2	Conformance test for EUTs with antenna connector .....	27
5.4.3.3	Conformance test for EUTs with integral antennas .....	27
5.4.4	Transmitter Unwanted Emissions (TXUE) .....	27
5.4.4.1	General .....	27
5.4.4.2	Transmitter Unwanted Emissions in the Out-Of-Band (OOB) domain .....	28
5.4.4.3	Transmitter Unwanted Emissions in the spurious domain .....	28
5.4.5	EUT radiation pattern .....	29
5.4.5.1	General .....	29
5.4.5.2	Conformance test for EUTs with antenna connector .....	30
5.4.5.3	Conformance test for EUTs with integral antennas .....	31

5.4.5.4	Antenna gain for EUTs with integral antennas .....	32
5.4.6	Adaptive Power Control (APC) .....	32
5.4.6.1	General .....	32
5.4.6.2	Conformance test for EUTs with integral antennas .....	32
5.4.6.3	Conformance test for EUTs with antenna connector .....	34
5.4.7	Duty cycle over signal repetition period .....	34
5.4.7.1	General .....	34
5.4.7.2	Conformance test for EUTs with antenna connector .....	35
5.4.7.3	Conformance test for EUTs with integral antennas .....	35
5.4.8	Frequency domain mitigation .....	35
5.4.8.1	General .....	35
5.4.8.2	Conformance test for EUTs with antenna connector .....	35
5.4.8.3	Conformance test for EUTs with integral antennas .....	35
5.4.9	TX-behaviour under the complete environmental profile .....	36
5.4.9.1	General .....	36
5.4.9.2	Conformance test for EUTs with antenna connector .....	36
5.4.9.3	Conformance test for EUTs with integral antennas .....	36
5.5	Conformance test methods for receiver .....	36
5.5.1	Receiver Baseline Sensitivity (RBS) .....	36
5.5.1.1	General .....	36
5.5.1.2	Conformance test for EUTs with integral antennas .....	36
5.5.1.3	Conformance test for EUTs with antenna connector .....	37
5.5.1.4	Test procedure .....	38
5.5.2	Receiver Baseline Resilience (RBR) .....	38
5.5.2.1	General .....	38
5.5.2.2	Test setups for EUTs providing no access to the receiver noise level .....	38
5.5.2.2.1	Conformance test for EUTs with integral antennas .....	38
5.5.2.2.2	Conformance test for EUTs with antenna connector .....	40
5.5.2.2.3	Test procedure .....	41
5.5.2.3	Test setups for EUTs providing access to the receiver noise level .....	41
5.5.2.3.1	General .....	41
5.5.2.3.2	Test procedure .....	42
<b>Annex A (informative):</b>	<b>Relationship between the present document and the essential requirements of Directive 2014/53/EU .....</b>	<b>44</b>
<b>Annex B (informative):</b>	<b>Selection of technical parameters .....</b>	<b>46</b>
<b>Annex C (normative):</b>	<b>Test scenarios for receiver parameters measurements .....</b>	<b>48</b>
C.1	Introduction .....	48
C.2	Definition of the real scenario .....	48
C.3	Derivation of the radiated equivalent scenario .....	49
C.4	Evaluation of the Radar Cross Section (RCS) of standard radar targets .....	49
<b>Annex D (normative):</b>	<b>Interferer signals for receiver baseline resilience .....</b>	<b>50</b>
D.1	General .....	50
D.2	Interferer within the OFR .....	50
D.3	Interferer outside of the OFR .....	50
<b>Annex E (informative):</b>	<b>Installation requirements .....</b>	<b>51</b>
<b>Annex F (informative):</b>	<b>FMCW modulation schemes .....</b>	<b>53</b>
<b>Annex G (informative):</b>	<b>Main beam direction of tilted LPR equipment .....</b>	<b>54</b>
<b>Annex H (informative):</b>	<b>Bibliography .....</b>	<b>55</b>
<b>Annex I (informative):</b>	<b>Change history .....</b>	<b>56</b>

History .....57

# Sample Document

get full document from [standards.iteh.ai](https://standards.iteh.ai)

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

## Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.2] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in Table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

The present document is part 2 of a multi-part deliverable covering Short Range Devices (SRD) using Ultra Wide Band technology (UWB); Harmonised standard for access to radio spectrum, as identified below:

**Part 1:** "Level Probing Radar (LPR) equipment operating in the frequency ranges 6 GHz to 8,5 GHz, 24,05 GHz to 26,5 GHz, 57 GHz to 64 GHz, 75 GHz to 85 GHz for strictly vertical downward installation";

**Part 2:** "**Level Probing Radar (LPR) equipment operating in the frequency range 75 GHz to 85 GHz for tilted downward installation**".

**NOTE:** The list above shows the planned multi-part deliverable, at the time, when the present document was finalized.

<b>National transposition dates</b>	
Date of adoption of this EN:	4 May 2026
Date of latest announcement of this EN (doa):	31 August 2026
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	28 February 2027
Date of withdrawal of any conflicting National Standard (dow):	29 February 2028

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

## Introduction

ETSI ERM TGUWB decided to develop more specific standards; this means instead of one generic ETSI EN 302 729 for all Level Probing Radar (LPR) devices, this multi-part deliverable was initiated in order to reflect the intended use in relation to different aspects of the corresponding regulation ECC Decision (11)02 [i.3].

Part 1 covers the original provisions made in ECC Decision (11)02 [i.3] of 11 March 2011 for LPR equipment with strictly vertical downward installation (see ECC Decision (11)02 [i.3], first four lines of Table 1 for strictly vertical antenna orientation).

Part 2 covers the amendments made in ECC Decision (11)02 [i.3] on 5 July 2019 for LPR equipment with tilted downward installation (see ECC Decision (11)02 [i.3], last three lines of Table 1 for tilted antenna orientation).

Due to the amendment of ECC Decision (11)02 [i.3] on 5 July 2019, ETSI ERM TGUWB decided to follow henceforth a two-part structure and to only reflect the amendments made in 2019 in part 2 of the series.

More information on the conducted changes in previous versions of the present document can be found in the change history in Annex H.

---

# 1 Scope

The present document specifies technical requirements, limits and test methods for Tilted Level Probing Radar (LPR) equipment using a downward tilted orientation of the LPR antenna in the three tilting ranges  $\pm 15^\circ$ ,  $\pm 30^\circ$  and  $\pm 45^\circ$  in relation to the strictly vertical downward direction and operating in the frequency range 75 GHz to 85 GHz in outdoor as well as indoor environments.

Tilted LPR equipment in the scope of the present document consist of a combined transmitter and receiver and are equipped with an integral or dedicated antenna provided also by the equipment manufacturer. Equipment intended to be equipped with antennas from a third-party are not covered by the scope of the present document.

Equipment exhibiting a receive only mode or a standby mode are also not covered by the scope of the present document. Furthermore, the present document is limited to tilted LPR equipment with FMCW modulation.

Tilted LPR equipment and the related categorization is further specified in clause 4.2.

NOTE: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.1] is given in Annex A.

---

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found in the [ETSI docbox](#).

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

The following referenced documents are necessary for the application of the present document.

- [1] [ETSI EN 303 883-1 \(V2.1.1\) \(08-2024\)](#): "Short Range Devices (SRD) and Ultra Wide Band (UWB); Part 1: Measurement techniques for transmitter requirements".
- [2] [ETSI EN 303 883-2 \(V2.1.1\) \(08-2024\)](#): "Short Range Devices (SRD) and Ultra Wide Band (UWB); Part 2: Measurement techniques for receiver requirements".
- [3] [ETSI TS 103 789 \(V1.1.1\) \(05-2023\)](#): "Short Range Devices (SRD) and Ultra Wide Band (UWB); Radar related parameters and physical test setup for object detection, identification and RCS measurement".
- [4] [ETSI TS 103 941 \(V1.1.1\) \(01-2024\)](#): "Short Range Devices (SRD) and Ultra Wide Band (UWB); Measurement setups and specifications for testing under full environmental profile (normal and extreme environmental conditions)".

### 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

The following referenced documents may be useful in implementing an ETSI deliverable or add to the reader's understanding, but are not required for conformance to the present document.

- [i.1] [Directive 2014/53/EU](#) of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC (RE-Directive).
- [i.2] [Commission implementing Decision C\(2015\) 5376](#) final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.3] [ECC Decision \(11\)02 \(11 March 2011\)](#): "Industrial Level Probing Radars (LPR) operating in frequency bands 6-8.5 GHz, 24.05-26.5 GHz, 57-64 GHz and 75-85 GHz".
- [i.4] [ECC Report 139](#): "Impact of Level Probing Radars Using Ultra-Wideband Technology on Radiocommunications Services", Rottach-Egern, February 2010.
- [i.5] [CEPT ERC Recommendation 74-01 \(May 2022\)](#): "Unwanted emissions in the spurious domain".
- [i.6] ETSI TR 102 601 V1.1.1 (12-2007): "Electromagnetic compatibility and Radio spectrum Matters (ERM); System reference document; Short Range Devices (SRD); Equipment for Detecting Movement using Ultra Wide Band (UWB) radar sensing technology; Level Probing Radar (LPR)-sensor equipment operating in the frequency bands 6 GHz to 8,5 GHz; 24,05 GHz to 26,5 GHz; 57 GHz to 64 GHz and 75 GHz to 85 GHz".
- [i.7] [Commission Implementing Decision \(EU\) 2025/105](#) of 22 January 2025 amending Decision 2006/771/EC updating harmonised technical conditions in the area of radio spectrum use for short-range devices and repealing Implementing Decision 2014/641/EU on harmonised technical conditions of radio spectrum use by wireless audio programme making and special events equipment in the Union.
- [i.8] Void.
- [i.9] Void.
- [i.10] ETSI EG 203 336 (V1.2.1) (05-2020): "Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.11] ETSI TS 103 567 (V1.1.1) (09-2019): "Requirements on signal interferer handling".
- [i.12] ETSI TS 103 361 (V1.1.1) (03-2016): "Short Range Devices (SRD) using Ultra Wide Band technology (UWB); Receiver technical requirements, parameters and measurement procedures to fulfil the requirements of the Directive 2014/53/EU".
- [i.13] ETSI TR 102 273-2 (V1.2.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 2: Anechoic chamber".

---

## 3 Definition of terms, symbols and abbreviations

### 3.1 Terms

For the purposes of the present document, the terms given in ETSI EN 303 883-1 [1], ETSI EN 303 883-2 [2] and the following apply:

**Adaptive Power Control (APC):** automatic mechanism to reduce interference to other radio services and applications

NOTE: The Adaptive Power Control (APC) is sometimes also called transmit power control.

**Duty Cycle over signal repetition period (DC\_  $T_{rep}$ ):** ratio of the sum of all active measurement periods  $T_{on}$  (bursts, sweeps, scans) within the signal repetition period  $T_{rep}$

**Equipment Under Test (EUT):** Level Probing Radar (LPR) under test

**Frequency Modulated Continuous Wave (FMCW) radar:** modulation scheme based on a periodically linear frequency sweep of the transmit signal

NOTE: See Annex F of the present document and ETSI EN 303 883-1 [1], clause C.2.2.

**main beam direction:** measurement direction of the tilted level probing radar

NOTE: See Annex G of the present document.

**radiation:** signals emitted intentionally for level measurements

**step response time (of an LPR):** time span after a sudden distance change until the output value (distance value) reaches 90 % of the final value for the first time

**tilting angle:** angle formed between the main beam direction of the device which is installed in the application and the vertical axis

NOTE: See Annex G of the present document.

## 3.2 Symbols

For the purposes of the present document, the following symbols apply:

$t_{on}$  dwell time or sweep time for FMCW modulation schemes

## 3.3 Abbreviations

For the purposes of the present document, the abbreviations given in ETSI EN 303 883-1 [1], ETSI EN 303 883-2 [2] and the following apply:

EFTA	European Free Trade Association
HPBW	Half Power BeamWidth
IEC	International Electrotechnical Commission
ITU-R	International Telecommunication Union - Radiocommunication Sector
LPR	Level Probing Radar
RB	Reference Bandwidth
UK	United Kingdom

---

# 4 Technical requirements specifications

## 4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be in accordance with its intended use, but as a minimum, shall be that specified in the test conditions contained in the present document. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the operational environmental profile defined by its intended use.

## 4.2 Equipment categories

### 4.2.1 General

Technical and regulatory requirements for Tilted LPR equipment are provided in general in European Commission Implementing Decision (EU) 2025/105 [i.7] and ECC Decision (11)02 [i.3], which are based on ECC Report 139 [i.4]. The present document covers only the essential technical requirements set out in the last three rows in Table 1 of ECC Decision (11)02 [i.3] for LPR equipment using a tilted vertical downward orientation of the equipment antenna.

In addition, the manufacturer needs to consider further installation requirements as specified in Annex E and will have to provide this information to the user/installer. These installation requirements, however, are not subject to Annex A of the present document.

The following criteria were considered for equipment categorization of the tilted LPR equipment covered by the present document:

- the tilting angle of the tilted LPR antenna, see clause 4.2.2;
- the used antenna connection, see clause 4.2.3.

An overview of the covered equipment categories is provided in clause 4.2.4, Table 3.

### 4.2.2 Categorization by tilting angle

The tilting angle is the angle between the vertical direction and the main beam direction of the equipment. It depends on the mounting orientation of the device in the application, see Annex G. The permitted tilting angle shall be stated in the technical documentation of the device.

The following equipment categorization by the tilting angle is used:

- TIL1: Tilting angle downward up to  $\pm 15^\circ$ ;
- TIL2: Tilting angle downward up to  $\pm 30^\circ$ ;
- TIL3: Tilting angle downward up to  $\pm 45^\circ$ .

This equipment categorization has been conducted, covering the permitted tilting angles of tilted LPRs of ECC Decision (11)02 [i.3].

**NOTE:** The TIL categorization defines the maximum tilting angle in degree in relation to the transmit power see clause 4.3.3. In other words if a larger tilting angle is required, the transmit power level of the equipment has to be reduced.

### 4.2.3 Categorization by antenna connection

The following equipment categorization by the antenna connection is used:

- ANT1: Tilted LPR features an antenna connector: the tilted LPR is equipped with a dedicated antenna;
- ANT2: Tilted LPR has no antenna connector: the tilted LPR is equipped with an integral antenna.

### 4.2.4 Summary equipment categories

An overview of the applicability of transmitter requirements and receiver requirements for the different equipment categories is shown in Table 1 and Table 2, respectively.

**Table 1: Applicability of transmitter requirements for the different Equipment categories**

TX requirements	Clause	Category	
		tilting angle	antenna connection
Operating frequency range	4.3.2	applicable to all TIL categories	applicable to all ANT categories
Mean e.i.r.p. spectral density	4.3.3		
Peak e.i.r.p. spectral density	4.3.4		
Transmitter Unwanted Emissions (TXUE)	4.3.5		
Antenna requirements	4.3.6		
Mitigation techniques	4.3.7.1		

**Table 2: Applicability of receiver requirements for the different Equipment categories**

RX requirements	Clause	Category	
		tilting angle	antenna connection
Receiver Baseline Sensitivity (RBS)	4.4.3	applicable to all TIL categories	applicable to all ANT categories
Receiver Baseline Resilience (RBR)	4.4.4		

The categories which are supported by the equipment shall be stated in the technical documentation of the equipment (TiltLPR1 to TiltLPR6, see Table 3).

**Table 3: Equipment categories based on categorization listed in clause 4.2.1**

Equipment category	Category	
	tilting angle	antenna connection
TiltLPR1	TIL1	ANT1
TiltLPR2	TIL1	ANT2
TiltLPR3	TIL2	ANT1
TiltLPR4	TIL2	ANT2
TiltLPR5	TIL3	ANT1
TiltLPR6	TIL3	ANT2

## 4.3 Transmitter requirements

### 4.3.1 General

The transmitter requirements for tilted LPR equipment covered by the scope of the present document are justified in Table B.1.

### 4.3.2 Operating Frequency Range (OFR)

#### 4.3.2.1 Applicability

The operating frequency range requirement applies to all equipment categories as specified in clause 4.2.4, Table 3.

#### 4.3.2.2 Description

The operating frequency range is described in ETSI EN 303 883-1 [1], clause 5.2.1. According to this description and the specification in ECC/DEC/(11)02 [i.3], note (5), 20 dB is specified for the parameter X. This parameter takes precedence over any other values mentioned in ETSI EN 303 883-1 [1], clause 5.2.1.

#### 4.3.2.3 Limits

The OFR (all frequencies between  $f_L$  and  $f_H$ ) shall be within the permitted frequency range (see Table 4).