
Satelitske zemeljske postaje in sistemi (SES) - Fiksne zemeljske postaje, ki komunicirajo z negeostacionarnimi satelitskimi sistemi FSS v pasovih 20 GHz in 30 GHz - Harmonizirani standard za dostop do radijskega spektra

Satellite Earth Stations and Systems (SES) - Fixed earth stations communicating with non-geostationary satellite systems in the 20 GHz and 30 GHz FSS bands - Harmonised Standard for access to radio spectrum

Sample Document

get full document from standards.iteh.ai

Ta slovenski standard je istoveten z: ETSI EN 303 699 V1.2.1 (2026-10)

ICS:

33.060.30	Radiorelejni in fiksni satelitski komunikacijski sistemi	Radio relay and fixed satellite communications systems
-----------	--	--

SIST EN 303 699 V1.2.1:2026

en

Sample Document

get full document from standards.iteh.ai

ETSI EN 303 699 V1.2.1 (2026-10)



**Satellite Earth Stations and Systems (SES);
Fixed earth stations communicating with non-geostationary
satellite systems in the 20 GHz and 30 GHz FSS bands;
Harmonised Standard for access to radio spectrum**

get full document from standards.iteh.ai

ReferenceREN/SES-00462

Keywordsantenna, earth station, FSS, harmonised standard,
non-GSO, regulation, satellite

ETSI650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part of this document may be reproduced in any form, by any means and in any media, without the prior written authorization of ETSI and except as expressly permitted below.

By way of exception and when the document is a normative deliverable (European Standard (EN), Technical Specification (TS), Group Specification (GS) or ETSI Standard (ES)), ETSI authorizes to reproduce and incorporate into products, services and technical documentation only those extracts (e.g. templates) that are strictly necessary for the technical implementation of the normative deliverable, to ensure compliance with the latter. Nothing in this notice shall be construed as limiting any mandatory exceptions to copyright provided by applicable law.

© ETSI 2026.
All rights reserved.

Contents

Intellectual Property Rights	7
Foreword.....	7
Modal verbs terminology.....	8
1 Scope	9
2 References	10
2.1 Normative references	10
2.2 Informative references.....	10
3 Definition of terms, symbols and abbreviations.....	11
3.1 Terms.....	11
3.2 Symbols.....	13
3.3 Abbreviations	13
4 Technical requirements specifications	14
4.1 General	14
4.1.1 Environmental profile	14
4.1.2 Operational configurations	14
4.1.3 EIRP _{Aggregate} for networks of ESs	14
4.1.4 Void	15
4.1.5 Void	15
4.1.6 Void	15
4.1.7 Peak pointing accuracy	15
4.2 Conformance requirements	15
4.2.1 Off-axis spurious radiation	15
4.2.1.1 Justification	15
4.2.1.2 Specification.....	15
4.2.1.3 Conformance tests	16
4.2.2 On-axis spurious radiation	16
4.2.2.1 Justification	16
4.2.2.2 Specification.....	16
4.2.2.2.1 "Carrier-on" radio state.....	16
4.2.2.2.2 "Carrier-off" and "Emissions disabled" radio states	17
4.2.2.3 Conformance tests	17
4.2.3 Void	17
4.2.4 Void	17
4.2.5 Carrier suppression	17
4.2.5.1 Justification	17
4.2.5.2 Specification.....	17
4.2.5.3 Conformance tests	17
4.2.6 Antenna pointing accuracy	18
4.2.6.1 Purpose.....	18
4.2.6.2 Pointing accuracy specification.....	18
4.2.6.3 On-axis polarization angle specification	18
4.2.6.4 Conformance tests	18
4.2.7 Cessation of emissions.....	18
4.2.7.1 Justification	18
4.2.7.2 Specification.....	18
4.2.7.2.1 Specification 1: Mode of cessation of emissions	18
4.2.7.2.2 Specification 2: Conditions under which the ES shall cease emissions.....	19
4.2.7.2.3 Specification 3: Cessation of emissions	19
4.2.7.2.4 Specification 4: Fault conditions	19
4.2.7.3 Conformance tests	19
4.2.8 Control and Monitoring Functions (CMFs)	20
4.2.8.1 ES States	20
4.2.8.1.1 General	20
4.2.8.1.2 CMF state diagram	21

4.2.8.2	Processor monitoring	22
4.2.8.2.1	Justification	22
4.2.8.2.2	Specification	22
4.2.8.2.3	Conformance tests	22
4.2.8.3	Transmit subsystem monitoring	23
4.2.8.3.1	Justification	23
4.2.8.3.2	Specification	23
4.2.8.3.3	Conformance tests	23
4.2.8.4	Power-on/Reset	23
4.2.8.4.1	Justification	23
4.2.8.4.2	Specification	23
4.2.8.4.3	Conformance tests	23
4.2.8.5	Control Channel (CC) and Response Channel (RC)	23
4.2.8.5.1	Justification	23
4.2.8.5.2	Specification	23
4.2.8.5.3	Conformance tests	24
4.2.8.6	Network control commands	24
4.2.8.6.1	Justification	24
4.2.8.6.2	Specification	24
4.2.8.6.3	Conformance tests	25
4.2.8.7	Initial burst transmission	25
4.2.8.7.1	Justification	25
4.2.8.7.2	Specification	25
4.2.8.7.3	Conformance tests	25
4.2.8.8	Inhibition of transmissions	25
4.2.8.8.1	Justification	25
4.2.8.8.2	Specification	25
4.2.8.8.3	Conformance tests	26
4.2.9	Receive antenna off-axis gain pattern	26
4.2.9.1	Justification	26
4.2.9.2	Specification for ES without beam forming and without interference mitigation techniques	26
4.2.9.3	Conformance tests	26
4.2.10	Blocking performance	27
4.2.10.1	Justification	27
4.2.10.2	Specification	27
4.2.10.3	Conformance tests	27
4.2.11	Adjacent Signal Selectivity	27
4.2.11.1	Justification	27
4.2.11.2	Specification	27
4.2.11.3	Conformance tests	27
4.2.12	Image frequency rejection	28
4.2.12.1	Justification	28
4.2.12.2	Specification	28
4.2.12.3	Conformance tests	28
5	Testing for compliance with technical requirements	28
5.1	Environmental conditions for testing	28
5.2	Presentation of equipment for testing purposes	28
5.3	Choice of model for testing	28
6	Test methods for all aspects of the ES	29
6.1	General	29
6.1.1	General requirements	29
6.2	Off-axis spurious radiation	29
6.2.1	General	29
6.2.2	Test method	29
6.2.2.1	General	29
6.2.2.2	Multi-carrier operation	29
6.2.3	Measurements up to 1 000 MHz	30
6.2.3.1	Test site	30
6.2.3.2	Measuring receivers	30
6.2.3.3	Procedure	30

6.2.4	Measurements above 1 000 MHz	31
6.2.4.1	General	31
6.2.4.2	Identification of the significant frequencies of spurious radiation	31
6.2.4.2.1	Test site.....	31
6.2.4.2.2	Procedure.....	31
6.2.4.3	Measurement of radiated power levels of identified spurious radiation.....	32
6.2.4.3.1	Test site.....	32
6.2.4.3.2	Procedure.....	32
6.2.4.4	Measurement of conducted spurious radiation at the antenna flange.....	33
6.2.4.4.1	Test site.....	33
6.2.4.4.2	Procedure.....	34
6.3	On-axis spurious radiation.....	34
6.3.1	Test method	34
6.3.1.1	General	34
6.3.1.2	Test site	34
6.3.1.3	Method of measurement.....	34
6.3.1.3.1	General	34
6.3.1.3.2	Method of measurement at the antenna flange	35
6.3.1.3.3	Method of measurement for an EUT with antenna.....	37
6.4	Void.....	38
6.5	Carrier suppression.....	38
6.5.1	General.....	38
6.5.2	Test method	38
6.6	Antenna pointing.....	38
6.6.1	General.....	38
6.6.2	Test method	39
6.7	Polarization angle alignment capability	39
6.7.1	General.....	39
6.7.2	Test site.....	40
6.7.3	Procedure	40
6.8	Cessation of emissions of the ES.....	41
6.8.1	General.....	41
6.8.2	Test Method.....	41
6.8.2.1	Required documentation	41
6.8.2.2	Cessation of emissions from the "Transmission enabled" state	41
6.8.2.3	Cessation of emission from the "Transmission disabled" state	41
6.8.2.4	Cessation of emission from the "Initial Phase" state	42
6.8.2.4.1	EUTs transmitting initial bursts.....	42
6.8.2.4.2	EUTs not transmitting initial bursts.....	42
6.8.2.5	"Single action" means of cessation of emissions.....	42
6.8.2.6	Fault conditions.....	43
6.9	Control and monitoring functions	43
6.9.1	General.....	43
6.9.2	Test arrangement	43
6.9.3	Processor monitoring- Test method	44
6.9.4	Transmit subsystem monitoring-Test method.....	44
6.9.5	Power-on/Reset-Test method.....	44
6.9.6	Control Channel and Response Channel -Test method.....	45
6.9.7	Network Control commands-Test method	45
6.9.8	Initial burst transmission-Test method.....	47
6.9.9	Inhibition of transmission-Test method	47
6.10	Receive EUT antenna off-axis gain pattern.....	47
6.10.0	General.....	47
6.10.1	Test method	47
6.10.1.1	Test site	47
6.10.1.2	Method of measurement.....	48
6.10.1.3	Computation.....	48
6.11	Blocking performance	48
6.11.1	General.....	48
6.11.2	Test method	49
6.12	Adjacent Signal Selectivity	50
6.12.1	Test method	50

6.13	Image frequency rejection	51
Annex A (normative): Relationship between the present document and the essential requirements of Directive 2014/53/EU		52
Annex B (informative): Linear Polarization Alignment Error Calculation.....		55
Annex C (normative): Radiated measurement		56
C.1	Test sites and general arrangements for measurements involving the use of radiated fields	56
C.1.1	General	56
C.1.2	Anechoic Chamber	56
C.1.3	Anechoic Chamber with a conductive ground plane	57
C.1.4	Open Area Test Site (OATS)	58
C.1.5	Minimum requirements for test sites for measurements above 18 GHz.....	59
C.1.6	Test antenna.....	59
C.1.7	Substitution antenna	60
C.1.8	Measuring antenna	60
C.2	Guidance on the use of radiation test sites	60
C.2.1	General	60
C.2.2	Verification of the test site	60
C.2.3	Preparation of the EUT.....	60
C.2.4	Power supplies to the EUT	60
C.2.5	Range length.....	61
C.2.6	Site preparation	61
C.3	Coupling of signals.....	62
C.3.1	General	62
C.4	Standard test methods.....	62
C.4.1	General	62
C.4.2	Calibrated setup.....	62
C.4.3	Substitution method.....	63
Annex D (normative): Conducted measurements		64
Annex E (informative): RF Cables.....		65
Annex F (informative): RF Waveguides.....		66
Annex G (informative): Measurement equipment		67
G.1	Maximum measurement uncertainty	67
G.2	Measuring receiver.....	67
Annex H (informative): Bibliography.....		69
Annex I (informative): Change history.....		70
History		71

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables (European Standard (EN), Technical Specification (TS), Group Specification (GS) or ETSI Standard (ES)) may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Satellite Earth Stations and Systems (SES).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.1] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.2].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

National transposition dates	
Date of adoption of this EN:	28 September 2026
Date of latest announcement of this EN (doa):	31 December 2026
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 June 2027
Date of withdrawal of any conflicting National Standard (dow):	30 June 2027

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Sample Document

get full document from standards.iteh.ai

1 Scope

The present document specifies technical characteristics and methods for measurements for satellite communications Earth Stations (ES) with the following characteristics:

- The ES is designed for stationary operation.
- The ES is operating as part of a satellite network (e.g. star, mesh or point to point) used for the distribution and/or exchange of information.
- The transmit and receive frequencies are shown in Table 1.

Table 1: Frequency bands

	Frequency Bands/frequencies
Transmit (Earth-to-space) 1	27,5 GHz to 29,1 GHz
Transmit (Earth-to-space) 2	29,5 GHz to 30,0 GHz
Receive (space-to-Earth)	17,3 GHz to 20,2 GHz

- The ES transmits within the frequency range from 27,5 GHz to 29,1 GHz and 29,5 GHz to 30,0 GHz, which are bands allocated to the Fixed Satellite Services (FSS) (Earth-to-space) among other services.
- At the national level, terminals covered by the present document, might operate on a co-frequency basis, with stations of other FSS networks / systems or with stations of other services. The present document does not cover requirements for ensuring protection of such services.
- The ES receives within the range from 17,30 GHz to 20,20 GHz (FSS).
- The ES uses linear or circular polarization.
- The ES operates through non-geostationary satellites.
- The ES is designed for unattended operation and it does not address specifications or requirements for earth stations operating as gateways or master earth station.
- The ES is controlled and monitored by a Network Control Facility (NCF). This function may be performed centrally (e.g. for a network of ESs with a central hub) or it could be performed within the ES for autonomous control. The NCF is outside the scope of the present document.
- The ES has one or more directive antennas that track satellites.

The present document may also be applicable to the frequency bands 30,0 GHz to 31,0 GHz (Earth-to-space) and 20,2 GHz to 21,2 GHz (space-to-Earth) subject to national regulation.

The present document applies to the ES including its ancillary equipment and its various telecommunication ports, and when operated within the boundary limits of the operational environmental profile as defined by the intended use of the ES.

NOTE: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.1] is given in annex A.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found in the [ETSI docbox](#).

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

The following referenced documents are necessary for the application of the present document.

- [1] Void.
- [2] [CISPR 16-1-1:2019](#): "Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-1: Radio disturbance and immunity measuring apparatus - Measuring apparatus".
- [3] [CISPR 16-1-4:2025](#): "Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-4: Radio disturbance and immunity measuring apparatus - Antennas and test sites for radiated disturbance measurements".
- [4] Void.
- [5] [CISPR 32:2015/AMD1:2019](#): "Electromagnetic compatibility of multimedia equipment - Emission requirements".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

The following referenced documents may be useful in implementing an ETSI deliverable or add to the reader's understanding, but are not required for conformance to the present document.

- [i.1] [Commission Implementing Decision C\(2015\) 5376](#) final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.2] [Directive 2014/53/EU](#) of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.3] Void.
- [i.4] Void.
- [i.5] IEC 60153 (all parts): "Hollow metallic waveguides".
- [i.6] ETSI TR 100 028 (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.7] Void.

- [i.8] ETSI EG 203 336 (V1.1.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.9] ETSI TR 102 273 (all parts) (V1.2.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties".
- [i.10] ANSI C63.5 (2017): "American National Standard for Electromagnetic Compatibility - Radiated Emission Measurements in Electromagnetic Interference (EMI) Control - Calibration of Antennas (9 kHz to 40 GHz)".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the following terms apply:

ancillary equipment: equipment used in connection with an ES when the following conditions are met:

- the equipment is intended for use in conjunction with the ES to provide additional operational and/or control features (e.g. to extend control to another position or location)
- the equipment cannot be used on a stand alone basis, to provide user functions independently of the ES
- the absence of the equipment does not inhibit the operation of the ES

antenna controller: equipment used to maintain antenna stabilization and tracking accuracy based on inputs from the Control and Monitoring Function

bandwidth of the ideal signal: bandwidth of a theoretical signal that is defined by the modulation scheme of the actual signal and contains no unwanted signal components that would increase the bandwidth

NOTE: In case of amplitude or phase shift keying signals the bandwidth of an ideal signal is $B = R_s \times (1 + \alpha)$, where R_s is the symbol rate and α is the roll-off. (B in Hertz, R_s in symbol/s and α between 0 and 1)

carrier-off radio state: radio state in which the ES may transmit and does not transmit any carrier

carrier-on radio state: radio state in which the ES may transmit and transmits a carrier

Control Channel(s) (CC): channel or channels by which ESs receive control information from the NCF

desense: reduction in the sensitivity of a receiver due to the presence of high power signals in the adjacent channel(s)

EIRP_{Aggregate}: sum of the EIRP (Watts) within the reference bandwidth of the ES network (consistent with RR No. 22.5D)

EIRP_{max}: maximum EIRP capability of the ES

NOTE: EIRP_{term} is the on axis EIRP (Watts) of the ES within the nominated bandwidth.

emissions disabled radio state: radio state in which the ES is not emitting

NOTE: Examples of cases where the ES is in this radio state: before system monitoring pass, before the control channel is received, when a failure is detected, when an ES is commanded to disable, and when the ES is in a location requiring cessation of emissions.

equivalent power flux density uplink: sum of the power flux densities produced at a receive station in the geostationary orbit by all the transmit earth stations within a non-geostationary satellite system

external control channel: control channel which is either:

- i) carried by the ES network via the same or another satellite, but not within the internal protocol of the ES system; or
- ii) carried by any other radio communication system

external response channel: response channel which is either:

- i) generated by the ES network via the same or another satellite, but not within the internal protocol of the ES system; or
- ii) generated by any other radio communication system

integral antenna: antenna which cannot be removed during the tests according to the intended use

internal control channel: control channel which is carried by the ES network via the same satellite as used for transmission of user data and within the internal protocol structure of the ES system

internal response channel: response channel which is carried by the ES network via the same satellite as used for transmission of user data and within the internal protocol structure of the ES system

mobile platform: any non-stationary platform such as a train, a vessel, an aircraft or other vehicles

Network Control Facility (NCF): set of functional entities that, at system level, monitor and control the correct operation of the ES and, if appropriate, all of the ESs in a network

nominal antenna diameter: diameter of the antenna (in meters) for the intended use of the ES

NOTE 1: An antenna with a nominal antenna diameter D has the same technical characteristic as a circular aperture antenna of diameter D . For non circular aperture antenna, the nominal antenna diameter is defined for the intended use of the ES.

NOTE 2: Network operators might request antennas of a certain diameter. Then an antenna that is compliant with the requirement for nominal antenna diameter equal to the requested antenna diameter can be used.

nominated bandwidth: bandwidth of the ES radio frequency transmission nominated for the intended use of the ES and which meets the following conditions:

- The nominated bandwidth is centred on the transmit frequency and does not exceed 5 times the occupied bandwidth.
- The nominated bandwidth is wide enough to encompass all spectral elements of the transmission which have a level greater than the specified spurious radiation limits. The nominated bandwidth is wide enough to take account of the transmit carrier frequency stability. This definition is chosen to allow flexibility regarding adjacent channel interference levels which will be taken into account by operational procedures depending on the exact transponder carrier assignment situation.

off-axis angle: angle between the direction of the axis of the antenna main beam and the considered direction

operating frequency band: frequency band the ES is intended to be operated

peak pointing accuracy: angular error of antenna pointing that is not exceeded during intended use of the ES

phased array antenna: assembly of several radiating elements, driven by adjustable phases and amplitudes, whose total radiation combine constructively in the wanted direction and destructively in the others, in such a way the wanted direction can be steered by the adjustment of the phases

NOTE: A narrow beam (or beams) can be created and pointed in different directions.

removable antenna: antenna which may be removed during the tests

Response Channel (RC): channel by which ES transmit monitoring information to the NCF

spurious radiation: any radiation outside the nominated bandwidth

transmission disabled state: radio state in which the ES is not authorized to transmit by the NCF

transmission enabled state: radio state in which the ES is authorized to transmit by the NCF

wanted signal occupied bandwidth: width of the signal spectrum 10 dB below the total mean in-band power of the emission

NOTE: For a digital modulation scheme only.

3.2 Symbols

For the purposes of the present document, the following symbols apply:

dBc	ratio expressed in decibels relative to the EIRP of the unmodulated carrier
dBi	ratio of an antenna gain to the gain of an isotropic antenna, expressed in decibels
dBW	ratio of a power to 1 watt, expressed in decibels
dBpW	ratio of a power to 1 picowatt, expressed in decibels
dB μ V/m	ratio of an electric field to 1 μ V/m, expressed in decibels ($20 \log(\text{electric field} / 1 \mu\text{V/m})$)
$G(\varphi)$	antenna gain at angle φ relative to antenna main axis $G_x(\varphi)$ cross-polarized antenna gain at angle φ
φ	angle relative to antenna main axis
$IT_{\max}$	maximum Inhibit Time
IT_{trans}	inhibit Time to transition from "Carrier off" to "Carrier on" radio state
N	maximum number of earth stations expected to transmit simultaneously
K	factor that accounts for a reduction on the on axis spurious radiation level in case of multiple earth stations operating on the same frequency
T_{trans}	time to transition from "Carrier off" to "Carrier on" radio state

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

BER	Bit Error Rate
BW	BandWidth
CC	Control Channel
CCF	Control Channel reception Failure
CCR	Control Channel correctly Received
CENR	Cessation of Emissions Not Required
CEPT	Conférence Européenne des Postes et Télécommunications (European Conference of Post and Telecommunications)
CER	Cessation of Emissions Required
CISPR	Comité International Spécial des Perturbations Radioélectriques (International Special Committee on Radio Interference)
CMF	Control and Monitoring Functions
CTR	Common Technical Regulation
CW	Continuous Wave
DC	Direct Current
EIRP	Equivalent Isotropically Radiated Power
EMC	Electro-Magnetic Compatibility
EN	European Norm
epfd	equivalent power flux-density
ES	Earth Station
EUT	Equipment Under Test
FEC	Forward Error Correction
FSS	Fixed Satellite Service
GSO	Geostationary Satellite Orbit
hEN	harmonised European Norm
HPA	High Power Amplifier
IDU	Indoor Unit
IEC	International Electrotechnical Commission
IP	Internet Protocol
KA	Ka band