

SLOVENSKI STANDARD

SIST EN 50342-6:2025

01-oktober-2025

Nadomešča:

SIST EN 50342-6:2016

SIST EN 50342-6:2016/A1:2019

Svinčeno-kislinske zaganjalne baterije - 6. del: Baterije za mikrociklične aplikacije

Lead-acid starter batteries - Part 6: Batteries for micro-cycle applications

Blei-Akkumulatoren-Starterbatterien - Teil 6 : Batterien für Mikrozyklen-Anwendungen

Batteries d'accumulateurs de démarrage au plomb - Partie 6: Batteries pour applications micro-cycles

Ta slovenski standard je istoveten z: EN 50342-6:2025

[SIST EN 50342-6:2025](https://standards.sist.si/catalog/standards/sist/11d77433-1025-4664-bc15-cc408c1a07a0/sist-en-50342-6-2025)

<https://standards.sist.si/catalog/standards/sist/11d77433-1025-4664-bc15-cc408c1a07a0/sist-en-50342-6-2025>

ICS:

29.220.20	Kislinski sekundarni členi in baterije	Acid secondary cells and batteries
-----------	--	------------------------------------

SIST EN 50342-6:2025

en

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 50342-6

August 2025

ICS 29.220.20

Supersedes EN 50342-6:2015; EN 50342-6:2015/A1:2018

English Version

Lead-acid starter batteries - Part 6: Batteries for micro-cycle applications

Batteries d'accumulateurs de démarrage au plomb - Partie
6: Batteries pour applications micro-cycles

Blei-Akkumulatoren-Starterbatterien - Teil 6 : Batterien für
Mikrozyklen-Anwendungen

This European Standard was approved by CENELEC on 2025-06-23. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.

SIST EN 50342-6:2025

<https://standards.iteh.ai/catalog/standards/sist/11d44433-f829-4664-bcf3-eea6be1a67af/sist-en-50342-6-2025>



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents

Page

European foreword.....	3
1 Scope	4
2 Normative references	4
3 Terms and definitions	4
4 General	4
4.1 Designation of starter batteries	4
4.2 Condition on delivery	4
5 General requirements — Identification and labelling	4
6 General test conditions.....	5
6.1 Characteristics and abbreviations.....	5
6.1.1 Nominal capacity C_n	5
6.1.2 Cranking current I_{CC}	5
6.2 Syntax of test descriptions.....	5
6.3 Requirements for measuring equipment capability.....	7
6.3.1 Equipment requirements for the micro-hybrid test MHT (8.2).....	7
6.3.2 Equipment requirements for the dynamic charge acceptance test DCA (8.3).....	8
6.3.3 Water bath	8
6.3.4 Equipment for other tests, measuring instruments.....	8
6.4 Sampling of batteries	8
7 Test sequence.....	8
8 Inspections and test procedures	9
8.1 Charging of batteries.....	9
8.2 Micro-hybrid test (MHT)	9
8.2.1 Purpose	9
8.2.2 Procedure	9
8.2.3 Data evaluation	12
8.3 Dynamic charge acceptance test (DCA).....	12
8.3.1 Purpose	12
8.3.2 Procedure	13
8.4 Endurance in cycle test with 17,5 % depth of discharge (DoD).....	17
8.4.1 Purpose	17
8.4.2 Procedure	17
8.5 Endurance in cycle test with 50 % depth of discharge (DoD) at 40 °C and preceded deep discharge.....	18
8.5.1 Purpose	18
8.5.2 Procedure	18
8.5.3 Deep discharge part	19
8.5.4 Rest time.....	19
8.5.5 Cycling part.....	19
9 Requirements and battery performance levels	20
9.1 General	20

9.2	Tests to be passed (no performance differentiation)	20
9.3	Tests determining the DCA performance level	21
9.4	Tests determining the micro-cycle performance level	22
Annex A (informative)	Flow charts of DCA test procedure, 8.3.	23
Annex B (normative)	Marking / Labelling of batteries	27
Bibliography		28

Tables

Table 1	Test steps	5
Table 2	Description of columns	6
Table 3	Acronyms and symbols	7
Table 4	Equipment requirements for the micro-hybrid test MHT	7
Table 5	Equipment requirements for the dynamic charge acceptance test DCA	8
Table 6	Test sequence	9
Table 7	Test sequence MHT V2	10
Table 8	DCA – Pre-cycling	13
Table 9	DCA – Charge Acceptance qDCA procedure	14
Table 10	DCA – The DCA_{pp} procedure	15
Table 11	DCA – The DCR_{ss} part	16
Table 12	Endurance 17,5 % DoD – Cycling units	18
Table 13	Endurance 50 % DoD – Deep discharge part	19
Table 14	Endurance 50 % DoD – Cycling part	20
Table 15	Requirements of tests to be passed	21
Table 16	Requirements levels DCA performance	21
Table 17	Requirements of tests determining the micro-cycle performance level M1...M3	22

Figures

Figure 1	Subphases of the DCR_{ss} part	17
Figure B.1	Optional Start-Stop logo	27