
Konektorji za električno in elektronsko opremo - Zahteve za izdelek - 2-118. del:
Okrogli konektorji - Podrobna specifikacija za oklepljene in neoklepljene, proste in
pritrjene konektorje z bajonetnim zaklepom velikosti B12, B17, B23 in B40, za
prenos električnega napajanja, signalov in podatkov (IEC 61076-2-118:2026)

Connectors for electrical and electronic equipment - Product requirements - Part 2-118:
Circular connectors - Detail specification for shielded and unshielded, free and fixed
connectors with bayonet-locking size B12, B17, B23 and B40, for power, signal and data
transmission (IEC 61076-2-118:2026)

Steckverbinder für elektrische und elektronische Geräte - Produktanforderungen -
Rundsteckverbinder - Einzelspezifikation für geschirmte und ungeschirmte, freie und
feste Steckverbinder mit Bajonettverriegelung der Größen B12, B17, B23 und B40, für
die Energie-, Signal- und Datenübertragung (IEC 61076-2-118:2026)

Connecteurs pour équipements électriques et électroniques - Exigences de produit -
Partie 2-118: Connecteurs circulaires - Spécification particulière relative aux fiches et
embases écrantées ou non écrantées avec verrouillage à baïonnette, des tailles B12,
B17, B23 et B40, pour la transmission de signaux, de puissance et de données (IEC
61076-2-118:2026)

Ta slovenski standard je istoveten z: EN IEC 61076-2-118:2026

ICS:

31.220.10	Vtiči in vtičnice, konektorji	Plug-and-socket devices. Connectors
-----------	-------------------------------	--

SIST EN IEC 61076-2-118:2026

en

Sample Document

get full document from standards.iteh.ai

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN IEC 61076-2-118

October 2026

ICS 31.220.10

English Version

Connectors for electrical and electronic equipment - Product requirements - Part 2-118: Circular connectors - Detail specification for shielded and unshielded, free and fixed connectors with bayonet-locking size B12, B17, B23 and B40, for power, signal and data transmission
(IEC 61076-2-118:2026)

Connecteurs pour équipements électriques et électroniques
- Exigences de produit - Partie 2-118: Connecteurs circulaires - Spécification particulière relative aux fiches et embases écrantées ou non écrantées avec verrouillage à baïonnette, des tailles B12, B17, B23 et B40, pour la transmission de signaux, de puissance et de données
(IEC 61076-2-118:2026)

Steckverbinder für elektrische und elektronische Geräte -
Produktanforderungen - Rundsteckverbinder - Einzelspezifikation für geschirmte und ungeschirmte, freie und feste Steckverbinder mit Bajonettverriegelung der Größen B12, B17, B23 und B40, für die Energie-, Signal- und Datenübertragung
(IEC 61076-2-118:2026)

This European Standard was approved by CENELEC on 2026-10-05. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

EN IEC 61076-2-118:2026 (E)**European foreword**

The text of document 48B/3196/FDIS, future edition 1 of IEC 61076-2-118, prepared by SC 48B "Electrical connectors" of IEC/TC 48 "Electrical connectors and mechanical structures for electrical and electronic equipment" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 61076-2-118:2026.

The following dates are fixed:

- latest date by which the document has to be implemented at national (dop) 2027-10-31 level by publication of an identical national standard or by endorsement
- latest date by which the national standards conflicting with the (dow) 2029-10-31 document have to be withdrawn

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

Any feedback and questions on this document should be directed to the users' national committee. A complete listing of these bodies can be found on the CENELEC website.

Endorsement notice

The text of the International Standard IEC 61076-2-118:2026 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following note has to be added for the standard indicated:

IEC 62197-1 NOTE Approved as EN 62197-1

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60068-1	-	Environmental testing - Part 1: General and guidance	EN 60068-1	-
IEC 60352	series	Solderless connections	EN 60352	series
IEC 60512-1	-	Connectors for electrical and electronic equipment - Tests and measurements - Part 1: Generic specification	EN IEC 60512-1	-
IEC 60512-1-1	-	Connectors for electronic equipment - Tests and measurements - Part 1-1: General examination - Test 1a: Visual examination	EN 60512-1-1	-
IEC 60512-1-2	-	Connectors for electronic equipment - Tests and measurements - Part 1-2: General examination - Test 1b: Examination of dimension and mass	EN 60512-1-2	-
IEC 60512-2-1	-	Connectors for electronic equipment - Tests and measurements - Part 2-1: Electrical continuity and contact resistance tests - Test 2a: Contact resistance - Millivolt level method	EN 60512-2-1	-
IEC 60512-2-5	-	Connectors for electronic equipment - Tests and measurements - Part 2-5: Electrical continuity and contact resistance tests - Test 2e: Contact disturbance	EN 60512-2-5	-
IEC 60512-3-1	-	Connectors for electronic equipment - Tests and measurements - Part 3-1: Insulation tests - Test 3a: Insulation resistance	EN 60512-3-1	-
IEC 60512-4-1	-	Connectors for electronic equipment - Tests and measurements - Part 4-1: Voltage stress tests - Test 4a: Voltage proof	EN 60512-4-1	-

EN IEC 61076-2-118:2026 (E)

IEC 60512-5-1	-	Connectors for electronic equipment - Tests and measurements - Part 5-1: Current-carrying capacity tests - Test 5a: Temperature rise	EN 60512-5-1	-
IEC 60512-6-3	-	Connectors for electronic equipment - Tests and measurements - Part 6-3: Dynamic stress tests - Test 6c: Shock	EN 60512-6-3	-
IEC 60512-6-4	-	Connectors for electronic equipment - Tests and measurements - Part 6-4: Dynamic stress tests - Test 6d: Vibration (sinusoidal)	EN 60512-6-4	-
IEC 60512-9-1	-	Connectors for electronic equipment - Tests and measurements - Part 9-1: Endurance tests - Test 9a: Mechanical operation	EN 60512-9-1	-
IEC 60512-9-2	-	Connectors for electronic equipment - Tests and measurements - Part 9-2: Endurance tests - Test 9b: Electrical load and temperature	EN 60512-9-2	-
IEC 60512-11-1	-	Connectors for electrical and electronic equipment - Tests and measurements - Part 11-1: Climatic tests - Test 11a - Climatic sequence	EN IEC 60512-11-1	-
IEC 60512-11-4	-	Connectors for electronic equipment - Tests and measurements - Part 11-4: Climatic tests - Test 11d: Rapid change of temperature	EN 60512-11-4	-
IEC 60512-11-9	-	Connectors for electronic equipment - Tests and measurements - Part 11-9: Climatic tests - Test 11i: Dry heat	EN 60512-11-9	-
IEC 60512-11-10	-	Connectors for electronic equipment - Tests and measurements - Part 11-10: Climatic tests - Test 11j: Cold	EN 60512-11-10	-
IEC 60512-11-12	-	Connectors for electronic equipment - Tests and measurements - Part 11-12: Climatic tests - Test 11m: Damp heat, cyclic	EN 60512-11-12	-
IEC 60512-13-2	-	Connectors for electronic equipment - Tests and measurements - Part 13-2: Mechanical operation tests - Test 13b: Insertion and withdrawal forces	EN 60512-13-2	-
IEC 60512-13-5	-	Connectors for electronic equipment - Tests and measurements - Part 13-5: Mechanical operation tests - Test 13e: Polarizing and keying method	EN 60512-13-5	-
IEC 60512-16-5	-	Connectors for electronic equipment - Tests and measurements - Part 16-5: Mechanical tests on contacts and terminations - Test 16e: Gauge retention force (resilient contacts)	EN 60512-16-5	-

EN IEC 61076-2-118:2026 (E)

IEC 60512-28-100	-	Connectors for electrical and electronic equipment - Tests and measurements - Part 28-100: Signal integrity tests up to 2 000 MHz - Tests 28a to 28g	EN IEC 60512-28-100	-
IEC 60529	1989	Degrees of protection provided by enclosures (IP Code)	EN 60529	1991
-	-		+ corrigendum May	1993
+ A1	1999		+ A1	2000
+ A2	2013		+ A2	2013
IEC 60664-1	2020	Insulation coordination for equipment within low-voltage supply systems - Part 1: Principles, requirements and tests	EN IEC 60664-1	2020
IEC 60998-2-1	-	Connecting devices for low-voltage circuits for household and similar purposes - Part 2-1: Particular requirements for connecting devices as separate entities with screw-type clamping units	EN 60998-2-1	-
IEC 60999-1	-	Connecting devices - Electrical copper conductors - Safety requirements for screw-type and screwless-type clamping units - Part 1: General requirements and particular requirements for clamping units for conductors from 0,2 mm ² up to 35 mm ² (included)	EN 60999-1	-
IEC 61076-1	-	Connectors for electronic equipment - Product requirements - Part 1: Generic specification	EN 61076-1	-
IEC 61984	2008	Connectors - Safety requirements and tests	EN 61984	2009
ISO 21920-1	-	Geometrical product specifications (GPS) - Surface texture: Profile - Part 1: Indication of surface texture	EN ISO 21920-1	-

Sample Document

get full document from standards.iteh.ai



IEC 61076-2-118

Edition 1.0 2026-08

INTERNATIONAL STANDARD

**Connectors for electrical and electronic equipment - Product requirements -
Part 2-118: Circular connectors - Detail specification for shielded and
unshielded, free and fixed connectors with bayonet-locking size B12, B17, B23
and B40, for power, signal and data transmission**

get full document from standards.iteh.ai

CONTENTS

FOREWORD	6
INTRODUCTION	8
1 Scope	9
2 Normative references	9
3 Terms and definitions	11
4 Technical information	12
4.1 Systems of levels	12
4.1.1 Performance levels	12
4.1.2 Compatibility levels	12
4.2 Classification into climatic categories	12
4.3 Current-carrying capacity	12
4.4 Type designation	13
4.5 Marking	16
4.6 Safety aspects	16
5 Dimensional information	16
5.1 General	16
5.2 Survey of styles and variants	16
5.2.1 General	16
5.2.2 Terminations	16
5.2.3 Fixed connectors	16
5.2.4 Free connectors	21
5.3 Interface dimensions	30
5.3.1 Interface dimensions – B12	30
5.3.2 Interface dimensions – B17	37
5.3.3 Interface dimensions – B23	55
5.3.4 Interface dimensions – B40	66
5.3.5 Interface dimensions – Trapezoidal data module	75
5.3.6 Engagement (mating) direction	78
5.4 Gauges	82
6 Characteristics	83
6.1 General	83
6.2 Contact assignment and other definitions	83
6.3 Classification into climatic categories	83
6.4 Electrical characteristics	84
6.4.1 General	84
6.4.2 Voltage proof	84
6.4.3 Rated impulse withstand voltage – pollution degree	85
6.4.4 Current-carrying capacity – temperature rise	85
6.4.5 Contact and shield resistance	86
6.4.6 Insulation resistance	86
6.5 Transmission performance	86
6.5.1 General	86
6.5.2 Insertion loss	86
6.5.3 Return loss	87
6.5.4 Near-end cross talk (NEXT)	87
6.5.5 Far-end cross talk (FEXT)	87

IEC 61076-2-118:2026 © IEC 2026

6.5.6	Transverse conversion loss (TCL)	88
6.5.7	Transverse conversion transfer loss (TCTL)	88
6.5.8	Transfer impedance	88
6.5.9	Coupling attenuation	89
6.5.10	Power sum alien (exogenous) NEXT (PS NEXT)	89
6.5.11	Power sum alien (exogenous) FEXT (PS AFEXT)	89
6.5.12	Propagation delay	90
6.6	Mechanical characteristics	90
6.6.1	Mechanical operations	90
6.6.2	Effectiveness of connector coupling device	90
6.6.3	Insertion and withdrawal forces	91
6.6.4	Polarization and coding	91
6.7	Other characteristics	92
6.7.1	Vibration (sinusoidal)	92
6.7.2	Shock	92
6.7.3	Degree of protection provided by enclosures (IP code)	92
6.7.4	Locking and unlocking torque	92
6.7.5	Environmental aspects – Marking of insulation material (plastics)	92
7	Test schedule	93
7.1	General	93
7.1.1	Overview	93
7.1.2	Climatic category	93
7.1.3	Arrangement for contact resistance measurements	93
7.1.4	Arrangement for dynamic stress tests (vibration)	94
7.1.5	Wiring of specimens	95
7.2	Test schedule	96
7.2.1	Test group P – Preliminary	96
7.2.2	Test group AP – Dynamic/climatic	96
7.2.3	Test group BP – Mechanical endurance	99
7.2.4	Test group CP – Electrical load	100
7.2.5	Test group DP – Connection method tests	101
7.2.6	Test group EP – Signal integrity requirements	101
7.2.7	Test group FP – Current carrying capacity	102
	Bibliography	103

Figure 1 – Fixed connector with wire ends, male power contacts, male data contacts, bayonet locking notch, and square flange front mounting

Figure 2 – Fixed connector with wire ends, male power contacts, male data contacts, bayonet locking notch, single hole front mounting, and keyway orientation

Figure 3 – Fixed connector with wire ends, male power contacts, male data contacts, bayonet locking notch, single hole rear mounting, and keyway orientation

Figure 4 – Fixed connector with wire ends, female power contacts, female data contacts, bayonet locking notch, and square flange front mounting

Figure 5 – Fixed connector with wire ends, female power contacts, female data contacts, bayonet locking notch, single hole front mounting, and keyway orientation

Figure 6 – Fixed connector with wire ends, female power contacts, female data contacts, bayonet locking notch, single hole rear mounting, and keyway orientation

IEC 61076-2-118:2026 © IEC 2026

Figure 7 – Rewirable connector, male, straight version, with bayonet locking nut.....	22
Figure 8 – Rewirable connector, male, angled version, with bayonet locking nut.....	23
Figure 9 – Non-rewirable connector, male, straight version, with bayonet locking nut.....	24
Figure 10 – Non-rewirable connector, male, angled version, with bayonet locking nut.....	24
Figure 11 – Rewirable connector, male, straight version, with bayonet locking notch	25
Figure 12 – Non-rewirable connector, male, straight version, with bayonet locking notch	26
Figure 13 – Rewirable connector, female, straight version, with bayonet locking nut.....	26
Figure 14 – Rewirable connector, female, angled version, with bayonet locking nut	27
Figure 15 – Non-rewirable connector, female, straight version, with bayonet locking nut.....	27
Figure 16 – Non-rewirable connector, female, angled version, with bayonet locking nut.....	28
Figure 17 – Rewirable connector, female, straight version, with bayonet locking notch	29
Figure 18 – Non-rewirable connector, female, straight version, with bayonet locking notch ...	29
Figure 19 – Dimensions of contact positioning of type B1201011	31
Figure 20 – Dimensions of contact positioning of type B1201012	32
Figure 21 – Dimension of B12 bayonet locking (2 bayonet grooves).....	35
Figure 22 – Dimensions of contact positioning of type B1702011	37
Figure 23 – Dimensions of contact positioning of type B1702012	38
Figure 24 – Dimensions of contact positioning of type B1703011	40
Figure 25 – Dimensions of contact positioning of type B1703012	41
Figure 26 – Dimensions of contact positioning of type B1704011	43
Figure 27 – Dimensions of contact positioning of type B1704012	44
Figure 28 – Dimensions of contact positioning of type B1705011	46
Figure 29 – Dimensions of contact positioning of type B1705012	47
Figure 30 – Dimension of contact positioning of type B1706211	49
Figure 31 – Dimensions of contact positioning of type B1706212	50
Figure 32 – Dimension of B17 bayonet locking (2 bayonet grooves).....	53
Figure 33 – Dimensions of contact positioning of type B2307011	56
Figure 34 – Dimensions of contact positioning of type B2307012	57
Figure 35 – Dimension of contact positioning of type B2308111	60
Figure 36 – Dimensions of contact positioning of type B2308112	61
Figure 37 – Dimension of B23 bayonet locking (2 bayonet grooves).....	64
Figure 38 – Dimensions of contact positioning of type B4009011	67
Figure 39 – Dimensions of contact positioning of type B4009012	68
Figure 40 – Dimension of B40 bayonet locking (3 bayonet grooves).....	71
Figure 41 – Dimensions of contact positioning and cross section of D1 data module.....	75
Figure 42 – Area for electric contact of shielding of D1 shielded data module	76
Figure 43 – Dimensions of contact positioning and cross section D2 data module.....	77
Figure 44 – Area for electric contact of shielding of D2 shielded data module	78
Figure 45 – Engagement (mating) information.....	79
Figure 46 – Gauge dimension	83
Figure 47 – Contact resistance arrangement.....	94
Figure 48 – Dynamic stress test arrangement	95

IEC 61076-2-118:2026 © IEC 2026

Table 1 – Ratings of connector power part	12
Table 2 – Ratings of connector signal part	13
Table 3 – Ratings of connector data part (data module)	13
Table 4 – Type designation	14
Table 5 – Combination possibilities of power, signal and data	15
Table 6 – Styles of fixed connectors	17
Table 7 – Dimensions of style DM	17
Table 8 – Dimensions of style EM	18
Table 9 – Dimensions of style FM	19
Table 10 – Dimensions of style DF	20
Table 11 – Dimensions of style EF	20
Table 12 – Dimensions of style FF	21
Table 13 – Styles of free connectors	22
Table 14 – Dimensions of style GM	23
Table 15 – Dimensions of style HM	23
Table 16 – Dimensions of style IM	24
Table 17 – Dimensions of style JM	25
Table 18 – Dimensions of style KM	25
Table 19 – Dimensions of style LM	26
Table 20 – Dimensions of style GF	26
Table 21 – Dimensions of style HF	27
Table 22 – Dimensions of style IF	28
Table 23 – Dimensions of style JF	28
Table 24 – Dimensions of style KF	29
Table 25 – Dimensions of style LF	30
Table 26 – Dimensions of contact positioning of type B12010□□	33
Table 27 – Type of B12 combined with D1 and D2 as application A	34
Table 28 – Type of B12 combined with D1 and D2 as application B	34
Table 29 – Dimensions of B12 bayonet locking	35
Table 30 – Mechanical codings B12 connectors	36
Table 31 – Dimensions of B12 mechanical codings	36
Table 32 – Dimensions of contact positioning of types B17020□□	39
Table 33 – Dimensions of contact positioning of types B17030□□	42
Table 34 – Dimensions of contact positioning of types B17040□□	45
Table 35 – Dimensions of contact positioning of types B17050□□	48
Table 36 – Dimensions of contact positioning of types B17062□□	51
Table 37 – Types of B17 combined with D1 and D2 as application A	52
Table 38 – Types of B17 combined with D1 and D2 as application B	52
Table 39 – Dimensions of B17 bayonet locking	53
Table 40 – Mechanical codings B17 connectors	54
Table 41 – Dimensions of B17 mechanical codings	55
Table 42 – Dimensions of contact positioning of types B23070□□	58
Table 43 – Dimensions of contact positioning of types B23081□□	62

IEC 61076-2-118:2026 © IEC 2026

Table 44 – Types of B23 combined with D1 and D2 as application A.....	63
Table 45 – Types of B23 combined with D1 as application B.....	64
Table 46 – Dimensions of B23 bayonet locking	65
Table 47 – Mechanical codings of B23 connectors	65
Table 48 – Dimensions of B23 mechanical codings	66
Table 49 – Dimensions of contact positioning of types B40090□□	69
Table 50 – Type of B40 combined with D1 and D2 as application A	70
Table 51 – Type of B40 combined with D1 and D2 as application B	70
Table 52 – Dimensions of B40 bayonet locking	72
Table 53 – Mechanical codings of B40 connectors	72
Table 54 – Dimensions of B40 mechanical codings	74
Table 55 – Dimensions of contact positioning of the D1 data module	76
Table 56 – Dimensions of contact positioning of the D2 data module	78
Table 57 – Connectors dimensions in mated and locked position	79
Table 58 – Gauges	83
Table 59 – Climatic category.....	84
Table 60 – Voltage proof.....	84
Table 61 – Rated impulse voltage and pollution degree	85
Table 62 – Insertion loss requirements	86
Table 63 – Return loss requirements	87
Table 64 – Near-end cross talk requirements	87
Table 65 – Far-end cross talk requirements	87
Table 66 – Transverse conversion loss requirements.....	88
Table 67 – Transverse conversion transfer loss requirements	88
Table 68 – Transfer impedance requirements	88
Table 69 – Coupling attenuation requirements	89
Table 70 – Power sum alien NEXT requirements	89
Table 71 – Power sum alien FEXT requirements.....	89
Table 72 – Propagation delay requirements	90
Table 73 – Number of cycles of mechanical operations.....	90
Table 74 – Minimum axial test force.....	91
Table 75 – Maximum insertion and withdrawal forces.....	91
Table 76 – Polarization insertion force	91
Table 77 – Maximum locking and unlocking torque	92
Table 78 – Number of test specimens and contacts	93
Table 79 – Test group P	96
Table 80 – Test group AP	96
Table 81 – Test group BP	99
Table 82 – Test group CP	100
Table 83 – Test group DP	101
Table 84 – Test group EP	101
Table 85 – Test group FP	102

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**Connectors for electrical and electronic equipment -
Product requirements -
Part 2-118: Circular connectors - Detail specification for free and fixed
connectors with bayonet-locking size B12, B17, B23 and B40, for power,
signal and data transmission**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61076-2-118 has been prepared by subcommittee 48B: Electrical connectors, of IEC technical committee 48: Electrical connectors and mechanical structures for electrical and electronic equipment. It is an International Standard.

The text of this International Standard is based on the following documents:

Draft	Report on voting
48B/3196/FDIS	48B/3205/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.