
Okoljski inženiring (EE) - Ocenjevanje energijske učinkovitosti mobilnega omrežja

Environmental Engineering (EE) - Assessment of mobile network energy efficiency

Ta slovenski standard je istoveten z: ETSI ES 203 228 V1.5.1 (2026-10)

ICS:

19.040	Preskušanje v zvezi z okoljem	Environmental testing
27.015	Energijska učinkovitost. Ohranjanje energije na splošno	Energy efficiency. Energy conservation in general
33.070.01	Mobilni servisi na splošno	Mobile services in general

SIST ES 203 228 V1.5.1:2026**en**

Sample Document

get full document from standards.iteh.ai

ETSI ES 203 228 V1.5.1 (2026-10)



Environmental Engineering (EE); Assessment of mobile network energy efficiency

Sample Document

get full document from standards.iteh.ai

Reference

RES/EE-EEPS69

Keywords

5G, access, base station, energy efficiency, GSM,
LTE, mobile, network, radio, UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part of this document may be reproduced in any form, by any means and in any media, without the prior written authorization of ETSI and except as expressly permitted below.

By way of exception and when the document is a normative deliverable (European Standard (EN), Technical Specification (TS), Group Specification (GS) or ETSI Standard (ES)), ETSI authorizes to reproduce and incorporate into products, services and technical documentation only those extracts (e.g. templates) that are strictly necessary for the technical implementation of the normative deliverable, to ensure compliance with the latter. Nothing in this notice shall be construed as limiting any mandatory exceptions to copyright provided by applicable law.

© ETSI 2026.
All rights reserved.

Contents

Intellectual Property Rights	5
Foreword.....	5
Modal verbs terminology.....	5
Executive summary	5
Introduction	6
1 Scope	7
2 References	7
2.1 Normative references	7
2.2 Informative references.....	8
3 Definition of terms, symbols and abbreviations.....	9
3.1 Terms.....	9
3.2 Symbols.....	10
3.3 Abbreviations	10
4 Network under test definition.....	12
4.1 Introduction	12
4.2 Test parameter categorization.....	14
4.3 Network classification	15
4.3.0 Introduction of network classification	15
4.3.1 Demography	15
4.3.2 Topography.....	16
4.3.3 Climate zones.....	16
4.3.4 Additional classification classes	17
5 Metrics for energy efficiency assessment.....	18
5.0 Introduction of clause.....	18
5.1 Energy Consumption and GHG emission metrics.....	18
5.1.1 Energy consumption metrics.....	18
5.1.2 GHG emission metrics.....	20
5.2 Performance metrics.....	21
5.2.1 Data Volume	21
5.2.2 Coverage Area	21
5.2.3 Latency	22
5.2.4 Massive machine type networks	22
5.3 Mobile Network Energy efficiency metrics	22
5.3.1 Mobile Network data Energy Efficiency	22
5.3.2 Mobile Network coverage Energy Efficiency.....	23
5.3.3 Mobile Network latency based Energy Efficiency	23
5.3.4 Mobile Network subscriber Energy Efficiency.....	23
5.3.5 Mobile Network slice Energy Efficiency.....	23
5.3.6 Mobile Network Energy Efficiency with quality factors.....	23
6 Measurement of energy efficiency	24
6.0 Introduction of clause.....	24
6.1 Time duration of the measurement.....	24
6.2 Measurement procedures.....	25
6.2.1 Measurement of Energy Consumption	25
6.2.2 Measurement of capacity	25
6.2.3 Determination of coverage area	26
6.2.3.0 Introduction.....	26
6.2.3.1 Geographic coverage area	26
6.2.3.2 Designated coverage area.....	26
6.2.3.3 Coverage quality	26
6.2.4 Measurement of latency.....	28
6.2.5 Measurement of the number of subscribers	29

7	Extrapolation for overall networks	29
7.0	Extrapolation approach.....	29
7.1	Extrapolation method	30
7.1.0	Introduction of extrapolation method	30
7.1.1	Statistical information about Demography	30
7.1.2	Statistical information about Topography.....	30
7.1.3	Statistical information about Climate zones	30
7.2	Extrapolation reporting tables	30
7.2.0	Introduction of extrapolation reporting tables.....	30
7.2.1	Reporting extrapolation based on Demography.....	31
7.2.2	Reporting extrapolation based on Topography	31
7.2.3	Reporting extrapolation based on Climate zones.....	31
8	Assessment report	32
8.0	Introduction of assessment report.....	32
8.1	Report of Network Area under test	32
8.2	Report of sites under test	33
8.3	Report of Site measurement	35
9	Implementation guidelines	35
Annex A (informative): Implementation examples		37
A.1	Implementation examples.....	37
A.2	Examples of reporting data.....	37
History		42

Sample Document

get full document from standards.iteh.ai

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables (European Standard (EN), Technical Specification (TS), Group Specification (GS) or ETSI Standard (ES)) may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This ETSI Standard (ES) has been produced by ETSI Technical Committee Environmental Engineering (EE).

The present document was developed jointly by ETSI TC EE and ITU-T Study Group 5. It will be published respectively by ITU and ETSI as Recommendation ITU-T L.1331 [i.4] and ETSI ES 203 228 (the present document), which are technically-equivalent.

Moreover the present document has been developed in collaboration with 3GPP SA5 and RAN3; GSMA has also given valuable suggestions and contributions.

Modal verbs terminology

In the present document **"shall"**, **"shall not"**, **"should"**, **"should not"**, **"may"**, **"need not"**, **"will"**, **"will not"**, **"can"** and **"cannot"** are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and **"must not"** are **NOT** allowed in ETSI deliverables except when used in direct citation.

Executive summary

The present document aims to provide a better understanding of the energy efficiency of mobile networks. The focus of the present document is on the metrics and methods of assessing energy efficiency in operational networks.

The networks considered are those whose size and scale could be defined by topologic, geographic or demographic boundaries.

The present document explains how to extrapolate the measurements made on partial networks to the level of the total network. Such a simplified approach is proposed as a way of making approximate energy efficiency evaluations at the level of network elements and cannot therefore be considered sufficient for the entire network operation including, for example, transport.

Introduction

The present document deals with the definition of metrics and methods to measure energy performance of Mobile Networks and adopts an approach based on the measurement of such performance on small networks, for feasibility and simplicity purposes. Such simplified approach is proposed for approximate energy efficiency evaluations and cannot be considered as a reference for planning evaluation purposes throughout the network operation process. The same approach was introduced also in ETSI TR 103 117 [i.1]; the measurements in testing laboratories of the efficiency of the Base Stations is the topic treated in ETSI ES 202 706 [i.2].

As the Energy Efficiency is a context-dependent metric, the present document provides the necessary clarification on the network classification (clause 4) and context of the network under assessment, as well as the implementation guidelines (clause 9) for such an assessment.

The present document provides also a method to extrapolate the assessment of energy efficiency to wider networks (clause 7).

The general outcome of the application of the method specified in the present document is based on the "Assessment report" introduced in clause 8. An example of application of the method is also given in annex A.

It is acknowledged that energy efficiency, which is the scope of this recommendation, is only one aspect of environmental sustainability; in addition, sustainability also encompasses social and economic aspects, but they are not in the scope here.

The present document was developed jointly by ETSI TC EE and ITU-T Study Group 5 and published by ITU and ETSI as Recommendation ITU-T L.1331 [i.4] and ETSI Standard ETSI ES 203 228 (the present document) respectively, which are technically equivalent.

get full document from standards.iteh.ai

1 Scope

The present document is aimed at defining the topology and level of analysis to assess the energy efficiency of mobile networks. Within the scope of the present document there is also the focus on the most energy consuming part, which is the radio access part of the mobile networks, and namely there are radio base stations, backhauling systems, radio controllers and other infrastructure radio site equipment. The covered technologies are GSM, UMTS, LTE and 5G New Radio (NR). In particular the present document defines metrics for mobile network energy efficiency and methods for assessing (and measuring) energy efficiency in operational networks. The purpose of the present document is to allow better comprehension of networks energy efficiency, in particular considering the networks' evolution in different periods in time.

Aiming to consider also the slicing approach of the networks from 5G onwards the metrics are extended to the latency of the network itself related to the energy consumed, additionally to the metrics based on traffic and on coverage, already existing for legacy networks and still valid.

The present document deals with both a homogeneous and heterogeneous "network" considering a network whose size and scale could be defined by topologic, geographic or demographic boundaries. For networks defined by topologic boundaries, a possible example of a network covered by the present document consists of a control node (whenever applicable), its supported access nodes as well as the related network elements. Networks could be defined by geographic boundaries, such as city-wide, national or continental networks and could be defined by demographic boundaries, such as urban or rural networks.

The present document applies to the so-called "partial" networks for which a measurement method is also recommended. The present document extends the measurements in partial networks to wider so-called "total" networks energy efficiency estimations (i.e. the network in a geographic area, the network in a whole country, the network of a MNO, etc.).

Terminal (end-user) equipment is outside the scope of the present document and is not considered in the energy efficiency measurement.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found in the [ETSI docbox](#).

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

The following referenced documents are necessary for the application of the present document.

- [1] [ETSI TS 125 104](#): "Universal Mobile Telecommunications System (UMTS); Base Station (BS) radio transmission and reception (FDD) (3GPP TS 25.104)".
- [2] [ETSI TS 136 104](#): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) radio transmission and reception (3GPP TS 36.104)".
- [3] [ETSI TS 132 425 \(V12.0.0\)](#): "LTE; Telecommunication management; Performance Management (PM); Performance measurements Evolved Universal Terrestrial Radio Access Network (E-UTRAN) (3GPP TS 32.425 version 12.0.0 Release 12)".
- [4] [ETSI TS 132 412 \(V11.1.0\)](#): "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; Telecommunication management; Performance Management (PM) Integration Reference Point (IRP); Information Service (IS) (3GPP TS 32.412 version 11.1.0 Release 11)".

- [5] [ETSI TS 123 203 \(V12.7.0\)](#): "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; Policy and charging control architecture (3GPP TS 23.203 version 12.7.0 Release 12)".
- [6] [ETSI TS 136 314](#): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Layer 2 - Measurements (3GPP TS 36.314)".
- [7] [ETSI TS 152 402 \(V11.0.0\)](#): "Digital cellular telecommunications system (Phase 2+); Telecommunication management; Performance Management (PM); Performance measurements - GSM (3GPP TS 52.402 version 11.0.0 Release 11)".
- [8] [ETSI TS 132 405 \(V11.1.1\)](#): "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; Telecommunication management; Performance Management (PM); Performance measurements; Universal Terrestrial Radio Access Network (UTRAN) (3GPP TS 32.405 version 11.1.1 Release 11)".
- [9] [ETSI ES 202 336-12](#): "Environmental Engineering (EE); Monitoring and control interface for infrastructure equipment (power, cooling and building environment systems used in telecommunication networks); Part 12: ICT equipment power, energy and environmental parameters monitoring information model".
- [10] [ISO/IEC 17025:2017](#): "General requirements for the competence of testing and calibration laboratories".
- [11] [ETSI EN 303 471](#): "Environmental Engineering (EE); Energy Efficiency measurement methodology and metrics for Network Function Virtualisation (NFV)".
- [12] [Recommendation ITU-R M.2410](#): "Minimum requirements related to technical performance for IMT-2020 radio interface(s)".
- [13] [ETSI TS 128 554](#): "5G; Management and orchestration; 5G end to end Key Performance Indicators (KPI) (3GPP TS 28.554)".
- [14] [ETSI TS 128 552 \(V16.6.0\)](#): "5G; Management and orchestration; 5G performance measurements (3GPP TS 28.552 version 16.6.0 Release 16)".
- [15] [ETSI TS 128 310](#): "LTE; 5G; Management and orchestration; Energy efficiency of 5G (3GPP TS 28.310)".
- [16] [ETSI TS 132 450](#): "Universal Mobile Telecommunications System (UMTS); LTE; Telecommunication management; Key Performance Indicators (KPI) for Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Definitions (3GPP TS 32.450)".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

The following referenced documents may be useful in implementing an ETSI deliverable or add to the reader's understanding, but are not required for conformance to the present document.

- [i.1] ETSI TR 103 117: "Environmental Engineering (EE); Principles for Mobile Network level energy efficiency".
- [i.2] ETSI ES 202 706 (all parts): "Environmental Engineering (EE); Metrics and measurement method for energy efficiency of wireless access network equipment".
- [i.3] ETSI GS NFV 003: "Network Functions Virtualisation (NFV); Terminology for Main Concepts in NFV".

- [i.4] Recommendation ITU-T L.1331: "Assessment of mobile network energy efficiency".
- [i.5] FAO Soils Portal: "[Harmonized World Soil Database v 1.2](#)".
- [i.6] Jürgen Grieser, René Gommès, Stephen Cofield and Michele Bernardi: "Data sources for FAO worldmaps of Koeppen climatologies and climatic net primary production", 2006.
- [i.7] Recommendation ITU-T L.1350: "Energy efficiency metrics of a base station site".
- [i.8] Recommendation ITU-T L.1351: "Energy efficiency measurement methodology for base station sites".
- [i.9] Recommendation ITU-T L.1450: "Methodologies for the assessment of the environmental impact of the information and communication technology sector".
- [i.10] Recommendation ITU-T L.1333: "Carbon data intensity for network energy performance monitoring".
- [i.11] The Greenhouse Gas protocol: "[A Corporate Accounting and Reporting Standard](#)".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the following terms apply:

backhaul equipment: equipment used to connect base stations to the core network, or to other BSs

Base Station (BS): generic term used for network component which serves one cell or more cells and interfaces the user terminal (through air interface) and a radio access network infrastructure

distributed RBS: BS architecture which contains Remote Radio Heads (RRH) close to the antenna element and a central element connecting BS to network infrastructure

end-to-end latency: time that takes to transfer a given piece of information from a source to a destination, measured at the communication interface, from the moment it is transmitted by the source to the moment it is successfully received at the destination

Energy Efficiency (EE): within ICT and especially for mobile networks, the relation between the useful output (similar to functional unit) and the energy consumption to realize that functionality

NOTE: For an electrical device, the EE is the percentage of total energy input consumed in useful work and not wasted as useless heat.

energy saving feature: feature which contributes to decreasing the energy consumption compared to the case when the feature is not implemented

integrated BS: BS architecture in which all BS elements are located close to each other for example in one or two cabinets

NOTE: The integrated BS architecture may include TMA close to antenna.

Mobile Network (MN): set of equipment from the radio access network or sub-network that are relevant for the assessment of energy efficiency

mobile network coverage energy efficiency: ratio between the area covered by the network in the Mobile Network under investigation and the energy consumption

mobile network data energy efficiency: ratio between the performance indicator based on Data Volume and the energy consumption when assessed during the same time frame

mobile network energy consumption: overall energy consumption of equipment included in the MN under investigation

mobile network energy efficiency: energy efficiency of a mobile network

Mobile Network Operator (MNO): operator that manages one or more mobile networks

mobile network operator penetration ratio: percentage of traffic served by an MNO in the area where it is active

mobile network performance delivered: performance indicator of the MN under investigation, defined as the data volume delivered by the mobile network under investigation during the time frame of the energy consumption assessment

energy consumption: power consumed by a device to achieve an intended application performance

radio access network: telecommunications network in which the access to the network (connection between user terminal and network) is implemented without the use of wires and that is part of GERAN, UTRAN, E-UTRA or 5G NR networks defined by 3GPP

Site Energy Efficiency (SEE): metric used to determine the energy efficiency of a telecommunication site

NOTE: SEE is defined by the ratio of "IT equipment energy" and "Total site energy", which generally includes rectifiers, cooling, storage, security and IT equipment. For datacentres, the "Total site energy" more globally includes building load, powering equipment (e.g. switchgear, Uninterruptible Power Supply (UPS), battery backup), cooling equipment (e.g. chillers, Computer Room Air Conditioning unit (CRAC)) and IT equipment energy.

telecommunication network: network operated under a license granted by a national telecommunications authority, which provides telecommunications between Network Termination Points (NTPs)

Virtualised Network Function (VNF): See ETSI GS NFV 003 [i.3].

3.2 Symbols

Void.

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

3GPP	3G (mobile) Partnership Project
AAOP	Accessibility and Availability Obligation Profile
BH	BackHaul
BS	Base Station
CC	Central Cloud
CoA	Coverage Area
CoA _{des}	designated coverage area as designed by network planning
CoA _{geo}	total geographical area under investigation and within the operator's license agreement
CoA _{Qdes}	quality factor describing how well users are covered within the coverage area
CoA _{MN}	Coverage Area Mobile Network
COP	Coverage Obligation Profile
CRAN	Cloud Radio Access Network
CS	Circuit Switched
CS/PS	Circuit Switched/Packet Switched
DC	Data Center
DCA	Designed Coverage Area
DL	DownLink
DP	Dominant Penetration
DU	Dense Urban
DV	Data Volume
DV _{MN}	Data Volume of the Mobile Network
E2E	End To End
EC	Energy Consumption
EC _{MN}	Energy Consumption of the Mobile Network